CEN

CWA 16926-5

WORKSHOP

February 2020

AGREEMENT

ICS 35.200; 35.240.15; 35.240.40

English version

Extensions for Financial Services (XFS) interface specification Release 3.40 - Part 5: Cash Dispenser Device Class Interface - Programmer's Reference

This CEN Workshop Agreement has been drafted and approved by a Workshop of representatives of interested parties, the constitution of which is indicated in the foreword of this Workshop Agreement.

The formal process followed by the Workshop in the development of this Workshop Agreement has been endorsed by the National Members of CEN but neither the National Members of CEN nor the CEN-CENELEC Management Centre can be held accountable for the technical content of this CEN Workshop Agreement or possible conflicts with standards or legislation.

This CEN Workshop Agreement can in no way be held as being an official standard developed by CEN and its Members.

This CEN Workshop Agreement is publicly available as a reference document from the CEN Members National Standard Bodies.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Table of Contents

European Foreword5			
1.		Introduction	9
	1.1	Background to Release 3.40	9
	1.2	XFS Service-Specific Programming	9
2.		Cash Dispensers	11
3.		References	12
4.		Note Classification	13
5.		Info Commands	
	5.1	WFS_INF_CDM_STATUS	
	5.2	WFS_INF_CDM_CAPABILITIES	
	5.3	WFS_INF_CDM_CASH_UNIT_INFO	
	5.4	WFS_INF_CDM_TELLER_INFO	
	5.5	WFS_INF_CDM_CURRENCY_EXP	
	5.6	WFS_INF_CDM_MIX_TYPES	
	5.7	WFS_INF_CDM_MIX_TABLE	
	5.8	WFS_INF_CDM_PRESENT_STATUS	
	5.9	WFS_INF_CDM_GET_ITEM_INFO	
		WFS_INF_CDM_GET_BLACKLIST	
		1 WFS_INF_CDM_GET_ALL_ITEMS_INFO	
	5.12	2 WFS_INF_CDM_GET_CLASSIFICATION_LIST	. 44
6.		Execute Commands	46
	6.1	WFS_CMD_CDM_DENOMINATE	. 46
	6.2	WFS_CMD_CDM_DISPENSE	. 49
	6.3	WFS_CMD_CDM_COUNT	. 53
	6.4	WFS_CMD_CDM_PRESENT	. 56
	6.5	WFS_CMD_CDM_REJECT	. 58
	6.6	WFS_CMD_CDM_RETRACT	. 59
	6.7	WFS_CMD_CDM_OPEN_SHUTTER	. 62
	6.8	WFS_CMD_CDM_CLOSE_SHUTTER	. 63
	6.9	WFS_CMD_CDM_SET_TELLER_INFO	. 64
	6.10	WFS_CMD_CDM_SET_CASH_UNIT_INFO	. 65
	6.11	1 WFS_CMD_CDM_START_EXCHANGE	. 67
	6.12	2 WFS_CMD_CDM_END_EXCHANGE	. 69
	6.13	3 WFS_CMD_CDM_OPEN_SAFE_DOOR	.71
	6.14	4 WFS_CMD_CDM_CALIBRATE_CASH_UNIT	.72
	6.1	5 WFS_CMD_CDM_SET_MIX_TABLE	.74

	6.16	WFS_CMD_CDM_RESET	75
	6.17	WFS_CMD_CDM_TEST_CASH_UNITS	77
	6.18	WFS_CMD_CDM_SET_GUIDANCE_LIGHT	79
	6.19	WFS_CMD_CDM_POWER_SAVE_CONTROL	81
	6.20	WFS_CMD_CDM_PREPARE_DISPENSE	82
	6.21	WFS_CMD_CDM_SET_BLACKLIST	83
	6.22	WFS_CMD_CDM_SYNCHRONIZE_COMMAND	84
	6.23	WFS_CMD_CDM_SET_CLASSIFICATION_LIST	85
7.	E	vents	. 86
		WFS_SRVE_CDM_SAFEDOOROPEN	
	7.2	WFS_SRVE_CDM_SAFEDOORCLOSED	
	7.3	WFS_USRE_CDM_CASHUNITTHRESHOLD	
	7.4	WFS_SRVE_CDM_CASHUNITINFOCHANGED	
	7.5	WFS_SRVE_CDM_TELLERINFOCHANGED	
	7.6	WFS_EXEE_CDM_DELAYEDDISPENSE	91
	7.7	WFS_EXEE_CDM_STARTDISPENSE	
	7.8	WFS_EXEE_CDM_CASHUNITERROR	93
	7.9	WFS_SRVE_CDM_ITEMSTAKEN	94
	7.10	WFS_SRVE_CDM_COUNTS_CHANGED	95
	7.11	WFS_EXEE_CDM_PARTIALDISPENSE	96
	7.12	WFS_EXEE_CDM_SUBDISPENSEOK	97
	7.13	WFS_EXEE_CDM_INCOMPLETEDISPENSE	98
	7.14	WFS_EXEE_CDM_NOTEERROR	99
	7.15	WFS_SRVE_CDM_ITEMSPRESENTED	. 100
	7.16	WFS_SRVE_CDM_MEDIADETECTED	. 101
	7.17	WFS_EXEE_CDM_INPUT_P6	. 102
	7.18	WFS_SRVE_CDM_DEVICEPOSITION	. 103
	7.19	WFS_SRVE_CDM_POWER_SAVE_CHANGE	. 104
	7.20	WFS_EXEE_CDM_INFO_AVAILABLE	. 105
	7.21	WFS_EXEE_CDM_INCOMPLETERETRACT	. 106
	7.22	WFS_SRVE_CDM_SHUTTERSTATUSCHANGED	. 107
8.	S	ub-Dispensing Command Flow	108
9.		Rules for Cash Unit Exchange	
		_	
1(vents Associated with Cash Unit Status Changes	
		One Physical Cash Unit Goes LOW	
		Last Physical Cash Unit Goes LOW	
		One Physical Cash Unit Goes INOP	
	10.4	Last Physical Cash Unit Goes EMPTY	. 115
1	1 N	Iultiple Dispense Command Flow	116

12. C - Header file	118
---------------------	-----

European Foreword

This CEN Workshop Agreement has been developed in accordance with the CEN-CENELEC Guide 29 "CEN/CENELEC Workshop Agreements – The way to rapid consensus" and with the relevant provisions of CEN/CENELEC Internal Regulations – Part 2. It was approved by a Workshop of representatives of interested parties on 2019-10-08, the constitution of which was supported by CEN following several public calls for participation, the first of which was made on 1998-06-24. However, this CEN Workshop Agreement does not necessarily include all relevant stakeholders.

The final text of this CEN Workshop Agreement was provided to CEN for publication on 2019-12-12.

The following organizations and individuals developed and approved this CEN Workshop Agreement:

- ATM Japan LTD
- AURIGA SPA
- BANK OF AMERICA
- CASHWAY TECHNOLOGY
- CHINAL ECTRONIC FINANCIAL EQUIPMENT SYSTEM CO.
- CIMA SPA
- CLEAR2PAY SCOTLAND LIMITED
- DIEBOLD NIXDORF
- EASTERN COMMUNICATIONS CO. LTD EASTCOM
- FINANZ INFORMATIK
- FUJITSU FRONTECH LIMITED
- FUJITSU TECHNOLOGY
- GLORY LTD
- GRG BANKING EQUIPMENT HK CO LTD
- HESS CASH SYSTEMS GMBH & CO. KG
- HITACHI OMRON TS CORP.
- HYOSUNG TNS INC
- JIANGSU GUOGUANG ELECTRONIC INFORMATION TECHNOLOGY
- KAL
- KEBA AG
- NCR FSG
- NEC CORPORATION
- OKI ELECTRIC INDUSTRY SHENZHEN

- OKI ELECTRONIC INDUSTRY CO
- PERTO S/A
- REINER GMBH & CO KG
- SALZBURGER BANKEN SOFTWARE
- SIGMA SPA
- TEB
- ZLJIN FULCRUM TECHNOLOGY CO.

It is possible that some elements of this CEN/CWA may be subject to patent rights. The CEN-CENELEC policy on patent rights is set out in CEN-CENELEC Guide 8 "Guidelines for Implementation of the Common IPR Policy on Patents (and other statutory intellectual property rights based on inventions)". CEN shall not be held responsible for identifying any or all such patent rights.

The Workshop participants have made every effort to ensure the reliability and accuracy of the technical and non-technical content of CWA 16926-5, but this does not guarantee, either explicitly or implicitly, its correctness. Users of CWA 16926-5 should be aware that neither the Workshop participants, nor CEN can be held liable for damages or losses of any kind whatsoever which may arise from its application. Users of CWA 16926-5 do so on their own responsibility and at their own risk.

The CWA is published as a multi-part document, consisting of:

- Part 1: Application Programming Interface (API) Service Provider Interface (SPI) Programmer's Reference
- Part 2: Service Classes Definition Programmer's Reference
- Part 3: Printer and Scanning Device Class Interface Programmer's Reference
- Part 4: Identification Card Device Class Interface Programmer's Reference
- Part 5: Cash Dispenser Device Class Interface Programmer's Reference
- Part 6: PIN Keypad Device Class Interface Programmer's Reference
- Part 7: Check Reader/Scanner Device Class Interface Programmer's Reference
- Part 8: Depository Device Class Interface Programmer's Reference
- Part 9: Text Terminal Unit Device Class Interface Programmer's Reference
- Part 10: Sensors and Indicators Unit Device Class Interface Programmer's Reference
- Part 11: Vendor Dependent Mode Device Class Interface Programmer's Reference
- Part 12: Camera Device Class Interface Programmer's Reference
- Part 13: Alarm Device Class Interface Programmer's Reference
- Part 14: Card Embossing Unit Device Class Interface Programmer's Reference
- Part 15: Cash-In Module Device Class Interface Programmer's Reference
- Part 16: Card Dispenser Device Class Interface Programmer's Reference
- Part 17: Barcode Reader Device Class Interface Programmer's Reference
- Part 18: Item Processing Module Device Class Interface Programmer's Reference
- Part 19: Biometrics Device Class Interface Programmer's Reference
- Parts 20 28: Reserved for future use.
- Parts 29 through 47 constitute an optional addendum to this CWA. They define the integration between the SNMP standard and the set of status and statistical information exported by the Service Providers.
- Part 29: XFS MIB Architecture and SNMP Extensions Programmer's Reference
- Part 30: XFS MIB Device Specific Definitions Printer Device Class

- Part 31: XFS MIB Device Specific Definitions Identification Card Device Class
- Part 32: XFS MIB Device Specific Definitions Cash Dispenser Device Class
- Part 33: XFS MIB Device Specific Definitions PIN Keypad Device Class
- Part 34: XFS MIB Device Specific Definitions Check Reader/Scanner Device Class
- Part 35: XFS MIB Device Specific Definitions Depository Device Class
- Part 36: XFS MIB Device Specific Definitions Text Terminal Unit Device Class
- Part 37: XFS MIB Device Specific Definitions Sensors and Indicators Unit Device Class
- Part 38: XFS MIB Device Specific Definitions Camera Device Class
- Part 39: XFS MIB Device Specific Definitions Alarm Device Class
- Part 40: XFS MIB Device Specific Definitions Card Embossing Unit Class
- Part 41: XFS MIB Device Specific Definitions Cash-In Module Device Class
- Part 42: Reserved for future use.
- Part 43: XFS MIB Device Specific Definitions Vendor Dependent Mode Device Class
- Part 44: XFS MIB Application Management
- Part 45: XFS MIB Device Specific Definitions Card Dispenser Device Class
- Part 46: XFS MIB Device Specific Definitions Barcode Reader Device Class
- Part 47: XFS MIB Device Specific Definitions Item Processing Module Device Class
- Part 48: XFS MIB Device Specific Definitions Biometrics Device Class
- Parts 49 60 are reserved for future use.
- Part 61: Application Programming Interface (API) Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Service Provider Interface (SPI) Programmer's Reference
- Part 62: Printer and Scanning Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference
- Part 63: Identification Card Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference
- Part 64: Cash Dispenser Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference
- Part 65: PIN Keypad Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference
- Part 66: Check Reader/Scanner Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference
- Part 67: Depository Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference
- Part 68: Text Terminal Unit Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference
- Part 69: Sensors and Indicators Unit Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference
- Part 70: Vendor Dependent Mode Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference
- Part 71: Camera Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference
- Part 72: Alarm Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference
- Part 73: Card Embossing Unit Device Class Interface Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) Programmer's Reference

Part 74: Cash-In Module Device Class Interface - Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) - Programmer's Reference

Part 75: Card Dispenser Device Class Interface - Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) - Programmer's Reference

Part 76: Barcode Reader Device Class Interface - Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) - Programmer's Reference

Part 77: Item Processing Module Device Class Interface - Migration from Version 3.30 (CWA 16926) to Version 3.40 (this CWA) - Programmer's Reference

In addition to these Programmer's Reference specifications, the reader of this CWA is also referred to a complementary document, called Release Notes. The Release Notes contain clarifications and explanations on the CWA specifications, which are not requiring functional changes. The current version of the Release Notes is available online from: https://www.cen.eu/work/Sectors/Digital_society/Pages/WSXFS.aspx.

The information in this document represents the Workshop's current views on the issues discussed as of the date of publication. It is provided for informational purposes only and is subject to change without notice. CEN makes no warranty, express or implied, with respect to this document.

1. Introduction

1.1 Background to Release 3.40

The CEN/XFS Workshop aims to promote a clear and unambiguous specification defining a multi-vendor software interface to financial peripheral devices. The XFS (eXtensions for Financial Services) specifications are developed within the CEN (European Committee for Standardization/Information Society Standardization System) Workshop environment. CEN Workshops aim to arrive at a European consensus on an issue that can be published as a CEN Workshop Agreement (CWA).

The CEN/XFS Workshop encourages the participation of both banks and vendors in the deliberations required to create an industry standard. The CEN/XFS Workshop achieves its goals by focused sub-groups working electronically and meeting quarterly.

Release 3.40 of the XFS specification is based on a C API and is delivered with the continued promise for the protection of technical investment for existing applications. This release of the specification extends the functionality and capabilities of the existing devices covered by the specification. Notable enhancements include:

- Common API level based 'Service Information' command to report Service Provider information, data and versioning.
- Common API level based events to report changes in status and invalid parameters.
- Support for Advanced Encryption Standard (AES) in PIN.
- VDM Entry Without Closing XFS Service Providers.
- Addition of a Biometrics device class.
- CDM/CIM Note Classification List handling.
- Support for Derived Unique Key Per Transaction (DUKPT) in PIN.
- Addition of Transaction Start/End commands.
- Addition of explicit CIM Prepare/Present commands.

1.2 XFS Service-Specific Programming

The service classes are defined by their service-specific commands and the associated data structures, error codes, messages, etc. These commands are used to request functions that are specific to one or more classes of Service Providers, but not all of them, and therefore are not included in the common API for basic or administration functions.

When a service-specific command is common among two or more classes of Service Providers, the syntax of the command is as similar as possible across all services, since a major objective of XFS is to standardize function codes and structures for the broadest variety of services. For example, using the **WFSExecute** function, the commands to read data from various services are as similar as possible to each other in their syntax and data structures.

In general, the specific command set for a service class is defined as a superset of the specific capabilities likely to be provided by the developers of the services of that class; thus any particular device will normally support only a subset of the defined command set.

There are three cases in which a Service Provider may receive a service-specific command that it does not support:

The requested capability is defined for the class of Service Providers by the XFS specification, the particular vendor implementation of that service does not support it, and the unsupported capability is *not* considered to be fundamental to the service. In this case, the Service Provider returns a successful completion, but does no operation. An example would be a request from an application to turn on a control indicator on a passbook printer; the Service Provider recognizes the command, but since the passbook printer it is managing does not include that indicator, the Service Provider does no operation and returns a successful completion to the application.

The requested capability is defined for the class of Service Providers by the XFS specification, the particular vendor implementation of that service does not support it, and the unsupported capability *is* considered to be fundamental to the service. In this case, a WFS_ERR_UNSUPP_COMMAND error for Execute commands or

WFS_ERR_UNSUPP_CATEGORY error for Info commands is returned to the calling application. An example would be a request from an application to a cash dispenser to retract items where the dispenser hardware does not have that capability; the Service Provider recognizes the command but, since the cash dispenser it is managing is unable to fulfil the request, returns this error.

The requested capability is *not* defined for the class of Service Providers by the XFS specification. In this case, a WFS_ERR_INVALID_COMMAND for Execute commands or WFS_ERR_INVALID_CATEGORY error for Info commands error is returned to the calling application.

This design allows implementation of applications that can be used with a range of services that provide differing subsets of the functionalities that are defined for their service class. Applications may use the **WFSGetInfo** and **WFSAsyncGetInfo** commands to inquire about the capabilities of the service they are about to use, and modify their behavior accordingly, or they may use functions and then deal with error returns to make decisions as to how to use the service.

2. Cash Dispensers

This specification describes the functionality of an XFS compliant Cash Dispenser Module (CDM) Service Provider. It defines the service-specific commands that can be issued to the Service Provider using the WFSGetInfo, WFSAsyncGetInfo, WFSExecute and WFSAsyncExecute functions.

Persistent values are maintained through power failures, open sessions, close session and system resets.

This specification covers the dispensing of items. An "item" is defined as any media that can be dispensed and includes coupons, documents, bills and coins. However, if coins and bills are both to be dispensed separate Service Providers must be implemented for each.

All currency parameters in this specification are expressed as a quantity of minimum dispense units, as defined in the description of the WFS INF CDM CURRENCY EXP command.

There are two types of CDM: Self-Service CDM and Teller CDM. A Self-Service CDM operates in an automated environment, while a Teller CDM has an operator present. The functionality provided by the following commands is only applicable to a Teller CDM:

```
WFS_CMD_CDM_SET_TELLER_INFO WFS_INF_CDM_TELLER_INFO
```

It is possible for the CDM to be part of a compound device with the Cash-In Module (CIM). This CIM\CDM combination is referred to throughout this specification as a "Cash Recycler". For details of the CIM interface see [Ref. 3].

If the device is a Cash Recycler then, if cash unit exchanges are required on both interfaces, the exchanges cannot be performed concurrently. An exchange on one interface must be complete (the

WFS_CMD_CDM_END_EXCHANGE must have completed) before an exchange can start on the other interface. The WFS_ERR_CDM_EXCHANGEACTIVE error code will be returned if the correct sequence is not adhered to.

The CIM interface can be used for all exchange operations on recycle devices, and the CIM interface should be used if the device has recycle units of multiple currencies and/or denominations (including multiple note identifiers associated with the same denomination).

The event WFS_SRVE_CDM_COUNTS_CHANGED will be posted if an operation on the CIM interface affects the cash unit counts which are available through the CDM interface.

The following commands on the CIM interface may affect the CDM counts:

WFS_CMD_CIM_CASH_IN
WFS_CMD_CIM_CASH_IN_END
WFS_CMD_CIM_CASH_IN_ROLLBACK
WFS_CMD_CIM_RETRACT
WFS_CMD_CIM_SET_CASH_IN_UNIT_INFO
WFS_CMD_CIM_END_EXCHANGE
WFS_CMD_CIM_RESET
WFS_CMD_CIM_REPLENISH
WFS_CMD_CIM_CASH_UNIT_COUNT

3. References

- 1. XFS Application Programming Interface (API)/Service Provider Interface (SPI), Programmer's Reference, Revision 3.40
- 2. ISO 4217 at http://www.iso.org
- 3. XFS Cash-In Module Device Class Interface, Programmer's Reference, Revision 3.40

4. Note Classification

Notes are classified by the XFS CDM specification according to the following definitions:

- 1. Level 1 Note is not recognized.
- 2. Level 2 Recognized counterfeit note.
- 3. Level 3 Suspected counterfeit note.
- 4. Level 4 Recognized note that is identified as genuine. This includes notes which are fit or unfit for recycling.

This definition allows support for legislative note handling standards that may exist in various countries and economic regions. Local requirements or device capability may dictate that notes are not classified as level 2 and level 3 and therefore counterfeit or suspect notes would be classified as level 1; the P6 string reported by WFS INF CIM CAPABILITIES *lpszExtra* reports whether notes are classified into all 4 levels.

The above classification levels can be used to support note handling functionality which includes:

- 1. The ability to remove counterfeit notes from circulation.
- 2. Reporting of unrecognized, recognized counterfeit and suspected counterfeit notes.
- 3. Creating and reporting of note signatures in order to allow back-tracing of notes.

A note's classification can be changed based on the note's serial number, currency and value by specifying a blacklist or classification list. A blacklist reclassifies a matching note as level 2, whereas a classification list can be used to re-classify a matching note to a lower level, including classifying a genuine note as unfit for dispensing. Once reclassified, the note will be automatically handled according to the local country specific note handling standard or legislation. Any reclassification will result in the normal events and behavior, for example a WFS_EXEE_CDM_INFO_AVAILABLE event will reflect the note's reclassification. Reclassification can be used to make dynamic changes to note handling procedures without a software upgrade, enabling functionality such as taking older notes out of circulation or handling of counterfeit notes on a local basis.

Reclassification cannot be used to change a note's classification to a higher level, for example, a note recognized as counterfeit by the device cannot be reclassified as genuine. In addition, it is not possible to re-classify a level 2 note as level 1. No particular use case has been identified for reclassifying Level 3 and 4 notes as level 1, but there is no reason to restrict this reclassification.

Blacklists can be specified using WFS_CMD_CDM_SET_BLACKLIST and retrieved using WFS_INF_CDM_GET_BLACKLIST. Classification lists can be specified using

WFS CMD CDM SET CLASSIFICATION LIST and retrieved using

WFS_INF_CDM_GET_CLASSIFICATION_LIST. A classification list is a superset of the blacklist; any items specified as level 2 in the classification list are considered part of the blacklist. However, it is not recommended that both sets of commands are used by a single application, as it may lead to overlap and confusion.

The blacklist or classification list functionality can use a mask to specify serial numbers. The mask is defined as follows: A '?' character (0x003F) is the wildcard used to match a single Unicode character, and a '*' character (0x002A) is the wildcard used to match one or more Unicode characters.

For example, "S8H9??16?4" would represent a match for the serial numbers "S8H9231654" and "S8H9761684". A mask of "HD90*2" would be used in order to match serial numbers that begin with "HD90" and end with "2", for example "HD9028882", "HD9083276112". Note that the mask can only use one asterisk, and if a real character is required then it must be preceded by a backslash, for example: '\\' for a backslash, '*' for an asterisk or '\?' for a question mark.

Note that this flexibility means that it is possible to overlap definitions, for example "HD90*" and "HD902*" would both match on the serial number HD9028882".

5. Info Commands

5.1 WFS_INF_CDM_STATUS

Description This command is used to obtain the status of the CDM. It may also return vendor-specific status

information.

Input Param None.

Output Param LPWFSCDMSTATUS lpStatus;

```
typedef struct _wfs_cdm_status
     WORD
                                fwDevice;
     WORD
                                fwSafeDoor;
     WORD
                                fwDispenser;
     WORD
                                fwIntermediateStacker;
     LPWFSCDMOUTPOS
                                *lppPositions;
                                lpszExtra;
     LPSTR
     DWORD
                                dwGuidLights[WFS CDM GUIDLIGHTS SIZE];
     WORD
                                wDevicePosition;
     USHORT
                                usPowerSaveRecoveryTime;
                                wAntiFraudModule;
     WORD
     } WFSCDMSTATUS, *LPWFSCDMSTATUS;
```

fwDevice

Supplies the state of the CDM. However, an *fwDevice* status of WFS_CDM_DEVONLINE does not necessarily imply that dispensing can take place: the value of the *fwDispenser* field must be taken into account and - for some vendors - the state of the safe door (*fwSafeDoor*) may also be relevant. The state of the CDM will have one of the following values:

Value	Meaning
WFS_CDM_DEVONLINE	The device is online. This is returned when
	the dispenser is present and operational.
WFS_CDM_DEVOFFLINE	The device is offline (e.g. the operator has
	taken the device offline by turning a switch).
WFS_CDM_DEVPOWEROFF	The device is powered off or physically not
	connected.
WFS_CDM_DEVNODEVICE	The device is not intended to be there, e.g.
	this type of self service machine does not
	contain such a device or it is internally not
	configured.
WFS_CDM_DEVHWERROR	The device is inoperable due to a hardware
	error.
WFS_CDM_DEVUSERERROR	The device is present but a person is
	preventing proper device operation.
WFS_CDM_DEVBUSY	The device is busy and unable to process an
	execute command at this time.
WFS_CDM_DEVFRAUDATTEMPT	The device is present but is inoperable
	because it has detected a fraud attempt.
WFS_CDM_DEVPOTENTIALFRAUD	The device has detected a potential fraud
	attempt and is capable of remaining in
	service. In this case the application should
	make the decision as to whether to take the
	device offline.

fwSafeDoor

Supplies the state of the safe door as one of the following values:

Value	Meaning
WFS_CDM_DOORNOTSUPPORTED	Physical device has no safe door or safe door
	state reporting is not supported.
WFS_CDM_DOOROPEN	Safe door is open.
WFS_CDM_DOORCLOSED	Safe door is closed.

WFS_CDM_DOORUNKNOWN

Due to a hardware error or other condition, the state of the safe door cannot be determined.

fwDispenser

Supplies the state of the dispenser's logical cash units as one of the following values:

Value	Meaning
WFS_CDM_DISPOK	All cash units present are in a good state.
WFS_CDM_DISPCUSTATE	One or more of the cash units is in a low, empty, inoperative or manipulated condition.
	Items can still be dispensed from at least one of the cash units.
WFS_CDM_DISPCUSTOP	Due to a cash unit failure dispensing is
	impossible. No items can be dispensed
	because all of the cash units are in an empty,
	inoperative or manipulated condition. This
	state may also occur when a reject/retract
	cash unit is full or no reject/retract cash unit
	is present, or when an application lock is set on every cash unit which can be locked.
WFS_CDM_DISPCUUNKNOWN	Due to a hardware error or other condition, the state of the cash units cannot be determined.

fwIntermediateStacker

Supplies the state of the intermediate stacker. These bills are typically present on the intermediate stacker as a result of a retract operation or because a dispense has been performed without a subsequent present. Possible values for this field are:

Value	Meaning
WFS_CDM_ISEMPTY	The intermediate stacker is empty.
WFS_CDM_ISNOTEMPTY	The intermediate stacker is not empty. The items have not been in customer access.
WFS_CDM_ISNOTEMPTYCUST	The intermediate stacker is not empty. The items have been in customer access. If the device is a recycler then the items on the intermediate stacker may be there as a result of a previous cash-in operation.
WFS_CDM_ISNOTEMPTYUNK	The intermediate stacker is not empty. It is not known if the items have been in customer access.
WFS_CDM_ISUNKNOWN	Due to a hardware error or other condition, the state of the intermediate stacker cannot be determined.
WFS_CDM_ISNOTSUPPORTED	The physical device has no intermediate stacker.

lppPositions

Pointer to a NULL-terminated array of pointers to WFSCDMOUTPOS structures. There is one structure for each position to which items can be dispensed or presented:

fwPosition

Supplies the output position as one of the following values:

Value	Meaning
WFS CDM POSLEFT	Left output position.

WFS_CDM_POSRIGHT	Right output position.
WFS_CDM_POSCENTER	Center output position.
WFS_CDM_POSTOP	Top output position.
WFS_CDM_POSBOTTOM	Bottom output position.
WFS_CDM_POSFRONT	Front output position.
WFS CDM POSREAR	Rear output position.

fwShutter

Supplies the state of the shutter as one of the following values:

Value	Meaning
WFS_CDM_SHTCLOSED	The shutter is operational and is closed.
WFS_CDM_SHTOPEN	The shutter is operational and is open.
WFS_CDM_SHTJAMMED	The shutter is jammed and is not
	operational. The field
	fwJammedShutterPosition provides the
	positional state of the shutter.
WFS_CDM_SHTUNKNOWN	Due to a hardware error or other
	condition, the state of the shutter cannot
	be determined.
WFS_CDM_SHTNOTSUPPORTED	The physical device has no shutter or
	shutter state reporting is not supported.

fwPositionStatus

Returns information regarding items which may be at the output position. If the device is a recycler it is possible that the output position will not be empty due to a previous cash-in operation. The possible values of this field are:

Value	Meaning
WFS_CDM_PSEMPTY	The output position is empty.
WFS_CDM_PSNOTEMPTY	The output position is not empty.
WFS_CDM_PSUNKNOWN	Due to a hardware error or other
	condition, the state of the output position cannot be determined.
WFS_CDM_PSNOTSUPPORTED	The device is not capable of reporting whether or not items are at the output position.

fwTransport

Supplies the state of the transport mechanism as one of the following values. The transport is defined as any area leading to or from the position:

Value	Meaning
WFS_CDM_TPOK	The transport is in a good state.
WFS_CDM_TPINOP	The transport is inoperative due to a
	hardware failure or media jam.
WFS_CDM_TPUNKNOWN	Due to a hardware error or other
	condition the state of the transport cannot
	be determined.
WFS_CDM_TPNOTSUPPORTED	The physical device has no transport or transport state reporting is not supported.

fwTransportStatus

Returns information regarding items which may be on the transport. If the device is a recycler device it is possible that the transport will not be empty due to a previous cash-in operation. The possible values of this field are:

Value	Meaning
WFS_CDM_TPSTATEMPTY	The transport is empty.
WFS_CDM_TPSTATNOTEMPTY	The transport is not empty.
WFS_CDM_TPSTATNOTEMPTYCUST	Items which a customer has had access to are on the transport.
WFS_CDM_TPSTATNOTEMPTY_UNK	Due to a hardware error or other condition it is not known whether there are items on the transport.

WFS CDM TPSTATNOTSUPPORTED

The device is not capable of reporting whether items are on the transport.

fwJammedShutterPosition

Returns information regarding the position of the jammed shutter. The possible values of this field are:

Value	Meaning
WFS_CDM_SHUTTERPOS_NOTSUPPORTED	The physical device has no shutter or
	the reporting of the position of a
	jammed shutter is not supported.
WFS_CDM_SHUTTERPOS_NOTJAMMED	The shutter is not jammed.
WFS_CDM_SHUTTERPOS_OPEN	The shutter is jammed, but fully open.
WFS_CDM_SHUTTERPOS_PARTIALLY_OPEN	The shutter is jammed, but partially
	open.
WFS_CDM_SHUTTERPOS_CLOSED	The shutter is jammed, but fully
	closed.
WFS_CDM_SHUTTERPOS_UNKNOWN	The position of the shutter is
	unknown.

lpszExtra

Pointer to a list of vendor-specific, or any other extended, information. The information is returned as a series of "key=value" strings so that it is easily extensible by Service Providers. Each string is null-terminated, with the final string terminating with two null characters. An empty list may be indicated by either a NULL pointer or a pointer to two consecutive null characters.

dwGuidLights [...]

Specifies the state of the guidance light indicators. The elements of this array can be accessed by using the predefined index values specified for the *dwGuidLights* [] field in the capabilities. Vendor specific guidance lights are defined starting from the end of the array. The maximum guidance light index is WFS CDM GUIDLIGHTS MAX.

Specifies the state of the guidance light indicator as

WFS_CDM_GUIDANCE_NOT_AVAILABLE, WFS_CDM_GUIDANCE_OFF or a combination of the following flags consisting of one type B, optionally one type C and optionally one type D.

Value	Meaning	Type
WFS_CDM_GUIDANCE_NOT_AVAILABLE	The status is not available.	A
WFS_CDM_GUIDANCE_OFF	The light is turned off.	A
WFS_CDM_GUIDANCE_SLOW_FLASH	The light is blinking slowly.	В
WFS_CDM_GUIDANCE_MEDIUM_FLASH	The light is blinking medium	В
	frequency.	
WFS_CDM_GUIDANCE_QUICK_FLASH	The light is blinking quickly.	В
WFS_CDM_GUIDANCE_CONTINUOUS	The light is turned on	В
	continuous (steady).	
WFS_CDM_GUIDANCE_RED	The light is red.	C
WFS_CDM_GUIDANCE_GREEN	The light is green.	C
WFS_CDM_GUIDANCE_YELLOW	The light is yellow.	C
WFS_CDM_GUIDANCE_BLUE	The light is blue.	C
WFS_CDM_GUIDANCE_CYAN	The light is cyan.	C
WFS_CDM_GUIDANCE_MAGENTA	The light is magenta.	C
WFS_CDM_GUIDANCE_WHITE	The light is white.	C
WFS_CDM_GUIDANCE_ENTRY	The light is in the entry state.	D
WFS_CDM_GUIDANCE_EXIT	The light is in the exit state.	D

wDevicePosition

Specifies the device position. The device position value is independent of the *fwDevice* value, e.g. when the device position is reported as WFS_CDM_DEVICENOTINPOSITION, *fwDevice* can have any of the values defined above (including WFS_CDM_DEVONLINE or WFS_CDM_DEVOFFLINE). If the device is not in its normal operating position (i.e. WFS_CDM_DEVICEINPOSITION) then media may not be presented through the normal customer interface. This value is one of the following values:

Value	Meaning
WFS_CDM_DEVICEINPOSITION	The device is in its normal operating position, or is fixed in place and cannot be moved.
WFS_CDM_DEVICENOTINPOSITION	The device has been removed from its normal operating position.
WFS_CDM_DEVICEPOSUNKNOWN	Due to a hardware error or other condition, the position of the device cannot be determined.
WFS_CDM_DEVICEPOSNOTSUPP	The physical device does not have the capability of detecting the position.

usPowerSaveRecoveryTime

Specifies the actual number of seconds required by the device to resume its normal operational state from the current power saving mode. This value is zero if either the power saving mode has not been activated or no power save control is supported.

wAntiFraudModule

Specifies the state of the anti-fraud module as one of the following values:

Value	Meaning
WFS_CDM_AFMNOTSUPP	No anti-fraud module is available.
WFS_CDM_AFMOK	Anti-fraud module is in a good state and no
	foreign device is detected.
WFS_CDM_AFMINOP	Anti-fraud module is inoperable.
WFS_CDM_AFMDEVICEDETECTED	Anti-fraud module detected the presence of a
	foreign device.
WFS_CDM_AFMUNKNOWN	The state of the anti-fraud module cannot be
	determined.

Error Codes

Only the generic error codes defined in [Ref. 1] can be generated by this command.

Comments

Applications which rely on the *lpszExtra* field may not be device or vendor-independent.

In the case where communication with the device has been lost, the *fwDevice* field will report WFS_CDM_DEVPOWEROFF when the device has been removed or WFS_CDM_DEVHWERROR if the communications are unexpectedly lost. All other fields should contain a value based on the following rules and priority:

- 1. Report the value as unknown.
- 2. Report the value as a general h/w error.
- 3. Report the value as the last known value.

WFS INF CDM CAPABILITIES

Description

This command retrieves the capabilities of the CDM. It may also return vendor specific capability information. The intermediate stacker and the transport are treated as separate areas. Some devices may have the capability to move items from the cash units to the intermediate stacker while there are items on the transport. Similarly some devices may be able to retract items to the transport or the cash units while there are items on the intermediate stacker.

Input Param

None.

Output Param LPWFSCDMCAPS lpCaps;

```
typedef struct wfs cdm caps
     WORD
                                 wClass;
                                 fwType;
     WORD
     WORD
                                 wMaxDispenseItems;
     BOOT.
                                 bCompound;
     BOOL
                                 bShutter;
     BOOL
                                 bShutterControl;
     WORD
                                 fwRet.ract.Areas:
     WORD
                                 fwRetractTransportActions;
     WORD
                                 fwRetractStackerActions;
     BOOL
                                 bSafeDoor;
     BOOL
                                 bCashBox;
     BOOL
                                 bIntermediateStacker;
     BOOL
                                 bItemsTakenSensor;
     WORD
                                 fwPositions;
     WORD
                                 fwMoveItems;
     WORD
                                 fwExchangeType;
     LPSTR
                                 lpszExtra;
     DWORD
                                 dwGuidLights[WFS CDM GUIDLIGHTS SIZE];
                                 bPowerSaveControl;
     BOOL
                                 bPrepareDispense;
     BOOL
     BOOL
                                 bAntiFraudModule;
     DWORD
                                 dwItemInfoTypes;
     BOOT.
                                 bBlacklist;
     LPDWORD
                                 lpdwSynchronizableCommands;
     BOOT.
                                 bClassificationList;
     } WFSCDMCAPS, *LPWFSCDMCAPS;
```

wClass

Specifies the logical service class as WFS SERVICE CLASS CDM.

Supplies the type of CDM as one of the following values:

Value	Meaning
WFS_CDM_TELLERBILL	The CDM is a Teller Bill Dispenser.
WFS_CDM_SELFSERVICEBILL	The CDM is a Self-Service Bill Dispenser.
WFS_CDM_TELLERCOIN	The CDM is a Teller Coin Dispenser.
WFS_CDM_SELFSERVICECOIN	The CDM is a Self-Service Coin Dispenser.

wMaxDispenseItems

Supplies the maximum number of items that can be dispensed in a single dispense operation. If no limit applies this value will be zero - in this case, if an attempt is made to dispense more items than the hardware limitations will allow, the Service Provider will implement the dispense as a series of sub-dispense operations (see section Sub-Dispensing Command Flow).

bCompound

Specifies whether the CDM is part of a compound device. If the CDM is part of a compound device with a CIM then this combination can be referred to as a recycler. In this case, no information on cash-in cash units will be supplied via the CDM interface. The CDM interface will however supply information on shared retract or reject cash units and recycle cash units.

bShutter

Specifies whether or not the commands WFS CMD CDM OPEN SHUTTER and WFS CMD CDM CLOSE SHUTTER are supported.

bShutterControl

If set to TRUE the shutter is controlled implicitly by the Service Provider. If set to FALSE the shutter must be controlled explicitly by the application using the

WFS_CMD_CDM_OPEN_SHUTTER and the WFS_CMD_CDM_CLOSE_SHUTTER commands. This field is always set to TRUE if the device has no shutter. This field applies to all shutters and all output positions.

fwRetractAreas

Specifies the area to which items may be retracted. If the device does not have a retract capability this field will be WFS_CDM_RA_NOTSUPP. Otherwise this field will be set to a combination of the following flags:

Value	Meaning
WFS_CDM_RA_RETRACT	The items may be retracted to a retract cash unit.
WFS_CDM_RA_TRANSPORT	The items may be retracted to the transport.
WFS_CDM_RA_STACKER	The items may be retracted to the intermediate stacker.
WFS_CDM_RA_REJECT	The items may be retracted to a reject cash unit.
WFS_CDM_RA_ITEMCASSETTE	The items may be retracted to the item cassettes, i.e. cassettes that can be dispensed from.

fwRetractTransportActions

Specifies the actions which may be performed on items which have been retracted to the transport. If the device does not have the capability to retract items to the transport or move items from the transport this value will be WFS_CDM_NOTSUPP. This field will be a combination of the following flags:

Value	Meaning
WFS_CDM_PRESENT	The items may be presented.
WFS_CDM_RETRACT	The items may be moved to a retract cash unit.
WFS_CDM_REJECT	The items may be moved to a reject bin.
WFS_CDM_ITEMCASSETTE	The items may be moved to the item cassettes, i.e. cassettes that can be dispensed from.

fwRetractStackerActions

Specifies the actions which may be performed on items which have been retracted to the stacker. If the device does not have the capability to retract items to the stacker or move items from the stacker this value will be WFS_CDM_NOTSUPP. Otherwise it will be a combination of the following flags:

Value	Meaning
WFS_CDM_PRESENT	The items may be presented.
WFS_CDM_RETRACT	The items may be moved to a retract cash unit.
WFS_CDM_REJECT WFS_CDM_ITEMCASSETTE	The items may be moved to a reject bin. The items may be moved to the item cassettes, i.e. cassettes that can be dispensed from.

bSafeDoor

Specifies whether or not the WFS_CMD_CDM_OPEN_SAFE_DOOR command is supported.

bCashBox

This field is only applicable to CDM types WFS_CDM_TELLERBILL and WFS_CDM_TELLERCOIN. It specifies whether or not tellers have been assigned a cash box.

bIntermediateStacker

Specifies whether or not the CDM supports stacking items to an intermediate position before the items are moved to the exit position. If this value is TRUE, the field *bPresent* of the WFS CMD CDM DISPENSE command can be set to FALSE.

bItemsTakenSensor

Specifies whether the CDM can detect when items at the exit position are taken by the user. If set to TRUE the Service Provider generates an accompanying WFS_SRVE_CDM_ITEMSTAKEN event. If set to FALSE this event is not generated. This field applies to all output positions.

fwPositions

Specifies the CDM output positions which are available as a combination of the following flags:

Value	Meaning
WFS_CDM_POSLEFT	The CDM has a left output position.
WFS_CDM_POSRIGHT	The CDM has a right output position.
WFS_CDM_POSCENTER	The CDM has a center output position.
WFS_CDM_POSTOP	The CDM has a top output position.
WFS_CDM_POSBOTTOM	The CDM has a bottom output position.
WFS_CDM_POSFRONT	The CDM has a front output position.
WFS_CDM_POSREAR	The CDM has a rear output position.

fwMoveItems

Specifies the CDM move item options which are available as a combination of the following flags:

Value	Meaning
WFS_CDM_FROMCU	The CDM can dispense items from the cash units to the intermediate stacker while there are items on the transport.
WFS_CDM_TOCU	The CDM can retract items to the cash units while there are items on the intermediate stacker.
WFS_CDM_TOTRANSPORT	The CDM can retract items to the transport while there are items on the intermediate stacker.
WFS_CDM_TOSTACKER	The CDM can dispense items from the cash units to the intermediate stacker while there are already items on the intermediate stacker that have not been in customer access. Items remaining on the stacker from a previous dispense may first need to be rejected explicitly by the application if they are not to be presented.

fwExchangeType

Specifies the type of cash unit exchange operations supported by the CDM as a combination of the following flags:

Value	Meaning
WFS_CDM_EXBYHAND	The CDM supports manual replenishment
	either by filling the cash unit by hand or by
	replacing the cash unit.
WFS_CDM_EXTOCASSETTES	The CDM supports moving items from the
	replenishment cash unit to another cash unit.

lpszExtra

Pointer to a list of vendor-specific, or any other extended, information. The information is returned as a series of "key=value" strings so that it is easily extensible by Service Providers. Each string is null-terminated, with the final string terminating with two null characters. An empty list may be indicated by either a NULL pointer or a pointer to two consecutive null characters.

dwGuidLights [...]

Specifies which guidance lights are available. A number of guidance light positions are defined below. Vendor specific guidance lights are defined starting from the end of the array. The maximum guidance light index is WFS CDM GUIDLIGHTS MAX.

In addition to supporting specific flash rates and colors, some guidance lights also have the capability to show directional movement representing "entry" and "exit". The "entry" state gives the impression of leading a user to place media into the device .The "exit" state gives the impression of ejection from a device to a user and would be used for retrieving media from the device.

The elements of this array are specified as a combination of the following flags and indicate all of the possible flash rates (type B) colors (type C) and directions (type D) that the guidance light indicator is capable of handling. If the guidance light indicator only supports one color then no value of type C is returned. If the guidance light indicator does not support direction then no value of type D is returned. A value of WFS_CDM_GUIDANCE_NOT_AVAILABLE indicates that the device has no guidance light indicator or the device controls the light directly with no application control possible.

Value	Meaning	Type
WFS_CDM_GUIDANCE_NOT_AVAILABLE	There is no guidance light control	A
	available at this position.	
WFS_CDM_GUIDANCE_OFF	The light can be off.	В
WFS_CDM_GUIDANCE_SLOW_FLASH	The light can blink slowly.	В
WFS_CDM_GUIDANCE_MEDIUM_FLASH	The light can blink medium	В
	frequency.	
WFS_CDM_GUIDANCE_QUICK_FLASH	The light can blink quickly.	В
WFS_CDM_GUIDANCE_CONTINUOUS	The light can be	В
	continuous (steady).	
WFS_CDM_GUIDANCE_RED	The light can be red.	C
WFS_CDM_GUIDANCE_GREEN	The light can be green.	C
WFS_CDM_GUIDANCE_YELLOW	The light can be yellow.	C
WFS_CDM_GUIDANCE_BLUE	The light can be blue.	C
WFS_CDM_GUIDANCE_CYAN	The light can be cyan.	C
WFS_CDM_GUIDANCE_MAGENTA	The light can be magenta.	C
WFS_CDM_GUIDANCE_WHITE	The light can be white.	C
WFS_CDM_GUIDANCE_ENTRY	The light is in the entry state.	D
WFS_CDM_GUIDANCE_EXIT	The light can be in the exit state.	D

Each array index represents an output position in the CDM. The elements are accessed using the following definitions for the index value:

Value	Meaning
WFS_CDM_GUIDANCE_POSOUTNULL	The default output position.
WFS_CDM_GUIDANCE_POSOUTLEFT	Left output position.
WFS_CDM_GUIDANCE_POSOUTRIGHT	Right output position.
WFS_CDM_GUIDANCE_POSOUTCENTER	Center output position.
WFS_CDM_GUIDANCE_POSOUTTOP	Top output position.
WFS_CDM_GUIDANCE_POSOUTBOTTOM	Bottom output position.
WFS_CDM_GUIDANCE_POSOUTFRONT	Front output position.
WFS_CDM_GUIDANCE_POSOUTREAR	Rear output position.

bPowerSaveControl

Specifies whether power saving control is available. This can either be TRUE if available or FALSE if not available.

bPrepareDispense

On some hardware it can take a significant amount of time for the dispenser to get ready to dispense media. On this type of hardware the WFS_CMD_CDM_PREPARE_DISPENSE command can be used to improve transaction performance. This flag indicates if the hardware requires the application to use the WFS_CMD_CDM_PREPARE_DISPENSE command to maximize transaction performance. If this flag is TRUE then the

WFS_CMD_CDM_PREPARE_DISPENSE command is supported and can be used to improve transaction performance. If this flag is FALSE then the

WFS CMD CDM PREPARE DISPENSE command is not supported.

bAntiFraudModule

Specifies whether the anti-fraud module is available. This can either be TRUE if available or FALSE if not available.

dwItemInfoTypes

Specifies the types of information that can be retrieved through the

WFS INF CDM GET ITEM INFO command as a combination of the following flags:

Value	Meaning
WFS_CDM_ITEM_SERIALNUMBER	Serial Number of the item.
WFS_CDM_ITEM_SIGNATURE	Signature of the item.
WFS CDM ITEM IMAGEFILE	Image file of the item.

bBlacklist

Specifies whether the device has the capability to maintain a blacklist of serial numbers as well as supporting the associated operations. This can either be TRUE if the device has the capability or FALSE if it does not.

lpdwSynchronizableCommands

Pointer to a zero-terminated list of DWORDs which contains the execute command IDs that can be synchronized. If no execute command can be synchronized then this parameter will be NULL.

bClassificationList

Specifies whether the device has the capability to maintain a classification list of serial numbers as well as supporting the associated operations. This can either be TRUE if the device has the capability or FALSE if it does not.

Error Codes Only the generic error codes defined in [Ref. 1] can be generated by this command.

Comments Applications which rely on the *lpszExtra* field may not be device or vendor-independent.

5.3 WFS INF CDM CASH UNIT INFO

Description

This command is used to obtain information regarding the status and contents of the cash units in the CDM.

Where a logical cash unit is configured but there is no corresponding physical cash unit currently present in the device, information about the missing cash unit will still be returned in the *lppList* field of the output parameter. The status of the cash unit will be reported as WFS CDM STATCUMISSING.

It is possible that one logical cash unit may be associated with more than one physical cash unit. In this case, the number of cash unit structures returned in *lpCashUnitInfo* will reflect the number of logical cash units in the CDM. That is, if a system contains four physical cash units but two of these are treated as one logical cash unit, *lpCashUnitInfo* will contain information about the three logical cash units and a *usCount* of 3. Information about the physical cash unit(s) associated with a logical cash unit is contained in the WFSCDMCASHUNIT structure representing the logical cash unit.

It is also possible that multiple logical cash units may be associated with one physical cash unit. This should only occur if the physical cash unit is capable of handling this situation, i.e. if it can store multiple denominations and report meaningful count and replenishment information for each denomination or if it can store retracted and rejected items as separate logical units and report meaningful count and replenishment information for each of them. In this case the information returned in *lpCashUnitInfo* will again reflect the number of logical cash units in the CDM.

Logical Types

A cash unit may have a logical type. A logical type is based on the value of the following fields of the WFSCDMCASHUNIT structure:

lpszCashUnitName usType cCurrencyID ulValues

A logical type of cash unit may be associated with more than one physical cash unit. The logical type is distinct from the logical number (*usNumber*), i.e. *usNumber* does not refer to the logical cassette type.

Counts

Item counts are typically based on software counts and therefore may not represent the actual number of items in the cash unit. Persistent values are maintained through power failures, open sessions, close session and system resets. If a cash unit is shared between the CDM and CIM device class, then CDM operations will result in count changes in the CIM cash unit structure and vice versa. All counts are reported consistently on both interfaces at all times.

On cash units that dispense items, if *ulCount* (on logical and physical cash units) reaches zero it will not decrement further but will remain at zero. When *ulCount* reaches zero no further dispense or denominate operations will be possible using that cash unit, unless the Service Provider provides a configuration option to continue using cash units when *ulCount* reaches zero. The default setting for any such configuration parameter must be to stop using the cash unit when this value reaches zero. If the Service Provider is configured such that the cash unit can still be used when *ulCount* reaches zero then WFS_CDM_STATCUEMPTY should not be generated when *ulCount* reaches zero, rather it should be generated when all physical cash units associated with the logical cash unit are physically empty. On recyclers, the Service Provider should not be configured to keep using the cash unit when *ulCount* is zero if the value in *ulCount* is used by any part of the application, as it may not be accurate. However, if the Service Provider is configured to keep using the cash unit when *ulCount* reaches zero, then the number of notes in the cash unit can be determined relative to *ulInitialCount* using *ulDispensedCount*, *ulRetractedCount* and the CIM *ulCashInCount*, e.g. Number of Notes = *ulInitialCount* – *ulDispensedCount* + *ulRetractedCount* + CIM::*ulCashInCount*.

On cash units that dispense items, *ulCount* on logical cash units is decremented when items are in customer access or successfully rejected. Therefore, items which are dispensed from the cash unit then removed from the device for other reasons (such as manual jam clearance) may mean that

ulCount on logical cash units no longer reflects the number of items in the cash unit. The count of items in the cash unit should therefore be determined from other counts, e.g., ulCount on physical cash units or Number of Notes = ulInitialCount - ulDispensedCount + ulRetractedCount +CIM::ulCashInCount (if applicable).

Exchanges

If a physical cash unit is inserted (including removal followed by a reinsertion) when the device is not in the exchange state the usStatus of the physical cash unit will be set to

WFS CDM STATCUMANIP and the values of the physical cash unit prior to its' removal will be returned in any subsequent WFS INF CDM CASH UNIT INFO command. The physical cash unit will not be used in any operation. The application must perform an exchange operation specifying the new values for the physical cash unit in order to recover the situation.

On recycling and retract units the counts and status are consistently reported on both the CDM and CIM interfaces. When a value is changed through an exchange on one interface it is also changed on the other.

Recyclers

The CDM interface does not report cash-in only cash units but does report cash units which are shared with the CIM, i.e. recycling cash units (WFS CDM TYPERECYCLING) and reject/retract cash units (WFS CDM TYPEREJECTCASSETTE /

WFS CDM TYPERETRACTCASSETTE). The CIM interface reports all cash units of all types, including those that can only be used by commands on the CDM interface.

Input Param

None.

Output Param LPWFSCDMCUINFO lpCashUnitInfo;

```
typedef struct _wfs_cdm_cu_info
     USHORT
                                usTellerID;
     USHORT
                                usCount;
     LPWFSCDMCASHUNIT
                                *lppList;
     } WFSCDMCUINFO, *LPWFSCDMCUINFO;
```

usTellerID

This field is not used in this command and is always zero.

Specifies the number of cash unit structures returned.

lppList

Pointer to an array of pointers to WFSCDMCASHUNIT structures:

```
typedef struct wfs cdm cashunit
     USHORT
                                 usNumber:
     USHORT
                                 usType;
     LPSTR
                                 lpszCashUnitName;
     CHAR
                                 cUnitID[5];
     CHAR
                                 cCurrencyID[3];
     ULONG
                                 ulValues;
     ULONG
                                 ulInitialCount;
     ULONG
                                 ulCount;
     ULONG
                                 ulRejectCount;
     ULONG
                                 ulMinimum;
     ULONG
                                 ulMaximum;
     BOOL
                                 bAppLock;
     USHORT
                                 usStatus;
     USHORT
                                 usNumPhysicalCUs;
     LPWFSCDMPHCU
                                 *lppPhysical;
     ULONG
                                 ulDispensedCount;
     III.ONG
                                 ulPresentedCount:
     ULONG
                                 ulRetractedCount;
     } WFSCDMCASHUNIT, *LPWFSCDMCASHUNIT;
```

usNumber

Index number of the cash unit structure. Each structure has a unique logical number starting with a value of one (1) for the first structure, and incrementing by one for each subsequent structure.

usType

Type of cash unit. Possible values are:

Value	Meaning
WFS_CDM_TYPENA	Not applicable. Typically means cash
	unit is missing.
WFS_CDM_TYPEREJECTCASSETTE	Reject cash unit. This type will also
	indicate a combined reject/retract cash unit.
WFS_CDM_TYPEBILLCASSETTE	Cash unit containing bills.
WFS_CDM_TYPECOINCYLINDER	Coin cylinder.
WFS_CDM_TYPECOINDISPENSER	Coin dispenser as a whole unit.
WFS_CDM_TYPERETRACTCASSETTE	Retract cash unit.
WFS_CDM_TYPECOUPON	Cash unit containing coupons or
	advertising material.
WFS_CDM_TYPEDOCUMENT	Cash unit containing documents.
WFS_CDM_TYPEREPCONTAINER	Replenishment container. A cash unit can
	be refilled from a replenishment
	container.
WFS_CDM_TYPERECYCLING	Recycling cash unit. This unit is only
	present when the device is a compound
	device with a CIM.

lpszCashUnitName

A name which helps to identify the logical type of the cash unit. This is especially useful in the case of cash units of type WFS_CDM_TYPEDOCUMENT where different documents can have the same currency and value. For example, travelers checks and bank checks may have the same currency and value but still need to be identifiable as different types of document. Where this value is not relevant (e.g. in bill cash units) the pointer will be NULL. This value is persistent.

cUnitID

The Cash Unit Identifier.

cCurrencyID

A three character array storing the ISO format [Ref. 2] Currency ID. This value will be an array of three ASCII 0x20h characters for cash units which contain items of more than one currency type or items to which currency is not applicable. If the *usStatus* field for this cash unit is WFS_CDM_STATCUNOVAL it is the responsibility of the application to assign a value to this field. This value is persistent.

ulValues

Supplies the value of a single item in the cash unit. This value is expressed in minimum dispense units (see section WFS_INF_CDM_CURRENCY_EXP). If the *cCurrencyID* field for this cash unit is an array of three ASCII 0x20h characters, then this field will contain zero. If the *usStatus* field for this cash unit is WFS_CDM_STATCUNOVAL it is the responsibility of the application to assign a value to this field. This value is persistent.

ulInitialCount

Initial number of items contained in the cash unit. This value is persistent.

ulCount

The meaning of this count depends on the type of cash unit. This value is persistent.

For all cash units except retract cash units (usType is not

WFS_CDM_TYPERETRACTCASSETTE) this value specifies the number of items inside all the physical cash units associated with this cash unit.

For all dispensing cash units (*usType* is WFS_CDM_TYPEBILLCASSETTE, WFS_CDM_TYPECOINCYLINDER, WFS_CDM_TYPECOINDISPENSER, WFS_CDM_TYPECOUPON, WFS_CDM_TYPEDOCUMENT or

WFS_CDM_TYPERECYCLING), this value includes any items from the physical cash units not yet presented to the customer. This count is only decremented when the items are either known to be in customer access or successfully rejected.

If the cash unit is usable from the CIM interface (*usType* is WFS_CDM_TYPERECYCLING, WFS_CDM_TYPERETRACTCASSETTE or WFS_CDM_TYPEREJECTCASSETTE) then this value will be incremented as a result of a cash-in operation.

Note that for a reject cash unit (*usType* is WFS_CDM_TYPEREJECTCASSETTE), this value is unreliable, since the typical reason for dumping items to the reject cash unit is a suspected count failure.

For a retract cash unit (*usType* is WFS_CDM_TYPERETRACTCASSETTE) this value specifies the number of retract operations (CDM commands, CIM commands and error recoveries) which result in items entering the cash unit.

ulRejectCount

The number of items dispensed from this cash unit which have been rejected, are in a cash unit other than this cash unit, and which have not been accessible to a customer. This value may be unreliable, since a typical reason for rejecting items is a suspected pick failure. Other reasons for rejecting items may include incorrect note denominations, classifications not valid for dispensing, or where the transaction has been cancelled and WFS_CMD_CDM_REJECT has been called. For reject and retract cash units (usType is

WFS_CDM_TYPEREJECTCASSETTE or WFS_CDM_TYPERETRACTCASSETTE) this field does not apply and will be reported as zero. This value is persistent.

ulMinimum

This field is not applicable to retract and reject cash units. For all other cash units, when *ulCount* reaches this value the threshold event

WFS_USRE_CDM_CASHUNITTHRESHOLD (WFS_CDM_STATCULOW) will be generated. If this value is non-zero then hardware sensors in the device do not trigger threshold events. If this value is zero then hardware sensors will trigger threshold events if bHardwareSensor is TRUE. This value is persistent.

ulMaximum

This field is only applicable to retract and reject cash units. When *ulCount* reaches this value the threshold event WFS_USRE_CDM_CASHUNITTHRESHOLD

(WFS_CDM_STATCUHIGH) will be generated. If this value is non-zero then hardware sensors in the device do not trigger threshold events. If this value is zero then hardware sensors will trigger threshold events if *bHardwareSensor* is TRUE. This value is persistent.

bAppLock

If this value is TRUE items cannot be dispensed from or deposited into the cash unit. If this value is TRUE and the application attempts to use the cash unit a

WFS_EXEE_CDM_CASHUNITERROR event will be generated and a

WFS_ERR_CDM_CASHUNITERROR code will be returned. This value is persistent.

usStatus

Supplies the status of the cash unit as one of the following values:

Value	Meaning
WFS_CDM_STATCUOK	The cash unit is in a good state.
WFS_CDM_STATCUFULL	The cash unit is full. This value only
	applies to cash units where usType is
	WFS_CDM_TYPEREJECTCASSETTE
	or WFS_CDM_TYPERETRACT-
	CASSETTE.

WFS CDM STATCUHIGH The cash unit is almost full (i.e. reached

> or exceeded the threshold defined by ulMaximum). This value only applies to

cash units where usTvpe is

WFS CDM TYPEREJECTCASSETTE or WFS CDM TYPERETRACT-

CASSETTE.

WFS CDM STATCULOW The cash unit is almost empty (i.e.

> reached or below the threshold defined by *ulMinimum*). This value does not apply to cash units where usTvpe is WFS CDM TYPEREJECTCASSETTE

or WFS CDM TYPERETRACT-

CASSETTE.

The cash unit is empty, or insufficient WFS CDM STATCUEMPTY

> items in the cash unit are preventing further dispense operations. Note that this status is available to all cash unit types, which is a change from previous versions of this specification, therefore service providers may wish to make this a

configurable option.

WFS CDM STATCUINOP The cash unit is inoperative. WFS CDM STATCUMISSING The cash unit is missing.

WFS CDM STATCUNOVAL The values of the specified cash unit are

not available.

There is no reference value available for WFS CDM STATCUNOREF

the notes in this cash unit. The cash unit

has not been calibrated.

WFS CDM STATCUMANIP The cash unit has been inserted

(including removal followed by a reinsertion) when the device was not in the exchange state. This cash unit cannot

be dispensed from.

ulDispensedCount

The number of items dispensed from all the physical cash units associated with this cash unit. This count is incremented when the items are removed from any of the associated physical cash units. This count includes any items that were rejected during the dispense operation and are no longer in this cash unit. This field is always zero for cash units with a usTvpe of WFS CDM TYPEREJECTCASSETTE or WFS CDM TYPERETRACTCASSETTE. This value is persistent.

ulPresentedCount

The number of items from all the physical cash units associated with this cash unit that have been presented to the customer. This count is incremented when the items are presented to the customer. If it is unknown if a customer has been presented with the items, then this count is not updated. This field is always zero for cash units with a usType of

WFS CDM TYPEREJECTCASSETTE or WFS CDM TYPERETRACTCASSETTE. This value is persistent.

ulRetractedCount

The number of items that have been accessible to a customer and retracted into all the physical cash units associated with this cash unit. This value is persistent.

usNumPhysicalCUs

The number of physical cash unit structures returned in the following *lppPhysical* array. This number must be at least 1.

lppPhysical

Pointer to an array of pointers to WFSCDMPHCU structures:

```
typedef struct wfs cdm physicalcu
     LPSTR
                                lpPhysicalPositionName;
     CHAR
                                 cUnitID[5];
                                ulInitialCount;
     ULONG
     ULONG
                                ulCount;
     ULONG
                                ulRejectCount;
     ULONG
                                ulMaximum;
     USHORT
                                usPStatus;
     BOOT
                                bHardwareSensor;
     ULONG
                                ulDispensedCount:
     ULONG
                                ulPresentedCount;
     ULONG
                                ulRetractedCount;
     } WFSCDMPHCU, *LPWFSCDMPHCU;
```

lpPhysicalPositionName

A name identifying the physical location of the cash unit within the CDM. This field can be used by CDMs which are compound with a CIM to identify shared cash units.

cUnitID

A 5 character array uniquely identifying the physical cash unit.

ulInitialCount

Initial number of items contained in the cash unit. This value is persistent.

ulCount

As defined by the logical *ulCount* description but applies to a single physical cash unit, but with the following exceptions:

This count does not include items dispensed but not yet presented.

On cash units belonging to logical cash units with usType set to

WFS_CDM_TYPERETRACTCASSETTE the physical count represents the number of items, unless the device cannot count items during a retract, in which case this count will be zero.

This value is persistent.

ulReiectCount

As defined by the logical *ulRejectCount* description but applies to a single physical cash unit. This value is persistent.

ulMaximum

The maximum number of items the cash unit can hold. This is only for informational purposes. No threshold event WFS_USRE_CDM_CASHUNITTHRESHOLD will be generated. This value is persistent.

usPStatus

Supplies the status of the physical cash unit as one of the following values:

Value	Meaning
WFS_CDM_STATCUOK	The cash unit is in a good state.
WFS_CDM_STATCUFULL	The cash unit is full. This value only applies to cash units where <i>usType</i> is WFS_CDM_TYPEREJECT-CASSETTE or
	WFS_CDM_TYPERETRACT-CASSETTE.
WFS_CDM_STATCUHIGH	The cash unit is almost full (reached or exceeded threshold defined by <i>ulMaximum</i>). This value only applies to cash units where <i>usType</i> is WFS_CDM_TYPEREJECT-CASSETTE or WFS_CDM_TYPERETRACT-CASSETTE.

WFS_CDM_STATCULOW The cash unit is almost empty. This

value does not apply to cash units where *usType* is WFS CDM TYPE-

REJECTCASSETTE or WFS CDM TYPERETRACT-

CASSETTE.

WFS_CDM_STATCUEMPTY The cash unit is empty, or insufficient

items in the cash unit are preventing further dispense operations. Note that this status is available to all cash unit types, which is a change from previous versions of this specification, therefore service providers may wish to make this a

configurable option.

WFS_CDM_STATCUINOP The cash unit is inoperative.
WFS_CDM_STATCUMISSING The cash unit is missing. The cash

unit has been removed and is physically not present in the machine.

WFS CDM STATCUNOVAL

The values of the specified cash unit

are not available.

WFS CDM STATCUNOREF There is no reference value available

for the notes in this cash unit. The cash unit has not been calibrated. The cash unit has been inserted (including removal followed by a

(including removal followed by a reinsertion) when the device was not in the exchange state. This cash unit

cannot be dispensed from.

bHardwareSensor

WFS CDM STATCUMANIP

Specifies whether or not threshold events can be generated based on hardware sensors in the device. If this value is TRUE for any of the physical cash units related to a logical cash unit then threshold events may be generated based on hardware sensors as opposed to logical counts.

ulDispensedCount

As defined by the logical *ulDispensedCount* description but applies to a single physical cash unit. This value is zero if the h/w does not support physical counts. This value is persistent.

ulPresentedCount

As defined by the logical *ulPresentedCount* description but applies to a single physical cash unit. This value is zero if the h/w does not support physical counts. This value is persistent.

ulRetractedCount

As defined by the logical *ulRetractedCount* description but applies to a single physical cash unit. This value is zero if the h/w does not support physical counts. This value is persistent.

Error Codes Only the generic error codes defined in [Ref. 1] can be generated by this command.

Comments None.

5.4 WFS INF CDM TELLER INFO

Description

This command only applies to Teller CDMs. It allows the application to obtain counts for each currency assigned to the teller. These counts represent the total amount of currency dispensed by the teller in all transactions.

This command also enables the application to obtain the position assigned to each teller. If the input parameter is NULL, this command will return information for all tellers and all currencies. The teller information is persistent.

Input Param

LPWFSCDMTELLERINFO lpTellerInfo;

```
typedef struct wfs cdm teller info
     USHORT
                                usTellerID;
     CHAR
                                cCurrencyID[3];
     } WFSCDMTELLERINFO, *LPWFSCDMTELLERINFO;
```

Identification of the teller. If the value of usTellerID is not valid the error WFS ERR CDM INVALIDTELLERID is reported.

cCurrencvID

Three character ISO format currency identifier [Ref 2].

This field can be an array of three ASCII 0x20 characters. In this case information on all currencies will be returned.

Output Param LPWFSCDMTELLERDETAILS *lppTellerDetails;

Pointer to a NULL-terminated array of pointers to WFSCDMTELLERDETAILS structures.

```
typedef struct wfs cdm teller details
     USHORT
                                usTellerID;
     ULONG
                                ulInputPosition;
     WORD
                                fwOutputPosition;
     LPWFSCDMTELLERTOTALS
                                *lppTellerTotals;
     } WFSCDMTELLERDETAILS, *LPWFSCDMTELLERDETAILS;
```

usTellerID

Identification of the teller.

ulInputPosition

The input position assigned to the teller for cash entry. This is only for compatibility except when the device is a compound device. The value is specified by one of the following values:

Value	Meaning
WFS_CDM_POSNULL	No position is assigned to the teller.
WFS_CDM_POSINLEFT	Left position is assigned to the teller.
WFS_CDM_POSINRIGHT	Right position is assigned to the teller.
WFS_CDM_POSINCENTER	Center position is assigned to the teller.
WFS_CDM_POSINTOP	Top position is assigned to the teller.
WFS_CDM_POSINBOTTOM	Bottom position is assigned to the teller.
WFS_CDM_POSINFRONT	Front position is assigned to the teller.
WFS_CDM_POSINREAR	Rear position is assigned to the teller.

fwOutputPosition

The output position from which cash is presented to the teller. The value is specified by one of the following values:

Value	Meaning
WFS_CDM_POSNULL	No position is assigned to the teller.
WFS_CDM_POSLEFT	Left position is assigned to the teller.
WFS_CDM_POSRIGHT	Right position is assigned to the teller.
WFS_CDM_POSCENTER	Center position is assigned to the teller.
WFS_CDM_POSTOP	Top position is assigned to the teller.
WFS_CDM_POSBOTTOM	Bottom position is assigned to the teller.
WFS_CDM_POSFRONT	Front position is assigned to the teller.

WFS_CDM_POSREAR

Rear position is assigned to the teller.

lppTellerTotals

Pointer to a NULL-terminated array of pointers to WFSCDMTELLERTOTALS structures.

```
typedef struct wfs cdm teller totals
     CHAR
                                cCurrencyID[3];
     ULONG
                                ulItemsReceived;
     ULONG
                                ulItemsDispensed;
     ULONG
                                ulCoinsReceived;
     ULONG
                                ulCoinsDispensed;
     ULONG
                                ulCashBoxReceived;
     ULONG
                                ulCashBoxDispensed;
     } WFSCDMTELLERTOTALS, *LPWFSCDMTELLERTOTALS;
```

cCurrencyID

Three character ISO format currency identifier [Ref. 2].

ulItemsReceived

The total amount of items (other than coins) of the specified currency accepted. The amount is expressed in minimum dispense units (see section WFS_INF_CDM_CURRENCY_EXP).

ulItemsDispensed

The total amount of items (other than coins) of the specified currency dispensed. The amount is expressed in minimum dispense units (see section WFS_INF_CDM_CURRENCY_EXP).

ulCoinsReceived

The total amount of coin currency accepted. The amount is expressed in minimum dispense units (see section WFS INF CDM CURRENCY EXP).

ulCoinsDispensed

The total amount of coin currency dispensed. The amount is expressed in minimum dispense units (see section WFS INF CDM CURRENCY EXP).

ulCashBoxReceived

The total amount of cash box currency accepted. The amount is expressed in minimum dispense units (see section WFS INF CDM CURRENCY EXP).

ulCashBoxDispensed

The total amount of cash box currency dispensed. The amount is expressed in minimum dispense units (see section WFS INF CDM CURRENCY EXP).

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_INVALIDCURRENCY	Specified currency not currently available.
WFS_ERR_CDM_INVALIDTELLERID	Invalid teller ID.

Comments

None.

WFS INF CDM CURRENCY EXP

Description This command returns each exponent assigned to each currency known to the Service Provider.

Input Param None.

Output Param

LPWFSCDMCURRENCYEXP *lppCurrencyExp;

Pointer to a NULL-terminated array of pointers to WFSCDMCURRENCYEXP structures:

```
typedef struct wfs cdm currency exp
     {
     CHAR
                                cCurrencyID[3];
     SHORT
                                sExponent;
     } WFSCDMCURRENCYEXP, *LPWFSCDMCURRENCYEXP;
```

cCurrencyID

Currency identifier in ISO 4217 format [Ref 2].

sExponent

Currency exponent in ISO 4217 format [Ref. 2].

Error Codes

Only the generic error codes defined in [Ref. 1] can be generated by this command.

Comments

For each currency ISO 4217 defines the currency identifier (a three character code) and a currency unit (e.g. European Euro, Japanese Yen). In the interface defined by this specification, every money amount is specified in terms of multiples of the minimum dispense unit, which is equal to the currency unit times ten to the power of the currency exponent. Thus an amount parameter relates to the actual cash amount as follows:

<cash amount> = <money amount parameter> * 10^<sExponent>

Example #1 - Euro

Currency identifier is 'EUR'

Currency unit is 1 Euro (= 100 Cent)

A Service Provider is developed for an ATM that can dispense coins down to one Cent. The currency exponent (sExponent) is set to -2 (minus two), so the minimum dispense unit is one Cent (1 * 10^-2 Euro); all amounts at the XFS interface are in Cent. Thus a money amount parameter of 10050 is 100 Euro and 50 Cent.

Example #2 - Japan

Currency identifier is 'JPY'

Currency unit is 1 Japanese Yen

A Service Provider is required to dispense a minimum amount of 1000 Yen. The currency exponent (sExponent) is set to +3 (plus three), so the minimum dispense unit is 1000 Yen; all amounts at the XFS interface are in multiples of 1000 Yen. Thus an amount parameter of 15 is 15000 Yen.

5.6 WFS INF CDM MIX TYPES

Description This command is used to obtain a list of supported mix algorithms and available house mix tables.

Input Param None.

None.

Output Param LP

LPWFSCDMMIXTYPE *lppMixTypes;

Pointer to a NULL-terminated array of pointers to WFSCDMMIXTYPE structures:

usMixNumber

Number identifying the mix algorithm or the house mix table. This number can be passed to the WFS_INF_CDM_MIX_TABLE, WFS_CMD_CDM_DISPENSE and WFS_CMD_CDM_DENOMINATE commands.

usMixType

Specifies whether the mix type is an algorithm or a house mix table. Possible values are:

Value	Meaning
WFS_CDM_MIXALGORITHM	Mix algorithm.
WFS CDM MIXTABLE	Mix table.

usSubType

Contains a vendor-defined number that identifies the type of algorithm. Individual vendor-defined mix algorithms are defined above hexadecimal 7FFF. Mix algorithms which are provided by the Service Provider are in the range hexadecimal 8000 - 8FFF. Application defined mix algorithms start at hexadecimal 9000. All numbers below 8000 hexadecimal are reserved. If *usMixType* is WFS CDM MIXTABLE, this value will be zero. Predefined values are:

Value	Meaning
WFS_CDM_MIX_MINIMUM_NUMBER_OF	BILLS
	Select a mix requiring the minimum possible number of items.
WFS_CDM_MIX_EQUAL_EMPTYING_OF_0	CASH_UNITS
WFS_CDM_MIX_MAXIMUM_NUMBER_OF	The denomination is selected based upon criteria which ensure that over the course of its operation the CDM cash units will empty as far as possible at the same rate and will therefore go LOW and then EMPTY at approximately the same time.

lpszName

Points to the name of the table/algorithm used.

Error Codes Only the generic error codes defined in [Ref. 1] can be generated by this command.

Comments None.

5.7 WFS_INF_CDM_MIX_TABLE

Description This command is used to obtain the house mix table specified by the supplied mix number.

Input Param LPUSHORT lpusMixNumber;

lpusMixNumber

Pointer to the number of the requested house mix table.

Output Param LPWFSCDMMIXTABLE lpMixTable;

```
typedef struct _wfs_cdm_mix_table
     USHORT
                                 usMixNumber:
     LPSTR
                                 lpszName;
     USHORT
                                 usRows;
     USHORT
                                 usCols;
     LPULONG
                                 lpulMixHeader;
     LPWFSCDMMIXROW
                                 *lppMixRows;
     } WFSCDMMIXTABLE, *LPWFSCDMMIXTABLE;
```

usMixNumber

Number identifying the house mix table.

lpszName

Points to the name of the house mix table.

usRows

Number of rows in the house mix table. There is at least one row for each distinct total amount to be denominated. If there is more than one row for an amount the first row is taken that is dispensable according to the current status of the cash units.

usCols

Number of columns in the house mix table. There is one column for each distinct item value included in the mix.

lpulMixHeader

Pointer to an array of length usCols of unsigned longs; each element defines the value of the item corresponding to its respective column (see section WFS INF CDM CURRENCY EXP).

lppMixRows

Pointer to an array (of length usRows) of pointers to WFSCDMMIXROW structures:

```
typedef struct wfs cdm mix row
     {
     ULONG
                                ulAmount;
     LPUSHORT
                                lpusMixture;
     } WFSCDMMIXROW, *LPWFSCDMMIXROW;
```

Amount denominated by this mix row (see section WFS INF CDM CURRENCY EXP).

lpusMixture

Pointer to a mix row, an array of length usCols of USHORTs; each element defines the quantity of each item denomination in the mix used in the denomination of ulAmount.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_INVALIDMIXNUMBER	The <i>lpusMixNumber</i> parameter does not
	correspond to a defined mix table.

Comments None.

5.8 WFS INF CDM PRESENT STATUS

Description

This command is used to obtain the status of the most recent attempt to dispense and/or present items to the customer from a specified output position. The items may have been dispensed and/or presented as a result of the WFS CMD CDM PRESENT or WFS CMD CDM DISPENSE command. This status is not updated as a result of any other command that can dispense/present items.

This value is persistent and is valid until the next time an attempt is made to present or dispense items to the customer.

The denominations reported by this command may not accurately reflect the operation if the cash units have been re-configured (e.g. if the values associated with a cash unit are changed, or new cash units are configured).

Input Param

LPWORD lpfwPosition;

lpfwPosition

Pointer to the required output position as one of the following values:

Value	Meaning
WFS_CDM_POSNULL	The default configuration.
WFS_CDM_POSLEFT	The left output position.
WFS_CDM_POSRIGHT	The right output position.
WFS_CDM_POSCENTER	The center output position.
WFS_CDM_POSTOP	The top output position.
WFS_CDM_POSBOTTOM	The bottom output position.
WFS_CDM_POSFRONT	The front output position.
WFS_CDM_POSREAR	The rear output position.

Output Param LPWFSCDMPRESENTSTATUS lpPresentStatus:

```
typedef struct wfs cdm present status
     LPWFSCDMDENOMINATION
                                lpDenomination;
     WORD
                                wPresentState;
     LPSTR
                                lpszExtra;
     } WFSCDMPRESENTSTATUS, *LPWFSCDMPRESENTSTATUS;
```

lpDenomination

Pointer to a WFSCDMDENOMINATION structure which contains the amount dispensed from the specified output position and the number of items dispensed from each cash unit. For a description of the WFSCDMDENOMINATION structure see the definition of the command WFS CMD CDM DENOMINATE. Where the capability fwMoveItems reports WFS CDM TOSTACKER this value is cumulative across a series of WFS CMD CDM DISPENSE calls that add additional items to the stacker.

Where mixed currencies were dispensed the *ulAmount* field in the returned denomination structure will be zero and the *cCurrencyID* field will be set to three ASCII 0x20 characters.

wPresentState

Supplies the status of the last dispense or present operation. Possible values are:

Value	Meaning
WFS_CDM_PRESENTED	The items were presented. This status is set
	as soon as the customer has access to the
	items.
WFS_CDM_NOTPRESENTED	The customer has not had access to the
	items.
WFS_CDM_UNKNOWN	It is not known if the customer had access to
	the items.

lpszExtra

Pointer to a list of vendor-specific, or any other extended, information. The information is returned as a series of "key=value" strings so that it is easily extensible by Service Providers. Each string is null-terminated, with the final string terminating with two null characters. An empty list may be indicated by either a NULL pointer or a pointer to two consecutive null characters.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_UNSUPPOSITION	The specified output position is not
	supported.

5.9 WFS INF CDM GET ITEM INFO

Description

This command is used to get information about a single detected item. This information is available from the point where the first WFS_EXEE_CDM_INFO_AVAILABLE event is generated until one of the following CDM commands is executed:

WFS_CMD_CDM_DISPENSE, WFS_CMD_CDM_COUNT, WFS_CMD_CDM_PRESENT, WFS_CMD_CDM_RETRACT, WFS_CMD_CDM_REJECT, WFS_CMD_CDM_OPEN_SHUTTER, WFS_CMD_CDM_CLOSE_SHUTTER, WFS_CMD_CDM_RESET, WFS_CMD_CDM_START_EXCHANGE,

WFS_CMD_CDM_END_EXCHANGE, WFS_CMD_CDM_CALIBRATE_CASH_UNIT, WFS_CMD_CDM_TEST_CASH_UNITS.

Additionally for a recycler, the following CIM commands will also invalidate the information:

```
WFS_CMD_CIM_CASH_IN_START, WFS_CMD_CIM_CASH_IN, WFS_CMD_CIM_CASH_IN_ROLLBACK, WFS_CMD_CIM_CASH_IN_END, WFS_CMD_CIM_RETRACT, WFS_CMD_CIM_RESET, WFS_CMD_CIM_START_EXCHANGE, WFS_CMD_CIM_END_EXCHANGE, WFS_CMD_CIM_CREATE_P6_SIGNATURE, WFS_CMD_CIM_REPLENISH, WFS_CMD_CIM_CASH_UNIT_COUNT.
```

This command is used to retrieve the required information on an individual item basis. Applications should loop retrieving the information for each index and for each level reported with the WFS EXEE CDM INFO AVAILABLE event.

Input Param

LPWFSCDMGETITEMINFO lpGetItemInfo;

usLevel

Defines the note level. Possible values are:

Value	Meaning
WFS_CDM_LEVEL_1	Information for level 1 notes. Only an image
	file can be retrieved for level 1 notes.
WFS_CDM_LEVEL_2	Information for level 2 notes. On systems
	that do not classify notes as level 2 this value
	cannot be used and
	WFS_ERR_INVALID_DATA will be
	returned.
WFS_CDM_LEVEL_3	Information for level 3 notes. On systems
	that do not classify notes as level 3 this
	value cannot be used and
	WFS_ERR_INVALID_DATA will be
	returned.
WFS_CDM_LEVEL_4	Information for level 4 notes.

usIndex

Specifies the index for the item information required (zero to *usNumOfItems-1* as reported in the WFS EXEE CDM INFO AVAILABLE event).

dwItemInfoType

Specifies the type of information required. This can be a combination of the following flags:

Value	Meaning
WFS_CDM_ITEM_SERIALNUMBER	Serial number of the item.
WFS_CDM_ITEM_SIGNATURE	Signature of the item.
WFS_CDM_ITEM_IMAGEFILE	Image file of the item.

Output Param LPWFSCDMITEMINFO lpItemInfo;

El Wiscellini I e ipitellini e,

The data returned by this command relates to a single item (usIndex).

cCurrencyID

Currency ID in ISO 4217 format [Ref. 2]. This value will be an array of three ASCII 0x20h characters for level 1 items.

ulValue

The value of a single item expressed in minimum dispense units. This value will be zero for level 1 items.

usRelease

The release of the banknote type. The higher this number is, the newer the release. Zero means that there is only one release of that banknote type. This value has not been standardized and therefore a release number of the same banknote will not necessarily have the same value in different systems. This value will be zero for level 1 items.

lpszSerialNumber

This field contains the serial number of the item as a Unicode string. A '?' character (0x003F) is used to represent any serial number character that cannot be recognized. If no serial number is available or has not been requested then *lpszSerialNumber* is NULL.

lpSignature

This field contains the signature for the item. If no signature is available or has not been requested then this field is NULL.

lpszImageFileName

Name of the file where the image containing the item's serial number is stored, e.g. "C:\Temp\cash123456.jpg". If the Service Provider does not support this function or the image file has not been requested then *lpszImageFileName* is NULL.

The application is responsible for the use and management of this file. For example, the application can transfer the image files to a directory which is managed by the application.

Error Codes

Only the generic error codes defined in [Ref. 1] can be generated by this command.

Comments

The application has to call this command multiple times in a loop where there is multiple information to retrieve. In addition, since the item information is not cumulative and can be replaced by any command that can move notes, it is recommended that applications that are interested in the available information should query for it following the

WFS_EXEE_CDM_INFO_AVAILABLE event but before any other command is executed.

5.10 WFS INF CDM GET BLACKLIST

Description

This command is used to retrieve the entire blacklist information pre-set inside the device or set

via the WFS CMD CDM SET BLACKLIST or

WFS CMD CDM SET CLASSIFICATION LIST command, or

WFS CMD CIM SET BLACKLIST or WFS CMD CIM SET CLASSIFICATION LIST in the case of a recycler.

Input Param

None.

Output Param LPWFSCDMBLACKLIST lpBlacklist;

```
typedef struct wfs cdm blacklist
     LPWSTR
                                lpszVersion;
     USHORT
                                usCount:
     LPWFSCDMBLACKLISTELEMENT
                                *lppBlacklistElements;
     } WFSCDMBLACKLIST, *LPWFSCDMBLACKLIST;
```

lpszVersion

This is an application defined Unicode string that sets the version identifier of the blacklist. This can be set to NULL if it has no version identifier.

usCount

Number of pointers to WFSCDMBLACKLISTELEMENT structures returned in lppBlacklistElements.

lppBlacklistElements

Pointer to an array of pointers to WFSCDMBLACKLISTELEMENT structures.

```
typedef struct wfs cdm blacklist element
     LPWSTR
                                lpszSerialNumber;
     CHAR
                                cCurrencyID[3];
     ULONG
                                ulValue;
     } WFSCDMBLACKLISTELEMENT,
                               *LPWFSCDMBLACKLISTELEMENT;
```

lpszSerialNumber

This Unicode string defines the serial number or a mask of serial numbers of one blacklist item with the defined currency and value. For a definition of the mask see Section 4.

cCurrencvID

The three character ISO format currency identifier [Ref. 2] of the blacklist element.

ulValue

The value of a blacklist element. This field can be zero to represent all values.

Error Codes

Only the generic error codes defined in [Ref. 1] can be generated by this command.

Comments

None.

5.11 WFS INF CDM GET ALL ITEMS INFO

Description

This command can be used to retrieve all item information available for all levels at once by specifying WFS_CDM_LEVEL_ALL in the *usLevel* parameter. Alternatively this command can be used to retrieve all information for a particular level of banknote. This information is available from the point where the first WFS_EXEE_CDM_INFO_AVAILABLE event is generated until one of the following CDM commands is executed:

WFS_CMD_CDM_DISPENSE, WFS_CMD_CDM_COUNT, WFS_CMD_CDM_PRESENT, WFS_CMD_CDM_RETRACT, WFS_CMD_CDM_REJECT, WFS_CMD_CDM_OPEN_SHUTTER, WFS_CMD_CDM_CLOSE_SHUTTER, WFS_CMD_CDM_RESET, WFS_CMD_CDM_START_EXCHANGE, WFS_CMD_CDM_END_EXCHANGE, WFS_CMD_CDM_CALIBRATE_CASH_UNIT, WFS_CMD_CDM_TEST_CASH_UNITS.

Additionally for a recycler, the following CIM commands will also invalidate the information:

WFS_CMD_CIM_CASH_IN_START, WFS_CMD_CIM_CASH_IN, WFS_CMD_CIM_CASH_IN_ROLLBACK, WFS_CMD_CIM_CASH_IN_END, WFS_CMD_CIM_RETRACT, WFS_CMD_CIM_RESET, WFS_CMD_CIM_START_EXCHANGE, WFS_CMD_CIM_END_EXCHANGE, WFS_CMD_CIM_CREATE_P6_SIGNATURE, WFS_CMD_CIM_REPLENISH, WFS_CMD_CIM_CASH_UNIT_COUNT.

The WFS_EXEE_CDM_INPUT_P6 event is only generated when level 2 and/or level 3 notes are detected.

Input Param

LPWFSCDMGETALLITEMSINFO lpGetAllItemsInfo;

usLevel

Defines the note level. Possible values are:

Value	Meaning
WFS_CDM_LEVEL_1	Information for level 1 notes. Only an image
	file can be retrieved for level 1 notes.
WFS_CDM_LEVEL_2	Information for level 2 notes is to be
	returned with the <i>lpAllItemsInfo</i> output
	parameter. On systems that do not classify
	notes as level 2 this value cannot be used and
	WFS_ERR_INVALID_DATA will be returned.
WES COM LEVEL 2	Information for level 3 notes is to be
WFS_CDM_LEVEL_3	
	returned with the <i>lpAllItemsInfo</i> output parameter. On systems that do not classify
	notes as level 3 this value cannot be used and
	WFS ERR INVALID DATA will be
	returned.
WFS CDM LEVEL 4	Information for level 4 notes is to be
	returned with the <i>lpAllItemsInfo</i> output
	parameter.
WFS_CDM_LEVEL_ALL	Information for all levels all items is to be
	returned with the lpAllItemsInfo output
	parameter.

Output Param LPWFSCDMALLITEMSINFO lpAllItemsInfo;

usCount

Number of WFSCDMITEMINFOALL structures returned in *lppItemsList*.

lppItemsList

Pointer to an array of pointers to WFSCDMITEMINFOALL structures:

```
typedef struct wfs cdm_item_info_all
     USHORT
     CHAR
                                 cCurrencyID[3];
     ULONG
                                 ulValue;
     USHORT
                                 usRelease;
     T.PWSTR
                                 lpszSerialNumber;
     LPSTR
                                 lpszImageFileName;
     WORD
                                 wOnBlacklist;
     WORD
                                 wItemLocation;
     USHORT
                                 usNumber;
                                 wOnClassificationList;
     WORD
     WORD
                                 wItemDeviceLocation;
     } WFSCDMITEMINFOALL, *LPWFSCDMITEMINFOALL;
```

usLevel

Defines the note level. Possible values are:

Value	Meaning
WFS_CDM_LEVEL_1	A level 1 banknote.
WFS_CDM_LEVEL_2	A level 2 banknote.
WFS_CDM_LEVEL_3	A level 3 banknote.
WFS CDM LEVEL 4	A level 4 banknote.

cCurrencyID

Currency ID in ISO 4217 format [Ref. 2]. This value will be an array of three ASCII 0x20h characters for level 1 items.

ulValue

The value of a single item expressed in minimum dispense units. This value will be zero for level 1 items.

usRelease

The release of the banknote type. The higher this number is, the newer the release. Zero means that there is only one release of that banknote type. This value has not been standardized and therefore a release number of the same banknote will not necessarily have the same value in different systems. This value will be zero for level 1 items.

lpszSerialNumber

This field contains the serial number of the item as a Unicode string. A '?' character (0x003F) is used to represent any serial number character that cannot be recognized. If no serial number is available then *lpszSerialNumber* is NULL.

lpszImageFileName

Full file path to an image file containing the serial number(s). If no image is available then this field is NULL. The application is responsible for the use and management of this file. For example, the application can transfer the image files to a directory which is managed by the application.

wOnBlacklist

Specifies if the serial number reported in the *lpszSerialNumber* field is on the blacklist. If the blacklist reporting capability is not supported this field will be zero. Otherwise, possible values are:

Value	Meaning
WFS_CDM_ONBLACKLIST	The serial number of the items is on the
	blacklist.
WFS_CDM_NOTONBLACKLIST	The serial number of the items is not on
	the blacklist.
WFS CDM BLACKLISTUNKNOWN	It is unknown if the serial number of the
	item is on the blacklist.

wItemLocation

Specifies the location of the item as one of the following values:

Value	Meaning
WFS_CDM_LOCATION_DEVICE	The item is inside the device in some position other than a cash unit.
WFS_CDM_LOCATION_CASHUNIT	The item is in a cash unit. The logical cash unit number is defined by <i>usNumber</i> .
WFS_CDM_LOCATION_CUSTOMER	The item has been dispensed to the customer.
WFS_CDM_LOCATION_UNKNOWN	The item location is unknown.

usNumber

If wItemLocation is WFS_CDM_LOCATION_CASHUNIT this parameter specifies the logical number of the cash unit which received the item. If wItemLocation is not WFS_CDM_LOCATION_CASHUNIT then usNumber will be zero.

wOnClassificationList

Specifies if the serial number reported in the *lpszSerialNumber* field is on the classification list. If the classification list reporting capability is not supported this field will be zero. Otherwise, possible values are:

Value	Meaning
WFS_CDM_CLASSIFICATIONLIST_ON	The serial number of the items is on the
	classification list.
WFS_CDM_CLASSIFICATIONLIST_NOTON	The serial number of the items is not on
	the classification list.
WFS_CDM_CLASSIFICATIONLIST_UNKNO	OWN It is unknown if the serial
	number of the item is on the
	classification list

wItemDeviceLocation

If wItemLocation is WFS_CDM_LOCATION_DEVICE this parameter specifies where the item is in the device. If wItemLocation is not WFS_CDM_LOCATION_DEVICE then wItemDeviceLocation will be zero:

Value	Meaning
WFS_CDM_DEVLOC_STACKER	The item is in the intermediate stacker.
WFS_CDM_DEVLOC_OUTPUT	The item is at the output position. The
	items have not been in customer access.
WFS_CDM_DEVLOC_TRANSPORT	The item is at another location in the
	device.
WFS_CDM_DEVLOC_UNKNOWN	The item is in the device but its location
	is unknown

Error Codes

Only the generic error codes defined in [Ref. 1] can be generated by this command.

Comments

In addition, since the item information is not cumulative and can be replaced by any command that can move notes, it is recommended that applications that are interested in the available information should query for it following the WFS_EXEE_CDM_INFO_AVAILABLE event but before any other command is executed.

5.12 WFS INF CDM GET CLASSIFICATION LIST

Description

This command is used to retrieve the entire note classification information pre-set inside the device or set via the WFS CMD CDM SET CLASSIFICATION LIST or

WFS CMD CDM SET BLACKLIST command, or

WFS CMD CIM SET CLASSIFICATION LIST or WFS CMD CIM SET BLACKLIST in the case of a recycler.

This extends the functionality provided by the blacklist commands and allows additional flexibility, for example to specify that notes can be taken out of circulation by specifying them as unfit. Any items not returned in this list will be handled according to normal classification rules.

Input Param

None.

Output Param LPWFSCDMCLASSIFICATIONLIST lpClassificationList;

```
typedef struct wfs cdm classification list
     LPWSTR
                                     lpszVersion;
     USHORT
                                     usCount;
     LPWFSCDMCLASSIFICATIONELEMENT
                                     *lppClassificationElements;
     } WFSCDMCLASSIFICATIONLIST, *LPWFSCDMCLASSIFICATIONLIST;
```

lpszVersion

This is an application defined Unicode string that sets the version identifier of the classification list. This can be set to NULL if it has no version identifier.

Number of pointers to WFSCDMCLASSIFICATIONELEMENT structures returned in lppClassificationElements.

lppClassificationElements

Pointer to an array of pointers to WFSCDMCLASSIFICATIONELEMENT structures.

```
typedef struct _wfs_cdm_classification_element
     LPWSTR
                                lpszSerialNumber;
     CHAR
                                cCurrencyID[3];
     ULONG
                                ulValue;
     USHORT
                                usLevel;
     BOOT
                                bUnfit;
     } WFSCDMCLASSIFICATIONELEMENT, *LPWFSCDMCLASSIFICATIONELEMENT;
```

lpszSerialNumber

This Unicode string defines the serial number or a mask of serial numbers of one element with the defined currency and value. For a definition of the mask see Section 4.

The three character ISO format currency identifier [Ref. 2] of the element.

ulValue

The value of the element. This field can be zero to represent all values.

usLevel

Specifies the note level. Possible values are:

Value	Meaning
WFS_CDM_LEVEL_1	The element specifies notes to be treated as level 1 notes.
WFS_CDM_LEVEL_2	The element specifies notes to be treated as level 2 notes.
WFS_CDM_LEVEL_3	The element specifies notes to be treated as level 3 notes.
WFS_CDM_LEVEL_4	The element specifies notes to be treated as level 4 notes.

bUnfit

Specifies whether the item is to be treated as unfit for dispensing. Applies only where usLevel is WFS CDM LEVEL 4.

Error Codes Only the generic error codes defined in [Ref. 1] can be generated by this command.

6. Execute Commands

6.1 WFS_CMD_CDM_DENOMINATE

Description

This command provides a denomination. A denomination specifies the number of items which are required from each cash unit in order to satisfy a given amount. The denomination depends upon the currency, the mix algorithm and any partial denomination supplied by the application.

This command can also be used to validate that any denomination supplied by the application can be dispensed.

If items of differing currencies are to be included in the same denomination then the currency field must be an array of three ASCII 0x20h characters, the amount must be zero and the mix number must be WFS_CDM_INDIVIDUAL. However, these restrictions do not apply if a single currency is combined with non-currency items, such as coupons.

If the *bCashBox* field of the WFSCDMCAPS structure returned by the WFS_INF_CDM_CAPABILITIES command is TRUE then, if the entire denomination cannot be satisfied, a partial denomination will be returned with the remaining amount to be supplied from the teller's cash box.

This command can be used in four different ways:

- In order to check that it is possible to dispense a given denomination. The input parameters to
 the command are currency and denomination, with a mix number of
 WFS_CDM_INDIVIDUAL and an amount of zero. If items of differing currencies are to be
 dispensed then the currency field should be an array of three ASCII 0x20h characters.
- 2. In order to validate that a given amount matches a given denomination and that it is possible to dispense the denomination. The input parameters to the command should be amount, currency and denomination, with a mix number of WFS_CDM_INDIVIDUAL.
- 3. In order to obtain a denomination of a given amount. The input parameters supplied should be amount, currency and mix number.
- 4. In order to complete a partial denomination of a given amount. In this case the input parameters to the command should be currency, amount, mix number and either a partially specified denomination or a minimum amount from the cash box. A completed denomination is returned. *ulCashBox* of the denomination structure may be updated as a result of this command.

Input Param

LPWFSCDMDENOMINATE lpDenominate;

usTellerID

Identification of teller. This field is ignored if the device is a Self-Service CDM.

usMixNumber

Mix algorithm or house mix table to be used.

lpDenomination

Pointer to a WFSCDMDENOMINATION structure, describing the contents of the denomination operation.

cCurrencvID

Identification of currency in ISO format [Ref. 2]. Where the denomination contains multiple currencies this field should be set to three ASCII 0x20 characters.

The amount to be denominated or dispensed. Where the denomination contains multiple currencies this value is zero.

usCount

The size of the *lpulValues* list. This *usCount* is the same as the *usCount* returned from the last WFS INF CDM CASH UNIT INFO command or set by the last WFS CMD CDM END EXCHANGE command. If this value is not required because a mix

algorithm is used then the *usCount* can be set to zero.

If the application passes in an invalid us Count the Service Provider should return a WFS ERR INVALID DATA return code.

Pointer to an array of ULONGs. This list specifies the number of items to take from each of the cash units. This list corresponds to the array of cash unit structures returned by the last WFS INF CDM CASH UNIT INFO command or set by the last WFS CMD CDM SET CASH UNIT INFO or WFS CMD CDM END EXCHANGE commands. The first value in the array is related to the cash structure with the index number 1.

This array contains a field for each possible cash unit. If a cash unit is not required in the denomination its corresponding field in this array should be set to zero.

If the application does not wish to specify a denomination, it should set the *lpulValues* pointer to NULL.

ulCashBox

Only applies to Teller CDM devices. Amount to be paid from the teller's cash box.

Output Param LPWFSCDMDENOMINATION lpDenomination;

For a description see the input structure.

Where mixed currencies are being denominated the *ulAmount* field in the returned denomination structure will be zero and the *cCurrencyID* field will be set to three ASCII 0x20 characters.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_INVALIDCURRENCY	There are no cash units in the CDM of the
	currency specified in the cCurrencyID field
	of the input parameter.
WFS_ERR_CDM_INVALIDTELLERID	Invalid teller ID. This error will never be
	generated by a Self-Service CDM.
WFS_ERR_CDM_CASHUNITERROR	There is a problem with a cash unit. A
	WFS_EXEE_CDM_CASHUNITERROR
	event will be posted with the details.
WFS_ERR_CDM_INVALIDDENOMINATION	
	WFS_CDM_INDIVIDUAL and the sum of
	the values for <i>ulCashBox</i> and the items
	specified by <i>lpulValues</i> does not match the
	non-zero amount specified. This error code
	is not used when the amount specified is
	zero.
WFS_ERR_CDM_INVALIDMIXNUMBER	Unknown mix algorithm.
WFS_ERR_CDM_NOCURRENCYMIX	The cash units specified in the denomination were not all of the same currency.

CWA 16926-5:2020 (E)

	WFS_ERR_CDM_NOTDISPENSABLE	The amount is not dispensable by the CDM. This error code is also returned if the <i>usMixNumber</i> is specified as WFS_CDM_INDIVIDUAL, but a cash unit is specified in the <i>lpulValues</i> list which is not a dispensing cash unit, e.g., a retract/reject cash unit.
	WFS_ERR_CDM_TOOMANYITEMS	The request requires too many items to be dispensed.
	WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state (see section WFS CMD CDM START EXCHANGE).
	WFS_ERR_CDM_NOCASHBOXPRESENT	Cash box amount needed, however teller is not assigned a cash box.
	WFS_ERR_CDM_AMOUNTNOTINMIXTAE	
		A mix table is being used to determine the denomination but the amount specified for the denomination is not in the mix table.
Events	In addition to the generic event defined in [Ref. 1], the following events can be generated as a result of this command:	
	Value	Meaning
	WFS_EXEE_CDM_CASHUNITERROR	An error occurred while attempting to denominate from the cash unit specified by the event.
Comments	None.	

6.2 WFS CMD CDM DISPENSE

Description

This command performs the dispensing of items to the customer. The command provides the same functionality as the WFS_CMD_CDM_DENOMINATE command plus the additional functionality of dispensing the items. If items of differing currencies are to be dispensed then the currency field must be an array of three ASCII 0x20h characters, the amount must be zero and the mix number must be WFS_CDM_INDIVIDUAL. However, these restrictions do not apply if a single currency is dispensed with non-currency items, such as coupons.

The WFS CMD CDM DISPENSE command can be used in the following ways:

- The input parameters to the command are amount, currency and denomination. The mix number is WFS_CDM_INDIVIDUAL. In this case, the denomination is checked for validity and, if valid, is dispensed.
- 2. The input parameters are amount, currency and mix number. In this case the amount is denominated and, if this succeeds, the items are dispensed.
- If the amount is zero, but the currency and the denomination are supplied with a mix number of WFS_CDM_INDIVIDUAL the denomination is checked for validity and, if valid, is dispensed.
- 4. The command will calculate a partial denomination of a given amount and dispense the complete denomination. In this case the input parameters to the command should be currency, amount, mix number and either a partially specified denomination or a minimum amount from the cash box. The cash box amount may be updated as a result of this command.

When more than one physical cash unit exists for a logical cash unit number, the device selects the actual physical cash unit to use in the dispense operation.

If the *bCashBox* field of the WFSCDMCAPS structure returned by the WFS_INF_CDM_CAPABILITIES command is TRUE then, if the entire denomination cannot be satisfied, a partial denomination will be returned with the remaining amount to be supplied from the teller's cash box.

If the device is a Teller CDM, the input field *fwPosition* can be set to WFS_CDM_POSNULL. If this is the case the *usTellerID* is used to perform the dispense operation to the assigned teller position.

The field *bPresent* of the WFSCDMDISPENSE structure determines whether items are actually presented to the user as part of the dispense operation. If this field is set to TRUE then the items will be moved to the exit slot, if it is FALSE the items will be moved to an intermediate stacker. In the second case it will be necessary to use the WFS_CMD_CDM_PRESENT command to present the items to the user. If *bPresent* is set to FALSE then the *fwPosition* field is ignored. If the CDM does not have an intermediate stacker then *bPresent* is ignored.

If *bPresent* is set to TRUE and a shutter exists, then it will be implicitly controlled during the present operation, even if the *bShutterControl* capability is set to FALSE. The shutter will be closed when the user removes the items or the items are retracted.

Note that a level 4 note can be dispensed, but is not necessarily presented to the customer. e.g. a note can be skewed, or can be unfit for dispensing.

Input Param

LPWFSCDMDISPENSE lpDispense;

usTellerID

Identifies the teller. This field is ignored if the device is a Self-Service CDM.

usMixNumber

Mix algorithm or house mix table to be used to create a denomination of the supplied amount. If the value is WFS CDM INDIVIDUAL, the denomination supplied in the lpDenomination field is validated prior to the dispense operation. If it is found to be invalid no alternative denomination will be calculated.

fwPosition

Determines to which side the amount is dispensed. If the device is a Teller CDM this field is ignored and the output position associated with usTellerID is used. The value is specified by one of the following values:

Value	Meaning
WFS_CDM_POSNULL	The default configuration information is
	used. This can be either position dependent
	or teller dependent.
WFS_CDM_POSLEFT	Present items to left side of device.
WFS_CDM_POSRIGHT	Present items to right side of device.
WFS_CDM_POSCENTER	Present items to center output position.
WFS_CDM_POSTOP	Present items to the top output position.
WFS_CDM_POSBOTTOM	Present items to the bottom output position.
WFS_CDM_POSFRONT	Present items to the front output position.
WFS CDM POSREAR	Present items to the rear output position.

bPresent

If this field is set to TRUE then the items will be moved to the exit slot, if it is FALSE the items will be moved to an intermediate stacker.

lpDenomination

Pointer to a WFSCDMDENOMINATION structure, describing the denominations used for the dispense operation. For the WFSCDMDENOMINATION structure specification see the definition of the command WFS CMD CDM DENOMINATE.

Output Param LPWFSCDMDENOMINATION lpDenomination;

For the WFSCDMDENOMINATION structure specification see the definition of the command WFS CMD CDM DENOMINATE.

The values in this structure report the amount dispensed and the number of items dispensed from each cash unit.

Where mixed currencies are being dispensed the *ulAmount* field in the returned denomination structure will be zero and the *cCurrencyID* field will be set to three ASCII 0x20 characters.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_INVALIDCURRENCY	There are no cash units in the CDM of the
	currency specified in the cCurrencyID field
	of the input parameter.
WFS_ERR_CDM_INVALIDTELLERID	Invalid teller ID. This error will never be
	generated by a Self-Service CDM.
WFS_ERR_CDM_CASHUNITERROR	There is a problem with a cash unit. A
	WFS_EXEE_CDM_CASHUNITERROR
	execute event is posted with the details.
WFS_ERR_CDM_INVALIDDENOMINATIO	
	units was greater than the amount specified.
WFS_ERR_CDM_INVALIDMIXNUMBER	Mix algorithm is not known.
WFS_ERR_CDM_NOCURRENCYMIX	Cash units containing two or more different currencies were selected.
WFS ERR CDM NOTDISPENSABLE	The amount is not dispensable by the CDM.
	This error code is also returned if the
	usMixNumber is specified as
	WFS_CDM_INDIVIDUAL, but a cash unit
	is specified in the <i>lpulValues</i> list which is
	not a dispensing cash unit, e.g., a
	retract/reject cash unit.

WFS_ERR_CDM_TOOMANYITEMS	The request would require too many items to be dispensed. This error is also generated if <i>bPresent</i> is FALSE and sub-dispensing is required.
WFS_ERR_CDM_UNSUPPOSITION	The specified output position is not supported.
WFS_ERR_CDM_SAFEDOOROPEN	The safe door is open. This device requires the safe door to be closed in order to perform this operation.
WFS ERR CDM EXCHANGEACTIVE	The CDM is in an exchange state.
WFS_ERR_CDM_NOCASHBOXPRESENT	Cash box amount needed, however teller is not assigned a cash box.
WFS ERR CDM AMOUNTNOTINMIXTAB	LE
	A mix table is being used to determine the denomination but the amount specified for the denomination is not in the mix table.
WFS_ERR_CDM_ITEMSNOTTAKEN	Items have not been taken during a sub- dispense operation. This error occurs if a hardware timeout expires.
WFS_ERR_CDM_ITEMSLEFT	Items have been left in the transport or exit slot as a result of a prior dispense, present or recycler cash-in operation.
WFS_ERR_CDM_SHUTTEROPEN	The Service Provider cannot dispense items with an open output shutter.

If the bPresent field of the WFSCDMDISPENSE structure is TRUE, the following error codes can also be returned:

Value	Meaning
WFS_ERR_CDM_SHUTTERNOTOPEN	The shutter is not open or did not open when
WFS ERR CDM PRERRORNOITEMS	it should have. No items presented. An error occurred while items were being
	moved to the exit slot - no items are presented.
WFS_ERR_CDM_PRERRORITEMS	An error occurred while items were being moved to the exit slot - at least some of the
	items have been presented.
WFS_ERR_CDM_PRERRORUNKNOWN	An error occurred while items were being moved to the exit slot - the position of the items is unknown. Intervention may be required to reconcile the cash amount totals.
	1

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated as a result of this command:

Value	Meaning
WFS_USRE_CDM_CASHUNITTHRESHOLD	
	one of the cash units.
WFS_EXEE_CDM_DELAYEDDISPENSE	The dispense operation will be delayed by
	the specified time.
WFS_EXEE_CDM_STARTDISPENSE	Fired when the delayed dispense operation starts.
WFS EXEE CDM CASHUNITERROR	A cash unit caused an error during a
	dispense operation.
WFS SRVE CDM ITEMSTAKEN	The user has removed the items presented. If
	the dispense is not a sub-dispense this event
	occurs after the completion of the dispense
	command.
WFS EXEE CDM PARTIALDISPENSE	Indicates that the dispense operation is to be
W15_5165_65W_11M111651615161	divided into several sub-dispense operations.
WFS EXEE CDM SUBDISPENSEOK	A sub-dispense operation was completed
WIS_EXEE_COM_SODDISTENSEOR	successfully.
	successiuity.

CWA 16926-5:2020 (E)

WFS_EXEE_CDM_INCOMPLETEDISPENSE It has not been possible to dispense the entire

denomination but part of the requested denomination is on the intermediate stacker or in customer access. The error code will be WFS_ERR_CDM_NOTDISPENSABLE.

WFS_EXEE_CDM_NOTEERROR An item detection error has occurred. WFS_EXEE_CDM_INPUT_P6 Level 2 and/or level 3 notes have been

detected.

WFS_EXEE_CDM_INFO_AVAILABLE Information is available for items being

processed by this operation.

WFS_SRVE_CDM_SHUTTERSTATUSCHANGED

The shutter status has changed.

6.3 WFS CMD CDM COUNT

Description

This command empties the specified physical cash unit(s). All items dispensed from the cash unit are counted and moved to the specified output location.

The number of items counted can be different from the number of items dispensed in cases where the CDM has the ability to detect this information. If the CDM cannot differentiate between what is dispensed and what is counted then *ulDispensed* will be the same as *ulCounted*.

Upon successful WFS CMD CDM COUNT command execution the physical cash unit(s) *ulCount* field within the WFSCDMPHCU structure is reset.

Input Param

LPWFSCDMPHYSICALCU lpPhysicalCU;

```
typedef struct _wfs_cdm_physical_cu
     BOOL
                                bEmptyAll;
     WORD
                                fwPosition;
     LPSTR
                                lpPhysicalPositionName;
     } WFSCDMPHYSICALCU, *LPWFSCDMPHYSICALCU;
```

Specifies whether all physical cash units are to be emptied. If this value is TRUE then lpPhysicalPositionName is ignored.

fwPosition

Specifies the location to which items should be moved. The value is set to one of the following values:

Value	Meaning
WFS_CDM_POSNULL	Output location is determined by Service
	Provider.
WFS_CDM_POSLEFT	Present items to left side of device.
WFS_CDM_POSRIGHT	Present items to right side of device.
WFS_CDM_POSCENTER	Present items to center output position.
WFS_CDM_POSTOP	Present items to the top output position.
WFS_CDM_POSBOTTOM	Present items to the bottom output position.
WFS_CDM_POSFRONT	Present items to the front output position.
WFS_CDM_POSREAR	Present items to the rear output position.
WFS CDM POSREJECT	Reject bin is used as output location.

lpPhysicalPositionName

Specifies which physical cash unit to empty and count. This name is the same as the lpPhysicalPositionName in the WFSCDMPHCU structure.

Output Param LPWFSCDMCOUNT lpCount;

```
typedef struct _wfs_cdm_count
                                usNumPhysicalCUs;
     LPWFSCDMCOUNTEDPHYSCU
                                *lppCountedPhysCUs;
     } WFSCDMCOUNT, *LPWFSCDMCOUNT;
```

usNumPhysicalCUs

This value indicates the number of physical cash unit structures (WFSCDMCOUNTEDPHYSCU) returned. This value will always be greater than zero.

lppCountedPhysCUs

Pointer to an array of pointers to WFSCDMCOUNTEDPHYSCU structures:

```
typedef struct wfs cdm counted phys cu
     LPSTR
                                lpPhysicalPositionName;
     CHAR
                                cUnitId[5];
     ULONG
                                ulDispensed;
     ULONG
                                ulCounted;
     USHORT
                                usPStatus;
     } WFSCDMCOUNTEDPHYSCU, *LPWFSCDMCOUNTEDPHYSCU;
```

lpPhysicalPositionName

Specifies which physical cash unit was emptied and counted. This name is that defined in the *lpPhysicalPositionName* field of the WFSCDMPHCU structure.

cUnitId

Cash unit ID. This is the identifier defined in the *cUnitID* field of the WFSCDMPHCU structure.

ulDispensed

The number of items that were dispensed during the emptying of the cash unit.

ulCounted

The number of items that were counted during the emptying of the cash unit.

usPStatus

Supplies the status of the physical cash unit as one of the following values:

Value	Meaning
WFS_CDM_STATCUOK	The cash unit is in a good state.
WFS_CDM_STATCUFULL	The cash unit is full.
WFS_CDM_STATCUHIGH	The cash unit is almost full (reached or
	exceeded the threshold defined by
	WFSCDMCASHUNIT.ulMaximum).
WFS_CDM_STATCULOW	The cash unit is almost empty.
WFS_CDM_STATCUEMPTY	The cash unit is empty.
WFS_CDM_STATCUINOP	The cash unit is inoperative.
WFS_CDM_STATCUMISSING	The cash unit is missing.
WFS_CDM_STATCUNOVAL	The values of the specified cash unit are
	not available.
WFS_CDM_STATCUNOREF	There is no reference value available for
	the notes in this cash unit.
WFS_CDM_STATCUMANIP	The cash unit has been inserted
	(including removal followed by a
	reinsertion) when the device was not in
	the exchange state. This cash unit cannot
	be dispensed from.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_CASHUNITERROR	A cash unit caused a problem. A
	WFS_EXEE_CDM_CASHUNITERROR
	event will be posted with the details.
WFS_ERR_CDM_UNSUPPOSITION	The position specified is not supported.
WFS_ERR_CDM_SAFEDOOROPEN	The safe door is open. This device requires
	the safe door to be closed in order to perform
	this operation.
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated as a result of this command:

Value	Meaning
WFS_EXEE_CDM_CASHUNITERROR	A cash unit caused an error during the count operation.
WFS_SRVE_CDM_ITEMSTAKEN	The items emptied to the output location have been removed by the user.
WFS_SRVE_CDM_ITEMSPRESENTED	Items have been emptied to the output location. These items may need to be removed from the output location before the operation can continue.
WFS_EXEE_CDM_NOTEERROR WFS_EXEE_CDM_INPUT_P6	An item detection error has occurred. Level 2 and/or level 3 notes have been detected.

WFS_EXEE_CDM_INFO_AVAILABLE

Information is available for items being processed by this operation.

WFS_SRVE_CDM_SHUTTERSTATUSCHANGED

The shutter status has changed.

6.4 WFS CMD CDM PRESENT

Description

This command will move items to the exit position for removal by the user. If a shutter exists, then it will be implicitly controlled during the present operation, even if the *bShutterControl* capability is set to FALSE. The shutter will be closed when the user removes the items or the items are retracted. If *lpfwPosition* points to WFS_CDM_POSNULL the position set in the WFS_CDM_DISPENSE command which caused these items to be dispensed will be used.

When this command successfully completes the items are in customer access.

Input Param

LPWORD lpfwPosition;

lpfwPosition

Pointer to the output position where the amount is to be presented. The value is set to one of the following values:

Value	Meaning
WFS_CDM_POSNULL	The default configuration information is
	used. This can be either position dependent
	or teller dependent.
WFS_CDM_POSLEFT	Present items to left side of device.
WFS_CDM_POSRIGHT	Present items to right side of device.
WFS_CDM_POSCENTER	Present items to center output position.
WFS_CDM_POSTOP	Present items to the top output position.
WFS_CDM_POSBOTTOM	Present items to the bottom output position.
WFS_CDM_POSFRONT	Present items to the front output position.
WFS_CDM_POSREAR	Present items to the rear output position.

Output Param None.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

WFS_ERR_CDM_SHUTTERNOTOPEN The shutter did not open when it should	Value	Meaning
1 37 %	WFS_ERR_CDM_SHUTTERNOTOPEN	The shutter did not open when it should
have. No items presented.		have. No items presented.
WFS_ERR_CDM_SHUTTEROPEN The shutter is open when it should be closed.	WFS_ERR_CDM_SHUTTEROPEN	The shutter is open when it should be closed.
No items presented.		No items presented.
WFS_ERR_CDM_NOITEMS There are no items on the stacker.	WFS_ERR_CDM_NOITEMS	There are no items on the stacker.
WFS_ERR_CDM_EXCHANGEACTIVE The CDM is in an exchange state.	WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.
WFS_ERR_CDM_PRERRORNOITEMS There was an error during the present	WFS_ERR_CDM_PRERRORNOITEMS	There was an error during the present
operation - no items were presented.		operation - no items were presented.
WFS_ERR_CDM_PRERRORITEMS There was an error during the present	WFS_ERR_CDM_PRERRORITEMS	
operation - at least some of the items were		operation - at least some of the items were
presented.		presented.
WFS_ERR_CDM_PRERRORUNKNOWN There was an error during the present	WFS_ERR_CDM_PRERRORUNKNOWN	S I
operation - the position of the items is		
unknown. Intervention may be required to		unknown. Intervention may be required to
reconcile the cash amount totals.		
WFS_ERR_CDM_UNSUPPOSITION The position specified is not supported.	WFS_ERR_CDM_UNSUPPOSITION	The position specified is not supported.

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated as a result of this command:

Value	Meaning
WFS_USRE_CDM_CASHUNITTHRESHOLD	A threshold condition has been reached in
	one of the cash units.
WFS_SRVE_CDM_ITEMSTAKEN	The items have been removed by the user.
	This event is generated after the
	completion of the present operation.
WFS_EXEE_CDM_INPUT_P6	Level 2 and/or level 3 notes have been
	detected.
WFS_EXEE_CDM_INFO_AVAILABLE	Information is available for items being
	processed by this operation.

WFS_SRVE_CDM_SHUTTERSTATUSCHANGED The shutter status has changed.

6.5 WFS_CMD_CDM_REJECT

Description This command will move items from the intermediate stacker and transport them to a reject cash

unit (i.e. a cash unit with usType WFS CDM TYPEREJECTCASSETTE). The

WFSCDMCASHUNIT.*ulCount* field of the reject cash unit is incremented by the number of items that were thought to be present at the time of the reject or the number counted by the device

during the reject. Note that the reject bin count is unreliable.

Input Param None.

Output Param None.

Error Codes In addition to the generic error codes defined in [Ref. 1], the following error codes can be

generated by this command:

Value	Meaning
WFS_ERR_CDM_CASHUNITERROR	A reject cash unit caused a problem. A
	WFS_EXEE_CDM_CASHUNITERROR
	event will be posted with the details.
WFS_ERR_CDM_NOITEMS	There were no items on the stacker.
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.

Events In addition to the generic events defined in [Ref. 1], the following events can be generated as a

result of this command:

Value	Meaning
WFS_USRE_CDM_CASHUNITTHRESHOLD	A reject bin threshold condition has been
	reached.
WFS_EXEE_CDM_CASHUNITERROR	A cash unit caused an error during the reject operation.
WFS_EXEE_CDM_INPUT_P6	Level 2 and/or level 3 notes have been detected.
WFS_EXEE_CDM_INFO_AVAILABLE	Information is available for items being processed by this operation.

6.6 WFS_CMD_CDM_RETRACT

Description

This command will retract items which may have been in customer access from an output position or from internal areas within the CDM. Retracted items will be moved to either a retract cash unit, a reject cash unit, item cash units, the transport or the intermediate stacker. After the items are retracted the shutter is closed automatically, even if the *bShutterControl* capability is set to FALSE.

If items are moved to a retract cash unit (i.e. a cash unit with usType WFS_CDM_TYPERETRACTCASSETTE), then the WFSCDMCASHUNIT.ulCount field of the retract cash unit must be incremented by 1 to specify the number of retracts. If items are moved to any other cash unit (e.g. a cash unit with usType WFS_CDM_TYPEREJECTCASSETTE) then the WFSCDMCASHUNIT.ulCount field of the cash unit must be incremented by the number of items that were thought to be present at the time the WFS_CMD_CDM_RETRACT command was issued or the number counted by the device during the retract. Note that reject bin counts are unreliable.

Input Param

LPWFSCDMRETRACT lpRetract;

fwOutputPosition

Specifies the output position from which to retract the items. The value is set to one of the following values:

Value	Meaning
WFS_CDM_POSNULL	The default configuration information should
	be used.
WFS_CDM_POSLEFT	Retract items from the left output position.
WFS_CDM_POSRIGHT	Retract items from the right output position.
WFS_CDM_POSCENTER	Retract items from the center output
	position.
WFS_CDM_POSTOP	Retract items from the top output position.
WFS_CDM_POSBOTTOM	Retract items from the bottom output
	position.
WFS_CDM_POSFRONT	Retract items from the front output position.
WFS_CDM_POSREAR	Retract items from the rear output position.

usRetractArea

This value specifies the area to which the items are to be retracted. Possible values are:

Value	Meaning
WFS_CDM_RA_RETRACT	Retract the items to a retract cash unit.
WFS_CDM_RA_TRANSPORT	Retract the items to the transport.
WFS_CDM_RA_STACKER	Retract the items to the intermediate stacker
	area.
WFS_CDM_RA_REJECT	Retract the items to a reject cash unit.
WFS_CDM_RA_ITEMCASSETTE	Retract the items to the item cassettes, i.e.
	cassettes that can be dispensed from.

usIndex

If usRetractArea is set to WFS_CDM_RA_RETRACT this field defines the position inside the retract cash units into which the cash is to be retracted. usIndex starts with a value of one (1) for the first retract position and increments by one for each subsequent position. If there are several logical retract cash units (of type WFS_CDM_TYPERETRACTCASSETTE in command WFS_INF_CDM_CASH_UNIT_INFO), usIndex would be incremented from the first position of the first retract cash unit to the last position of the last retract cash unit defined in WFSCDMCUINFO. The maximum value of usIndex is the sum of WFSCDMCASHUNIT.ulMaximum of each retract cash unit. If usRetractArea is not set to WFS_CDM_RA_RETRACT the value of this field is ignored.

Output Param LPWFSCDMITEMNUMBERLIST lpItemNumberList;

Pointer to a WFSCDMITEMNUMBERLIST structure. This parameter will provide details about the items moved with this command or this parameter will be NULL if the device is not capable of identifying the moved items.

usNumOfItemNumbers

Number of item types moved during this command, i.e. the number of *lppItemNumber* list elements.

lppItemNumber

List of item types moved to the *usRetractArea* during this command. A pointer to an array of pointers to WFSCDMITEMNUMBER structures:

cCurrencyID

A three character array storing the ISO format [Ref. 2] Currency ID; or three ASCII 0x20h characters if the currency of the item is not known.

ulValues

The value of a single item expressed in minimum dispense units; or a zero value if the value of the item is not known.

usRelease

The release of the item. The higher this number is, the newer the release. Zero means that there is only one release or the release is not known. This value has not been standardized and therefore a release number of the same item will not necessarily have the same value in different systems.

ulCount

The count of items of the same type moved to the same destination during the execution of this command.

usNumber

The logical number of the cash unit which received items during the execution of this command. This value will be zero if items were moved to the *usRetractArea* WFS CDM RA TRANSPORT or WFS CDM RA STACKER.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_CASHUNITERROR	A cash unit caused a problem. A
	WFS_EXEE_CDM_CASHUNITERROR
	event will be posted with the details.
WFS_ERR_CDM_NOITEMS	There were no items to retract.
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.
WFS_ERR_CDM_SHUTTERNOTCLOSED	The shutter failed to close.
WFS_ERR_CDM_ITEMSTAKEN	Items were present at the output position at
	the start of the operation, but were removed
	before the operation was complete - some or
	all of the items were not retracted.
WFS_ERR_CDM_INVALIDRETRACTPOSIT	TION

The *usIndex* is not supported.

WFS_ERR_CDM_NOTRETRACTAREA

WFS_ERR_CDM_UNSUPPOSITION

WFS_ERR_CDM_POSITION_NOT_EMPTY

WFS_ERR_CDM_INCOMPLETERETRACT

WFS_ERR_CDM_INCOMPLETERETRACT

WFS_ERR_CDM_INCOMPLETERETRACT

WFS_ERR_CDM_INCOMPLETERETRACT

WFS_ERR_CDM_INCOMPLETERETRACT

WFS_ERR_CDM_INCOMPLETERETRACT

Some or all of the items were not retracted for a reason not covered by other error codes. The detail will be reported with the WFS_EXEE_CDM_INCOMPLETERETRACT

CT event.

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated as a result of this command:

Value	Meaning
WFS_USRE_CDM_CASHUNITTHRESHOLD	A threshold condition has been reached in a
	retract or reject cash unit.
WFS_EXEE_CDM_CASHUNITERROR	An error occurred while attempting to retract
	to a cash unit.
WFS_SRVE_CDM_ITEMSTAKEN	The items presented have been removed by
	the user.
WFS_EXEE_CDM_INPUT_P6	Level 2 and/or level 3 notes have been
	detected.
WFS_EXEE_CDM_INFO_AVAILABLE	Information is available for items being
	processed by this operation.
WFS_EXEE_CDM_INCOMPLETERETRACT	The retract command has completed with an
	error and not all of the items have been
	retracted. The detail of what was actually
	retracted will be reported with the event
	data.
WFS SRVE CDM SHUTTERSTATUSCHAN	GED
	The shutter status has changed.

6.7 WFS_CMD_CDM_OPEN_SHUTTER

Description This command opens the shutter.

Input Param LPWORD lpfwPosition;

lpfwPosition

Pointer to the output position where the shutter is to be opened. If the application does not need to specify a shutter, this field can be set to NULL or its contents to WFS_CDM_POSNULL. The position can be set to one of the following values:

Value	Meaning
WFS_CDM_POSNULL	The default configuration information should
	be used.
WFS_CDM_POSLEFT	Open the shutter at the left output position.
WFS_CDM_POSRIGHT	Open the shutter at the right output position.
WFS_CDM_POSCENTER	Open the shutter at the center output position.
WFS_CDM_POSTOP	Open the shutter at the top output position.
WFS_CDM_POSBOTTOM	Open the shutter at the bottom output position.
WFS_CDM_POSFRONT	Open the shutter at the front output position.
WFS_CDM_POSREAR	Open the shutter at the rear output position.

Output Param None.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_UNSUPPOSITION	The position specified is not supported.
WFS_ERR_CDM_SHUTTERNOTOPEN	The shutter failed to open.
WFS_ERR_CDM_SHUTTEROPEN	The shutter was already open.
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated as a result of this command:

Value	Meaning
WFS_SRVE_CDM	SHUTTERSTATUSCHANGED

The shutter status has changed.

6.8 WFS_CMD_CDM_CLOSE_SHUTTER

Description This command closes the shutter.

Input Param LPWORD lpfwPosition;

lpfwPosition

Pointer to the output position where the shutter is to be closed. If the application does not need to specify a shutter, this field can be set to NULL or its contents to WFS_CDM_POSNULL. The position can be set to one of the following values:

Value	Meaning
WFS_CDM_POSNULL	The default configuration information should
	be used.
WFS_CDM_POSLEFT	Close the shutter at the left output position.
WFS_CDM_POSRIGHT	Close the shutter at the right output position.
WFS_CDM_POSCENTER	Close the shutter at the center output
	position.
WFS_CDM_POSTOP	Close the shutter at the top output position.
WFS_CDM_POSBOTTOM	Close the shutter at the bottom output
	position.
WFS_CDM_POSFRONT	Close the shutter at the front output position.
WFS_CDM_POSREAR	Close the shutter at the rear output position.

Output Param None.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_UNSUPPOSITION	The position specified is not supported.
WFS_ERR_CDM_SHUTTERCLOSED	The shutter was already closed.
WFS_ERR_CDM_SHUTTERNOTCLOSED	The shutter failed to close.
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated as a result of this command:

Value	Meaning
WFS SRVE CD	M SHUTTERSTATUSCHANGED

The shutter status has changed.

6.9 WFS_CMD_CDM_SET_TELLER_INFO

Description

This command allows the application to set the teller position and initialize counts for each currency assigned to the teller. The values set by this command are persistent. This command only applies to Teller CDMs.

Input Param

LPWFSCDMTELLERUPDATE lpTellerUpdate;

usAction

The action to be performed specified as one of the following values:

Value	Meaning
WFS_CDM_CREATE_TELLER	A teller is to be added.
WFS_CDM_MODIFY_TELLER	Information about an existing teller is to be
	modified.
WFS CDM DELETE TELLER	A teller is to be removed.

lpTellerDetails

For a specification of the structure WFSCDMTELLERDETAILS please refer to the WFS_INF_CDM_TELLER_INFO command.

Output Param

None.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_INVALIDCURRENCY	The specified currency is not currently available.
WFS_ERR_CDM_INVALIDTELLERID	The teller ID is invalid. This error will never be generated by a Self-Service CDM.
WFS_ERR_CDM_UNSUPPOSITION	The position specified is not supported.
WFS_ERR_CDM_EXCHANGEACTIVE	The target teller is currently in the middle of an exchange operation.

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated as a result of this command:

Value	Meaning
WFS_SRVE_CDM_TELLERINFOCHANGED	Teller information has been created,
	modified or deleted.

Comments

None.

6.10 WFS_CMD_CDM_SET_CASH_UNIT_INFO

Description

This command is used to adjust information regarding the status and contents of the cash units present in the CDM.

This command generates the service event WFS SRVE CDM CASHUNITINFOCHANGED to inform applications that the information for a cash unit has been changed.

This command can only be used to change software counters, thresholds and the application lock. All other fields in the input structure will be ignored.

The following fields of the WFSCDMCASHUNIT structure may be updated by this command:

ulInitialCount

ulCount

ulRejectCount

ulMinimum

ulMaximum

bAppLock |

ulDispensedCount

ulPresentedCount

ulRetractedCount

As may the following fields of the WFSCDMPHCU structure:

ulInitialCount

ulCount

ulRejectCount

ulDispensedCount

ulPresentedCount

ulRetractedCount

Any other changes must be performed via an exchange operation.

If the fields ulCount and ulRejectCount of lppPhysical are set to zero by this command, the application is indicating that it does not wish counts to be maintained for the physical cash units. Counts on the logical cash units will still be maintained and can be used by the application. If the physical counts are set by this command then the logical count will be the sum of the physical counts and any value sent as a logical count will be ignored.

The values set by this command are persistent.

Input Param

LPWFSCDMCUINFO lpCUInfo;

The WFSCDMCUINFO structure is specified in the documentation of the

WFS INF CDM CASH UNIT INFO command. All cash units should be included not just the cash units whose values are to be changed.

Output Param None.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_INVALIDTELLERID	Invalid teller ID. This error will never be
	generated by a Self-Service CDM.
WFS_ERR_CDM_INVALIDCASHUNIT	Invalid cash unit.
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.
WFS_ERR_CDM_CASHUNITERROR	A problem occurred with a cash unit. A
	WFS_EXEE_CDM_CASHUNITERROR
	event will be posted with the details.

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated as a result of this command:

Value	Meaning	
WFS_USRE_CDM_CASHU	NITTHRESHOLD A threshold of	condition has been reached in
	one of the ca	sh units.

CWA 16926-5:2020 (E)

WFS_SRVE_CDM_CASHUNITINFOCHANGED

A cash unit was updated as a result of this

command.

WFS_EXEE_CDM_CASHUNITERROR An error occurred while accessing a cash

unit.

6.11 WFS CMD CDM START EXCHANGE

Description

This command puts the CDM in an exchange state, i.e. a state in which cash units can be emptied, replenished, removed or replaced. Other than the updates which can be made via the WFS_CMD_CDM_SET_CASH_UNIT_INFO command all changes to a cash unit must take place while the cash unit is in an exchange state.

This command returns current cash unit information in the form described in the documentation of the WFS_INF_CDM_CASH_UNIT_INFO command. This command will also initiate any physical processes which may be necessary to make the cash units accessible. Before using this command an application should first have ensured that it has exclusive control of the CDM.

This command may return WFS_SUCCESS even if WFS_EXEE_CDM_CASHUNITERROR events are generated. If this command returns WFS_SUCCESS or WFS_ERR_CDM_EXCHANGEACTIVE the CDM is in an exchange state.

While in an exchange state the CDM will process all WFS requests but exclude WFS[Async]Execute commands, except those listed below:

```
WFS_CMD_CDM_END_EXCHANGE
WFS_CMD_CDM_SET_MIX_TABLE
WFS_CMD_CDM_RESET
```

Any other WFS[Async]Execute commands will result in the error WFS ERR CDM EXCHANGEACTIVE being generated.

If an error is returned by this command, the WFS_INF_CDM_CASH_UNIT_INFO command should be used to determine cash unit information.

If the CDM is part of a compound device together with a CIM (i.e. a cash recycler), exchange operations can either be performed separately on each interface to the compound device, or the entire exchange operation can be done through the CIM interface.

Exchange via CDM and CIM interfaces

If the exchange is performed separately via the CDM and CIM interfaces then these operations cannot be performed simultaneously. An exchange state must therefore be initiated on each interface in the following sequence:

```
CDM

(Lock)

WFS_CMD_CDM_START_EXCHANGE
...exchange action...

WFS_CMD_CDM_END_EXCHANGE
(Unlock)

CIM

(Lock)

WFS_CMD_CIM_START_EXCHANGE
...exchange action...

WFS_CMD_CIM_END_EXCHANGE
(Unlock)
```

In the case of a recycler, the cash-in cash unit counts are set via the CIM interface and the cash-out cash unit counts are set via the CDM interface. Recycling cash units can be set via either interface. However, if the device has recycle units of multiple currencies and/or denominations (or multiple note identifiers associated with the same denomination) then the CIM interface should be used for exchange operations which affect these units. Those fields which are not common to both the CDM and CIM cash units are left unchanged when an exchange (or

WFS_CMD_XXX_SET_CASH_UNIT_INFO) is executed on the other interface. For example if the CDM is used to set the current counts then the CIM *lpNoteNumberList* structure is not changed even if the data becomes inconsistent.

Exchange via the CIM Interface

CWA 16926-5:2020 (E)

All cash unit info fields exposed through the CDM interface are also exposed through the CIM interface, so the entire exchange operation for a recycling device can be achieved through the CIM interface.

Input Param

LPWFSCDMSTARTEX lpStartEx;

```
typedef struct wfs cdm start ex
     {
     WORD
                                fwExchangeType;
     USHORT
                                usTellerID;
     USHORT
                                usCount;
     LPUSHORT
                                lpusCUNumList;
     } WFSCDMSTARTEX, *LPWFSCDMSTARTEX;
```

fwExchangeType

Specifies the type of cash unit exchange operation. This field should be set to one of the following values:

Value	Meaning
WFS_CDM_EXBYHAND	The cash units will be replenished manually
	either by filling or emptying the cash unit by
	hand or by replacing the cash unit.
WFS_CDM_EXTOCASSETTES	Items will be moved from the replenishment
	container to the bill cash units.

usTellerID

Identifies the teller. If the device is a Self-Service CDM this field is ignored.

Number of cash units to be exchanged. This is also the size of the array contained in the lpusCUNumList field.

lpusCUNumList

Pointer to an array of unsigned shorts containing the logical numbers of the cash units to be exchanged. If an invalid logical number is contained in this list, the command will fail with a WFS ERR CDM CASHUNITERROR error.

Output Param LPWFSCDMCUINFO lpCUInfo;

The WFSCDMCUINFO structure is specified in the documentation of the

WFS INF CDM CASH UNIT INFO command. This is the complete list of cash units not just the cash units that are to be changed.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_INVALIDTELLERID	Invalid teller ID. This error will never be
	generated by a Self-Service CDM.
WFS_ERR_CDM_CASHUNITERROR	An error occurred with a cash unit while
	performing the exchange operation. A
	WFS_EXEE_CDM_CASHUNITERROR
	event will be posted with the details.
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is already in an exchange state.

Events

In addition to the generic events defined in [Ref. 1] the following events can be generated by this command:

Value	Meaning
WFS_EXEE_CDM_CASHUNITERROR	A cash unit caused an error.
WFS_EXEE_CDM_NOTEERROR	An item detection error has occurred.
WFS_EXEE_CDM_INPUT_P6	Level 2 and/or level 3 notes have been detected.
WFS_EXEE_CDM_INFO_AVAILABLE	Information is available for items being processed by this operation.

Comments

None.

6.12 WFS CMD CDM END EXCHANGE

Description

This command will end the exchange state. If any physical action took place as a result of the WFS_CMD_CDM_START_EXCHANGE command then this command will cause the cash units to be returned to their normal physical state. Any necessary device testing will also be initiated. The application can also use this command to update cash unit information in the form described in the documentation of the WFS_INF_CDM_CASH_UNIT_INFO command.

When *lpCUInfo* is not NULL the input parameters to this command may be ignored if the Service Provider can obtain cash unit information from self-configuring cash units.

If the fields *ulCount* and *ulRejectCount* of *lppPhysical* are set to zero by this command, the application is indicating that it does not wish counts to be maintained for the physical cash units. Counts on the logical cash units will still be maintained and can be used by the application. If the physical counts are set by this command then the logical count will be the sum of the physical counts and any value sent as a logical count will be ignored.

If an error occurs during the execution of this command, the application must issue WFS_INF_CDM_CASH_UNIT_INFO to determine the cash unit information.

A WFS_EXEE_CDM_CASHUNITERROR event will be sent for any logical cash unit which cannot be successfully updated. If no cash units could be updated then a WFS_ERR_CDM_CASHUNITERROR code will be returned and WFS_EXEE_CDM_CASHUNITERROR events generated for every logical cash unit that could not be updated.

Even if this command does not return WFS SUCCESS the exchange state has ended.

The values set by this command are persistent.

Input Param

LPWFSCDMCUINFO lpCUInfo;

The WFSCDMCUINFO structure is specified in the documentation for the WFS_INF_CDM_CASH_UNIT_INFO command. This pointer can be NULL if the cash unit information has not changed. If this parameter is not NULL then it must contain the complete list of cash unit structures, not just the ones that have changed. If this parameter is NULL then any cash unit in a manipulated state (i.e. *usPStatus* value of WFS_CDM_STATCUMANIP) will remain in this state after the command completes.

The *usStatus* and *usPStatus* values passed in the cash unit structures included within the *lpCUInfo* parameter are ignored and the actual status of the cash units is determined when this command is executed. When *lpCUInfo* is not NULL and this command is successfully executed cash units will no longer be in a manipulated state (i.e. *usPStatus* will no longer be WFS CDM STATCUMANIP).

Output Param

None.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_CASHUNITERROR	A cash unit problem occurred that meant no
	cash units could be updated. One or more
	WFS_EXEE_CDM_CASHUNITERROR
	events will be sent with the details.
WFS_ERR_CDM_NOEXCHANGEACTIVE	There is no exchange active.

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated by this command:

Value	Meaning
WFS_EXEE_CDM_CASHUNITERROR	A cash unit caused an error.
WFS SRVE CDM CASHUNITINFOCHANGED	
	A cash unit was changed.
WFS_USRE_CDM_CASHUNITTHRESHOLD	A threshold condition has been reached in
	one of the cash units.
WFS_EXEE_CDM_NOTEERROR	An item detection error has occurred.

CWA 16926-5:2020 (E)

WFS_EXEE_CDM_INPUT_P6

WFS_EXEE_CDM_INFO_AVAILABLE

Level 2 and/or level 3 notes have been

detected.

Information is available for items being processed by this operation.

6.13 WFS_CMD_CDM_OPEN_SAFE_DOOR

Description This command unlocks the safe door or starts the time delay count down prior to unlocking the

safe door, if the device supports it. The command completes when the door is unlocked or the

timer has started.

Input Param None.Output Param None.

Error Codes In addition to the generic error codes defined in [Ref. 1], the following error codes can be

generated by this command:

Value Meaning

WFS_ERR_CDM_EXCHANGEACTIVE The CDM is in an exchange state.

Events Only the generic events defined in [Ref. 1] can be generated by this command.

6.14 WFS CMD CDM CALIBRATE CASH UNIT

Description

This command will cause a vendor dependent sequence of hardware events which will calibrate one or more physical cash units associated with a logical cash unit. This is necessary if a new type of bank note is put into the cash unit as the command enables the CDM to obtain the measures of the new bank notes.

If more than one physical cash unit is associated with the cash unit, it is up to the Service Provider to determine whether all the physical cash units need to be calibrated or if it is sufficient to calibrate for one physical unit and load the data into the others.

This command cannot be used to calibrate cash units which have been locked by the application. A WFS ERR CDM CASHUNITERROR code will be returned and a WFS EXEE CDM CASHUNITERROR event generated.

Input Param

LPWFSCDMCALIBRATE lpCalibrateIn;

```
typedef struct wfs cdm calibrate
     USHORT
                                usNumber;
     USHORT
                                usNumOfBills:
     LPWFSCDMITEMPOSITION
                                *lpPosition;
     } WFSCDMCALIBRATE, *LPWFSCDMCALIBRATE;
```

usNumber

The logical number of the cash unit.

usNumOfBills

The number of bills to be dispensed during the calibration process.

Specifies where the dispensed items should be moved to. For a description of the WFSCDMITEMPOSITION structure see section WFS CMD CDM RESET.

This parameter is a pointer to a pointer to WFSCDMITEMPOSITION structure.

Output Param LPWFSCDMCALIBRATE lpCalibrateOut;

The WFSCDMCALIBRATE structure is defined in the Input Param section.

The logical number of cash unit which has been calibrated.

usNumOfBills

Number of items that were actually dispensed during the calibration process. This value may be different from that passed in using the input structure if the cash dispenser always dispenses a default number of bills. When bills are presented to an output position this is the count of notes presented to the output position, any other notes rejected during the calibration process are not included in this count as they will be accounted for within the cash unit counts.

Specifies where the items were moved to during the calibration process.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_CASHUNITERROR	A cash unit caused an error. A
	WFS_EXEE_CDM_CASHUNITERROR
	event will be sent with the details.
WFS_ERR_CDM_UNSUPPOSITION	The position specified is not valid.
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.
WFS ERR CDM INVALIDCASHUNIT	The cash unit number specified is not valid.

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated by this command:

Value			Meaning
WFS_USF	E_CDM	CASHUNITTHRESHOLD	A threshold condition has been reached in
			one of the cash units

WFS_SRVE_CDM_CASHUNITINFOCHANGED

A cash unit was changed.

WFS_EXEE_CDM_CASHUNITERROR

WFS_SRVE_CDM_ITEMSTAKEN

WFS_EXEE_CDM_NOTEERROR

A cash unit caused an error.

The items were removed.

An item detection error has occurred.

WFS_EXEE_CDM_INPUT_P6 Level 2 and/or level 3 notes have been

detected.

WFS EXEE CDM INFO AVAILABLE Information is available for items being

processed by this operation.

6.15 WFS CMD CDM SET MIX TABLE

Description

This command is used to set up the mix table specified by the mix number. Mix tables are persistent and are available to all applications in the system. An amount can be specified as different denominations within the mix table. If the amount is specified more than once the Service Provider will attempt to denominate or dispense the first amount in the table. If this does not succeed (e.g. because of a cash unit failure) the Service Provider will attempt to denominate or dispense the next amount in the table. The Service Provider can only dispense amounts which are explicitly mentioned in the mix table.

If a mix number passed in already exists then the information is overwritten with the new information.

Input Param

LPWFSCDMMIXTABLE lpMixTable;

The structure WFSCDMMIXTABLE is defined in the documentation of the command WFS INF CDM MIX TABLE.

Output Param None.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_INVALIDMIXNUMBER	The supplied <i>usMixNumber</i> is reserved for a
	predefined mix algorithm.
WFS_ERR_CDM_INVALIDMIXTABLE	The contents of at least one of the defined
	rows of the mix table is incorrect.

Events

Only the generic events defined in [Ref. 1] can be generated by this command.

Comments

None.

6.16 WFS CMD CDM RESET

Description

This command is used by the application to perform a hardware reset which will attempt to return the CDM device to a known good state. This command does not over-ride a lock obtained through WFS[Async]Lock on another application or service handle.

The device will attempt to move any items found anywhere within the device to the position specified within the *lpResetIn* parameter. This may not always be possible because of hardware problems.

If items are found inside the device the WFS_SRVE_CDM_MEDIADETECTED event will be generated and will inform the application where the items were actually moved to.

If an exchange state is active then this command will end the exchange state (even if this command does not complete successfully).

On a recycling device this command is not accepted if a cash-in transaction is active and will return a WFS ERR DEV NOT READY error.

If items are moved to a retract cash unit (i.e. a cash unit with usType

WFS_CDM_TYPERETRACTCASSETTE), then the WFSCDMCASHUNIT.ulCount field of the retract cash unit must be incremented by 1 to specify the number of operations that changed the count. If items are moved to any other cash unit (e.g. a cash unit with usType WFS_CDM_TYPEREJECTCASSETTE), then the WFSCDMCASHUNIT.ulCount field of the cash unit must be incremented either by the number of items that were present at the time the WFS CMD_CDM_RESET_command was issued or the number counted by the device during the

Input Param

If the application does not wish to specify a cash unit or position it can set *lpResetIn* to NULL. In this case the Service Provider will determine where to move any items found.

WFS CMD CDM RESET command. Note that reject bin counts are unreliable.

LPWFSCDMITEMPOSITION lpResetIn;

usNumber

If non-zero, this value specifies the usNumber (as specified by

WFS_INF_CDM_CASH_UNIT_INFO) of the single cash unit to be used for the storage of any items found.

If items are to be moved to an output position, this value must be zero, *lpRetractArea* must be NULL and *fwOutputPosition* specifies where items are to be moved to.

If this value is zero and items are to be moved to internal areas of the device, *lpRetractArea* specifies where items are to be moved to or stored.

lpRetractArea

This field is used if items are to be moved to internal areas of the device, including cash units, the intermediate stacker, or the transport. The field is only relevant if *usNumber* is zero. The WFSCDMRETRACT structure is defined in WFS CMD CDM RETRACT.

fwOutputPosition

This value will be ignored, because all items are moved from all positions.

usRetractArea

See the description in WFS CMD CDM RETRACT.

usIndex

See the description in WFS CMD CDM RETRACT.

fwOutputPosition

The output position to which items are to be moved. This field is only used if *usNumber* is zero and *lpRetractArea* is NULL. The value is specified as one of the following values:

Value	Meaning
WFS_CDM_POSNULL	The default configuration.
WFS_CDM_POSLEFT	The left output position.
WFS_CDM_POSRIGHT	The right output position.
WFS_CDM_POSCENTER	The center output position.
WFS_CDM_POSTOP	The top output position.
WFS_CDM_POSBOTTOM	The bottom output position.
WFS_CDM_POSFRONT	The front output position.
WFS_CDM_POSREAR	The rear output position.

Output Param None.

Error Codes

In addition to the generic error codes defined in [Ref. 1] the following can be generated by this command:

Value	Meaning
WFS_ERR_CDM_CASHUNITERROR	A cash unit caused an error. One or more
	WFS_EXEE_CDM_CASHUNITERROR
	events will be sent with the details.
WFS_ERR_CDM_UNSUPPOSITION	The position specified is not supported.
WFS_ERR_CDM_INVALIDCASHUNIT	The cash unit number specified is not valid.
WFS_ERR_CDM_INVALIDRETRACTPOSIT	TION
	The <i>usIndex</i> is not supported.
WFS_ERR_CDM_NOTRETRACTAREA	The retract area specified in <i>usRetractArea</i> is
	not supported.
WFS_ERR_CDM_POSITION_NOT_EMPTY	The retract area specified in usRetractArea is
	not empty so the moving of items was not
	possible.
WFS_ERR_CDM_INCOMPLETERETRACT	Some or all of the items were not retracted
	for a reason not covered by other error
	codes. The detail will be reported with the
	WFS_EXEE_CDM_INCOMPLETERETRA
	CT event.

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated by this command:

Value	Meaning
WFS_USRE_CDM_CASHUNITTHRESHOLD	A threshold condition has been reached in
	one of the cash units.
WFS_EXEE_CDM_CASHUNITERROR	A cash unit caused an error.
WFS_SRVE_CDM_MEDIADETECTED	Media has been found in the device.
WFS_SRVE_CDM_ITEMSTAKEN	The items presented have been removed by
	the user.
WFS_EXEE_CDM_INPUT_P6	Level 2 and/or level 3 notes have been
	detected.
WFS_EXEE_CDM_INFO_AVAILABLE	Information is available for items being
	processed by this operation.
WFS_EXEE_CDM_INCOMPLETERETRACT	The command has completed with an error
	and not all of the items have been retracted.
	The detail of what was actually retracted will
	be reported in the
	WFS_EXEE_CDM_INCOMPLETERETRA
	CT event data.
WFS_SRVE_CDM_SHUTTERSTATUSCHAN	GED

The shutter status has changed.

6.17 WFS CMD CDM TEST CASH UNITS

Description

This command is used to test cash units following replenishment. All physical cash units which are testable (i.e. that have a status of WFS CDM STATCUOK or WFS CDM STATCULOW and no application lock in the logical cash unit associated with the physical cash unit) are tested. If the hardware is able to do so tests are continued even if an error occurs while testing one of the cash units. The command completes with WFS SUCCESS if the Service Provider successfully manages to test all of the testable cash units regardless of the outcome of the test. This is the case if all testable cash units could be tested and a dispense was possible from at least one of the cash units.

A WFS EXEE CDM CASHUNITERROR event will be sent for any logical cash unit which has one or more physical cash units which cannot be tested or which fail the test, even if the logical cash unit has other physical cash units which are successfully tested. If all the cash units could not be tested or no cash units are testable then a WFS ERR CDM CASHUNITERROR code will be returned and WFS EXEE CDM CASHUNITERROR events generated for every logical cash unit that encountered a problem. The operation performed to test the cash units is vendor dependent. Items may be dispensed or transported into a reject bin as a result of this command.

If no cash units are testable then a WFS ERR CDM CASHUNITERROR code will be returned and WFS EXEE CDM CASHUNITERROR events will be generated for every cash unit.

Input Param

LPWFSCDMITEMPOSITION lpPosition;

Specifies where items dispensed as a result of this command should be moved to. For a description of the WFSCDMITEMPOSITION structure see section WFS CMD CDM RESET.

If a Service Provider default configuration is to be used this parameter can be NULL.

Output Param LPWFSCDMCUINFO lpCUInfo;

The WFSCDMCUINFO structure is defined in the documentation of the WFS INF CDM CASH UNIT INFO command.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_CASHUNITERROR	A cash unit caused a problem that meant all cash units could not be tested or no cash units were testable. One or more WFS_EXEE_CDM_CASHUNITERROR events will be posted with the details.
WFS ERR CDM UNSUPPOSITION	The position specified is not supported.
WFS_ERR_CDM_SHUTTERNOTOPEN	The shutter is not open or did not open when it should have. No items presented.
WFS_ERR_CDM_SHUTTEROPEN	The shutter is open when it should be closed. No items presented.
WFS_ERR_CDM_INVALIDCASHUNIT	The cash unit number specified is not valid.
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.
WFS_ERR_CDM_PRERRORNOITEMS	There was an error during the present operation - no items were presented.
WFS_ERR_CDM_PRERRORITEMS	There was an error during the present operation - at least some of the items were presented.
WFS_ERR_CDM_PRERRORUNKNOWN	There was an error during the present operation - the position of the items is unknown. Intervention may be required to reconcile the cash amount totals.

Events

Value

In addition to the generic events defined in [Ref. 1], the following events can be generated by this command:

Value	Meaning
WFS_USRE_CDM_CASHUNITTHRESHO	OLD A threshold condition has been reached in
	one of the cash units.

CWA 16926-5:2020 (E)

WFS_EXEE_CDM_CASHUNITERROR A cash unit has failed the test or a cash unit

was not testable.

WFS_SRVE_CDM_ITEMSTAKEN The items presented have been removed by

the user.

WFS SRVE CDM CASHUNITINFOCHANGED

A cash unit was updated as a result of this

command.

WFS_EXEE_CDM_NOTEERROR An item detection error has occurred. WFS_EXEE_CDM_INPUT_P6 Level 2 and/or level 3 notes have been

detected.

WFS_SRVE_CDM_SHUTTERSTATUSCHANGED

The shutter status has changed.

WFS_EXEE_CDM_INFO_AVAILABLE Information is available for items being

processed by this operation.

6.18 WFS_CMD_CDM_SET_GUIDANCE_LIGHT

Description

This command is used to set the status of the CDM guidance lights. This includes defining the flash rate, the color and the direction. When an application tries to use a color or direction that is not supported then the Service Provider will return the generic error WFS ERR UNSUPP DATA.

Input Param

LPWFSCDMSETGUIDLIGHT lpSetGuidLight;

wGuidLight

Specifies the index of the guidance light to set as one of the values defined within the capabilities section in the *dwGuidLights* [...] field.

dwCommand

Specifies the state of the guidance light indicator as WFS_CDM_GUIDANCE_OFF or a combination of the following flags consisting of one type B, optionally one type C and optionally one type D. If no value of type C is specified then the default color is used. The Service Provider determines which color is used as the default color.

Value	Meaning	Type
WFS_CDM_GUIDANCE_OFF	The light indicator is turned off.	A
WFS_CDM_GUIDANCE_SLOW_FLASH	The light indicator is set to flash	В
	slowly.	
WFS_CDM_GUIDANCE_MEDIUM_FLASH	The light indicator is set to flash	В
	medium frequency.	
WFS_CDM_GUIDANCE_QUICK_FLASH	The light indicator is set to flash	В
	quickly.	_
WFS_CDM_GUIDANCE_CONTINUOUS	The light indicator is turned on	В
W.D.G. G.D.L. G.W.D. L.V.G.D. D.D.	continuously (steady).	~
WFS_CDM_GUIDANCE_RED	The light indicator color is set	C
WEG COM CHE MICE CONTON	to red.	G
WFS_CDM_GUIDANCE_GREEN	The light indicator color is set	C
WEG COM CHID ANCE MELLOW	to green.	C
WFS_CDM_GUIDANCE_YELLOW	The light indicator color is set	C
WEG COM CHIDANCE DITTE	to yellow.	C
WFS_CDM_GUIDANCE_BLUE	The light indicator color is set to blue.	С
WES COM CHIDANCE CVAN		С
WFS_CDM_GUIDANCE_CYAN	The light indicator color is set	C
WFS_CDM_GUIDANCE_MAGENTA	to cyan. The light indicator color is set	C
WFS_CDM_GUIDANCE_MAGENTA	to magenta.	C
WFS_CDM_GUIDANCE_WHITE	The light indicator color is set	С
WIS_CDM_GOIDANCE_WIITE	to white.	C
WFS_CDM_GUIDANCE_ENTRY	The light indicator is set	D
WIS_CDM_COIDMICD_ENTRI	to the entry state.	D
WFS CDM GUIDANCE EXIT	The light indicator is set	D
WIS_SEM_GOIDMINGS_EMI		D
	to the exit state.	

Output Param None.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_INVALID_PORT	An attempt to set a guidance light to a new value was invalid because the guidance light does not exist.

Events

Only the generic events defined in [Ref. 1] can be generated by this command.

CWA 16926-5:2020 (E)

Comments

Guidance light support was added into the CDM primarily to support guidance lights for workstations where more than one instance of a CDM is present. The original SIU guidance light mechanism was not able to manage guidance lights for workstations with multiple CDMs. This command can also be used to set the status of the CDM guidance lights when only one instance of a CDM is present.

The slow and medium flash rates must not be greater than 2.0 Hz. It should be noted that in order to comply with American Disabilities Act guidelines only a slow or medium flash rate must be used.

6.19 WFS_CMD_CDM_POWER_SAVE_CONTROL

Description

This command activates or deactivates the power-saving mode.

If the Service Provider receives another execute command while in power saving mode, the Service Provider automatically exits the power saving mode, and executes the requested command. If the Service Provider receives an information command while in power saving mode, the Service Provider will not exit the power saving mode.

Input Param

 $LPWFSCDMPOWERSAVECONTROL\ lpPowerSaveControl;$

usMaxPowerSaveRecoveryTime

Specifies the maximum number of seconds in which the device must be able to return to its normal operating state when exiting power save mode. The device will be set to the highest possible power save mode within this constraint. If *usMaxPowerSaveRecoveryTime* is set to zero then the device will exit the power saving mode.

Output Param

None.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_POWERSAVETOOSHORT	1 0
	activated because the device is not able to
	resume from the power saving mode within
	the specified
	usMaxPowerSaveRecoveryTime value.
WFS_ERR_CDM_POWERSAVEMEDIAPRES	
	The power saving mode has not been
	activated because media is present inside the
	device.
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.

Events

In addition to the generic events defined in [Ref. 1], the following events can be generated by this command:

Value Meaning
WFS_SRVE_CDM_POWER_SAVE_CHANGE The power save recovery time has changed.

Comments

None.

6.20 WFS CMD CDM PREPARE DISPENSE

Description

On some hardware it can take a significant amount of time for the dispenser to get ready to dispense media. On this type of hardware the WFS_CMD_CDM_PREPARE_DISPENSE command can be used to improve transaction performance.

If this command is supported (see the *bPrepareDispense* capability) then applications can help to improve the time taken to dispense media by issuing this command as soon as the application knows that a dispense is likely to happen. This command either prepares the device for the next dispense operation, or terminates the dispense preparation if the subsequent dispense operation is no longer required.

With the exception of the WFS_CMD_CDM_DENOMINATE and WFS_CMD_CDM_DISPENSE commands, which will not stop the dispense preparation, any execute command on CDM or CIM will automatically stop the dispense preparation.

If this command is executed and the device is already in the specified *wAction state*, then this execution will have no effect and will complete with WFS SUCCESS.

Input Param

LPWFSCDMPREPAREDISPENSE lpPrepareDispense;

wAction

A value specifying the type of actions. The value is set to one of the following values:

Value	Meaning
WFS_CDM_START	Initiates the action to prepare for the next dispense command. This command does not wait until the device is ready to dispense
	before returning a completion event, it completes as soon as the preparation has been initiated.
WFS_CDM_STOP	Stops the previously activated dispense preparation. For example the motor of the transport will be stopped. This should be used if for some reason the subsequent dispense operation is no longer required.

Output Param None.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.

Events

Only the generic events defined in [Ref. 1] can be generated by this command.

Comments

None.

6.21 WFS CMD CDM SET BLACKLIST

Description This command is used to set all blacklist information. This list is persistent. Information set by

this command overrides any existing blacklist or classification list, although it is not

recommended that an application use both this command and

WFS CMD CDM SET CLASSIFICATION LIST to avoid overlap and confusion.

Input Param This parameter should be set to NULL if the application wishes to empty the blacklist.

LPWFSCDMBLACKLIST lpBlacklist;

The LPWFSCDMBLACKLIST structure is defined in the documentation of the WFS INF CDM GET BLACKLIST command.

This is an application defined Unicode string that sets the version identifier of the blacklist. This can be set to NULL if it has no version identifier.

Number of pointers to WFSCDMBLACKLISTELEMENT structures returned in lppBlacklistElements.

lppBlacklistElements

Pointer to an array of pointers to WFSCDMBLACKLISTELEMENT structures. Each element represents a serial number, currency and value combination that a banknote will be matched against to determine if it is blacklisted.

The WFSCDMBLACKLISTELEMENT structure is defined in the documentation of the WFS INF CDM GET BLACKLIST command.

lpszSerialNumber

This Unicode string defines the serial number or a mask of serial numbers of one blacklist element with the defined currency and value. For a definition of the mask see Section 4.

The three character ISO format currency identifier [Ref. 2] of the blacklist element.

ulValue

The value of a blacklist element. This field can be set to zero to match all values.

Output Param None.

Error Codes Only the generic error codes defined in [Ref. 1] can be generated by this command.

Events Only the generic events defined in [Ref. 1] can be generated by this command.

Some classes of counterfeit banknotes have the same or similar serial numbers. By setting a serial **Comments**

number blacklist financial institutions can react quickly to a threat from counterfeit banknotes.

6.22 WFS CMD CDM SYNCHRONIZE COMMAND

Description

This command is used to reduce response time of a command (e.g. for synchronization with display) as well as to synchronize actions of the different device classes. This command is intended to be used only on hardware which is capable of synchronizing functionality within a single device class or with other device classes.

The list of execute commands which this command supports for synchronization is retrieved in the *lpdwSynchronizableCommands* parameter of the WFS_INF_CDM_CAPABILITIES.

This command is optional, i.e. any other command can be called without having to call it in advance. Any preparation that occurs by calling this command will not affect any other subsequent command. However, any subsequent execute command other than the one that was specified in the *dwCommand* input parameter will execute normally and may invalidate the pending synchronization. In this case the application should call the

WFS_CMD_CDM_SYNCHRONIZE_COMMAND again in order to start a synchronization.

Input Param

LPWFSCDMSYNCHRONIZECOMMAND lpSynchronizeCommand;

dwCommand

The command ID of the command to be synchronized and executed next.

lpCmdData

Pointer to data or a data structure that represents the parameter that is normally associated with the command that is specified in *dwCommand*. For example, if *dwCommand* is WFS_CMD_CDM_RETRACT then *lpCmdData* will point to a WFSCDMRETRACT structure. This parameter can be NULL if no command input parameter is needed or if this detail is not needed to synchronize for the command.

It will be device-dependent whether the synchronization is effective or not in the case where the application synchronizes for a command with this command specifying a parameter but subsequently executes the synchronized command with a different parameter. This case should not result in an error; however, the preparation effect could be different from what the application expects. The application should, therefore, make sure to use the same parameter between *lpCmdData* of this command and the subsequent corresponding execute command.

Output Param

None.

Error Codes

In addition to the generic error codes defined in [Ref. 1], the following error codes can be generated by this command:

Value	Meaning
WFS_ERR_CDM_EXCHANGEACTIVE	The CDM is in an exchange state.
WFS_ERR_CDM_COMMANDUNSUPP	The command specified in the dwCommand
	field is not supported by the Service
	Provider.
WFS_ERR_CDM_SYNCHRONIZEUNSUPP	The preparation for the command specified
	in the dwCommand with the parameter
	specified in the <i>lpCmdData</i> is not supported
	by the Service Provider.

Events

Only the generic events defined in [Ref. 1] can be generated by this command.

Comments

For sample flows of this synchronization see the [Ref 1] Appendix C.

6.23 WFS CMD CDM SET CLASSIFICATION LIST

Description

This command is used to specify the entire note classification list. Any items not specified in this list will be handled according to normal classification rules. This information is persistent. Information set by this command overrides any existing blacklist or classification list, although it is not recommended that an application use both this command and WFS CMD CDM SET BLACKLIST to avoid overlap and confusion.

If a note is reclassified, it is handled as though it was a note of the new classification. For example, a fit note reclassified as unfit would be treated as though it were unfit, which may mean that the note is not dispensed.

Reclassification cannot be used to change a note's classification to a higher level, for example, a note recognized as counterfeit by the device cannot be reclassified as genuine. In addition, it is not possible to re-classify a level 2 note as level 1.

If two or more classification elements specify overlapping note definitions, but different *usLevel* values then the first one takes priority.

Input Param

LPWFSCDMCLASSIFICATIONLIST lpClassificationList;

The LPWFSCDMCLASSIFICATIONLIST structure is defined in

 $WFS_INF_CDM_GET_CLASSIFICATION_LIST.\ This\ parameter\ should\ be\ set\ to\ NULL\ if\ the$

application wishes to empty the note classification list.

Output Param None

Error Codes Only the generic error codes defined in [Ref. 1] can be generated by this command.

Events Only the generic events defined in [Ref. 1] can be generated by this command.

7. Events

7.1 WFS_SRVE_CDM_SAFEDOOROPEN

Description This service event is generated when the safe door has been opened.

Event Param None. **Comments** None.

7.2 WFS_SRVE_CDM_SAFEDOORCLOSED

Description This service event is generated when the safe door has been closed.

Event Param None. **Comments** None.

7.3 WFS USRE CDM CASHUNITTHRESHOLD

Description

This user event is generated when a threshold condition has occurred in one of the logical cash units. If the logical cash unit is a shared cash unit in a compound CIM/CDM then this event can also be generated as a result of a CIM operation.

This event can be triggered either by hardware sensors in the device or by the logical *ulCount* reaching the *ulMinimum* or *ulMaximum* value as specified in the WFSCDMCASHUNIT structure.

The application can check if the device has hardware sensors by querying the *bHardwareSensor* field of the physical cash unit structure. If any of the physical cash units associated with the logical cash unit have this capability then threshold events based on hardware sensors will be triggered if the *ulMaximum* or *ulMinimum* values are not used and are set to zero.

In the situation where the cash unit is associated with multiple physical cash units the WFS_SRVE_CDM_CASHUNITINFOCHANGED event will be generated when any of the physical cash units reaches the threshold. When the final physical cash unit reaches the threshold, the WFS_USRE_CDM_CASHUNITTHRESHOLD event as well as the WFS_SRVE_CDM_CASHUNITINFOCHANGED event will be generated.

Event Param

LPWFSCDMCASHUNIT lpCashUnit;

lpCashUnit

Pointer to a WFSCDMCASHUNIT structure, describing the cash unit on which the threshold condition occurred. See *lpCashUnit->usStatus* for the current status. For a description of the WFSCDMCASHUNIT structure, see the definition of the WFS_INF_CDM_CASH_UNIT_INFO command.

Comments

None.

7.4 WFS SRVE CDM CASHUNITINFOCHANGED

Description

This service event is generated under the following circumstances:

- It is generated whenever usStatus and/or usPStatus changes. For instance, a physical
 cash unit has been removed or inserted, or a physical/logical cash unit has become empty
 or full.
- This event will also be generated for every cash unit changed in any way (including changes to counts, e.g. *ulCount*, *ulRejectCount*, *ulInitialCount*, *ulDispensedCount* and *ulPresentedCount*) as a result of the following commands:

```
WFS_CMD_CDM_SET_CASH_UNIT_INFO WFS_CMD_CDM_END_EXCHANGE
```

• This event will also be fired when any change is made to a cash unit by the following commands, except for changes to counts (e.g. *ulCount*, *ulRejectCount*, *ulInitialCount*, *ulDispensedCount* and *ulPresentedCount*):

```
WFS_CMD_CDM_CALIBRATE_CASH_UNIT WFS_CMD_CDM_TEST_CASH_UNITS
```

If the cash unit is shared cash unit in a compound CIM/CDM then this event can also be generated as a result of a CIM operation.

When a physical cash unit is removed, the status of the physical cash unit becomes WFS_CDM_STATCUMISSING. If there are no physical cash units of the same logical type remaining the status of the logical type becomes WFS_CDM_STATCUMISSING.

When a physical cash unit is inserted and this physical cash unit is of an existing logical type, both the logical and the physical cash unit structures will be updated.

If a physical cash unit of a new logical type is inserted the cash unit structure reported by the last WFS_INF_CDM_CASH_UNIT_INFO command is no longer valid. In that case an application should issue a WFS_INF_CDM_CASH_UNIT_INFO command after receiving this event to obtain updated cash unit information.

Event Param

LPWFSCDMCASHUNIT lpCashUnit;

lpCashUnit

Pointer to the changed cash unit structure. For a description of the WFSCDMCASHUNIT structure see the definition of the WFS_INF_CDM_CASH_UNIT_INFO command.

Comments

None.

7.5 WFS_SRVE_CDM_TELLERINFOCHANGED

Description This service event is generated when the counts assigned to a teller have changed. This event is

only returned as a result of a WFS_CMD_CDM_SET_TELLER_INFO command.

Event Param LPUSHORT lpusTellerID;

lpusTellerID

Pointer to an unsigned short holding the ID of the teller whose counts have changed.

7.6 WFS_EXEE_CDM_DELAYEDDISPENSE

Description This execute event is generated if the start of a dispense operation has been delayed.

Event Param LPULONG lpulDelay;

lpulDelay

Pointer to an unsigned long holding the time in milliseconds by which the dispense operation will

be delayed.

7.7 WFS_EXEE_CDM_STARTDISPENSE

Description This execute event is generated when a delayed dispense operation begins.

Event Param LPREQUESTID lpReqID;

lpReqID

Pointer to the *RequestID* of the original dispense command.

7.8 WFS_EXEE_CDM_CASHUNITERROR

Description This execute event is generated if there is a problem with a cash unit during the execution of a

command.

Event Param LPWFSCDMCUERROR lpCashUnitError;

wFailure

Specifies the kind of failure that occurred in the cash unit. Values are:

Value	Meaning
WFS_CDM_CASHUNITEMPTY	Specified cash unit is empty.
WFS_CDM_CASHUNITERROR	Specified cash unit has malfunctioned.
WFS_CDM_CASHUNITFULL	Specified cash unit is full.
WFS_CDM_CASHUNITLOCKED	Specified cash unit is locked.
WFS_CDM_CASHUNITINVALID	Specified cash unit is invalid.
WFS_CDM_CASHUNITCONFIG	An attempt has been made to change the
	settings of a self-configuring cash unit.
WFS CDM CASHUNITNOTCONF	Specified cash unit is not configured.

lpCashUnit

Pointer to the cash unit structure that caused the problem. The WFSCDMCASHUNIT structure is defined in the documentation of the WFS_INF_CDM_CASH_UNIT_INFO command. It is possible that this pointer may be NULL if the *wFailure* field is WFS_CDM_CASHUNITINVALID.

7.9 WFS_SRVE_CDM_ITEMSTAKEN

Description This service event is generated when items presented to the user have been taken. This event may

be generated at any time.

Event Param LPWORD lpfwPosition;

lpfwPosition

Pointer to the output position from which the items have been removed. Possible values are:

Value	Meaning
WFS_CDM_POSNULL	The default configuration.
WFS_CDM_POSLEFT	The left output position.
WFS_CDM_POSRIGHT	The right output position.
WFS_CDM_POSCENTER	The center output position.
WFS_CDM_POSTOP	The top output position.
WFS_CDM_POSBOTTOM	The bottom output position.
WFS_CDM_POSFRONT	The front output position.
WFS CDM POSREAR	The rear output position.

7.10 WFS_SRVE_CDM_COUNTS_CHANGED

Description This service event is generated if the device is a compound device together with a CIM and the

counts in a shared cash unit have changed as a result of any CIM operation other than WFS_CMD_CIM_SET_CASH_UNIT_INFO and WFS_CMD_CIM_END_EXCHANGE.

Event Param LPWFSCDMCOUNTSCHANGED lpCountsChanged;

usCount

The size of lpusCUNumList.

lpusCUNumList

Pointer to a list of the usNumber values of the cash units whose counts have changed.

7.11 WFS_EXEE_CDM_PARTIALDISPENSE

Description This execute event is generated when a dispense operation is divided into several sub-dispense

operations because the hardware capacity of the CDM is exceeded.

Event Param LPUSHORT lpusDispNum;

lpusDispNum

Pointer to an unsigned short holding the number of sub-dispense operations into which the

dispense operation has been divided.

7.12 WFS_EXEE_CDM_SUBDISPENSEOK

Description This execute event is generated when one of the sub-dispense operations into which the dispense

operation was divided has finished successfully.

Event Param LPWFSCDMDENOMINATION lpDenomination;

lpDenomination

The WFSCDMDENOMINATION structure is defined in the documentation of the command WFS_CMD_CDM_DENOMINATE. Note that in this case the values in this structure report the

amount and number of each denomination dispensed in the sub-dispense operation.

7.13 WFS_EXEE_CDM_INCOMPLETEDISPENSE

Description This execute event is generated during WFS_CMD_CDM_DISPENSE when it has not been

possible to dispense the entire denomination but part of the requested denomination is on the

intermediate stacker or in customer access.

Event Param LPWFSCDMDENOMINATION lpDenomination;

lpDenomination

The WFSCDMDENOMINATION structure is defined in the documentation of the command WFS_CMD_CDM_DENOMINATE. Note that in this case the values in this structure report the amount and number of each denomination that are in customer access or on the intermediate stacker. WFS_INF_CDM_PRESENT_STATUS can be used to determine whether the items are

in customer access.

7.14 WFS_EXEE_CDM_NOTEERROR

Description This execute event specifies the reason for a note detection error during the execution of a

command.

Event Param LPUSHORT lpusReason;

lpusReason

Pointer to an unsigned short holding the reason for the notes detection error. Possible values are:

Value	Meaning
WFS_CDM_DOUBLENOTEDETECTED	Double notes have been detected.
WFS_CDM_LONGNOTEDETECTED	A long note has been detected.
WFS_CDM_SKEWEDNOTE	A skewed note has been detected.
WFS_CDM_INCORRECTCOUNT	An item counting error has occurred.
WFS_CDM_NOTESTOOCLOSE	Notes have been detected as being too close.
WFS_CDM_OTHERNOTEERROR	An item error not covered by the other
	values has been detected.
WFS CDM SHORTNOTEDETECTED	Short notes have been detected.

7.15 WFS_SRVE_CDM_ITEMSPRESENTED

Description This service event specifies that items have been presented to the user during a count operation

and need to be taken.

Event Param None. **Comments** None.

7.16 WFS_SRVE_CDM_MEDIADETECTED

Description This service event is generated if media is detected during a reset (WFS CMD CDM RESET).

The parameter on the event informs the application of the position of the media after the reset completes. If the device has been unable to successfully move the items found then this parameter

will be NULL.

Event Param LPWFSCDMITEMPOSITION *lpItemPosition;

For a description of this parameter see section WFS_CMD_CDM_RESET. This parameter is a

pointer to a pointer to WFSCDMITEMPOSITION structure.

7.17 WFS_EXEE_CDM_INPUT_P6

Description This execute event is generated if level 2 and/or level 3 notes are detected during execution of a

CDM command.

Event Param None.Comments None.

7.18 WFS_SRVE_CDM_DEVICEPOSITION

Description This service event reports that the device has changed its position status.

Event Param LPWFSCDMDEVICEPOSITION lpDevicePosition;

wPosition

Position of the device as one of the following values:

Value	Meaning
WFS_CDM_DEVICEINPOSITION	The device is in its normal operating
	position.
WFS_CDM_DEVICENOTINPOSITION	The device has been removed from its
	normal operating position.
WFS CDM DEVICEPOSUNKNOWN	The position of the device cannot be
	determined.

7.19 WFS_SRVE_CDM_POWER_SAVE_CHANGE

Description This service event specifies that the power save recovery time has changed.

Event Param LPWFSCDMPOWERSAVECHANGE lpPowerSaveChange;

usPowerSaveRecoveryTime

Specifies the actual number of seconds required by the device to resume its normal operational state. This value is zero if the device exited the power saving mode.

Comments

If another device class compounded with this device enters into a power saving mode, this device will automatically enter into the same power saving mode and this event will be generated.

7.20 WFS_EXEE_CDM_INFO_AVAILABLE

Description This execute event is generated when information is available for items being processed by the

Service Provider.

Event Param LPWFSCDMITEMINFOSUMMARY *lppItemInfoSummary;

Pointer to a NULL-terminated array of pointers to WFSCDMITEMINFOSUMMARY structures, one structure for every level.

usLevel

Defines the note level. Possible values are:

Value	Meaning
WFS_CDM_LEVEL_1	Information for level 1 notes.
WFS_CDM_LEVEL_2	Information for level 2 notes.
WFS_CDM_LEVEL_3	Information for level 3 notes.
WFS_CDM_LEVEL_4	Information for level 4 notes.

usNumOfItems

Number of items classified as *usLevel* which have information available.

7.21 WFS_EXEE_CDM_INCOMPLETERETRACT

Description This execute event is sent when the WFS_CMD_CDM_RETRACT or

WFS_CMD_CDM_RESET command has completed with an error and not all of the items have

been retracted.

Event Param LPWFSCDMINCOMPLETERETRACT lpIncompleteRetract;

lpItemNumberList

The lpItemNumberList parameter is a WFSCDMITEMNUMBERLIST structure as defined in the description of the command WFS_CMD_CDM_RETRACT. Note that in this case the values in this structure report the amount and number of each denomination that were successfully moved during the command prior to the failure.

usReason

The reason for not having retracted items. The value is specified as one of the following values:

Value	Meaning
WFS_CDM_IRRETRACTFAILURE	The retract has partially failed for a reason not covered by the other reasons listed in this event, for example failing to pick an item to be retracted.
WFS_CDM_IRRETRACTAREAFULL	The specified retract area (see input parameter <i>usRetractArea</i>) has become full during the retract operation.
WFS_CDM_IRFOREIGNITEMSDETECTED WFS_CDM_IRINVALIDBUNCH	Foreign items have been detected. An invalid bunch of items has been detected, e.g. it is too large or could not be processed.

7.22 WFS_SRVE_CDM_SHUTTERSTATUSCHANGED

Description

Within the limitations of the hardware sensors this service event is generated whenever the status of a shutter changes. The shutter status can change because of an explicit, implicit or manual operation depending on how the shutter is operated.

Event Param

LPWFSCDMSHUTTERSTATUSCHANGED lpShutterStatusChanged;

fwPosition

Specifies one of the CDM output positions whose shutter status has changed as one of the following values:

Value	Meaning
WFS_CDM_POSLEFT	Left output position.
WFS_CDM_POSRIGHT	Right output position.
WFS_CDM_POSCENTER	Center output position.
WFS_CDM_POSTOP	Top output position.
WFS_CDM_POSBOTTOM	Bottom output position.
WFS_CDM_POSFRONT	Front output position.
WFS_CDM_POSREAR	Rear output position.

fwShutter

Specifies the new state of the shutter as one of the following values:

Value	Meaning
WFS_CDM_SHTCLOSED	The shutter is closed.
WFS_CDM_SHTOPEN	The shutter is opened.
WFS_CDM_SHTJAMMED	The shutter is jammed.
WFS_CDM_SHTUNKNOWN	Due to a hardware error or other condition,
	the state of the shutter cannot be determined.

Comments

None.

8. Sub-Dispensing Command Flow

"Sub-dispensing" of bills occur when a WFS_CMD_CDM_DISPENSE execute command is issued and the required number of bills to be dispensed exceeds the CDM hardware limit for bills that can be dispensed with a single "hardware level" dispense command. In this situation, the CDM Service Provider determines the number of "hardware level" dispense commands required and enters what is referred to as a "sub-dispensing" operation until the full amount has been dispensed. Through use of a "sub-dispensing" operation the application is fully removed from "hardware level dependencies" as to how many bills can be dispensed based on hardware vendor design limitations.

The following series of tables illustrate the steps taken on behalf of an end-user, application, XFS Service Provider, and CDM hardware for sub-dispensing operations: All examples below assume the *bPresent* field in the WFS CMD CDM DISPENSE command is set to TRUE.

Sub-Dispensing Is Not Required - Transaction Successful

This table illustrates a successful WFS_CMD_CDM_DISPENSE command where sub-dispensing is not required:

Step	End-User	Application	XFS SP	CDM
				Hardware
1.	User wants to dispense 40 USD.			
2.		WFS_CMD_CDM_DISPENSE command issued.		
3.			Determines that a single "hardware level" dispense command can be issued for full dispense request.	
4.			"Hardware level" dispense command issued.	
5.			WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTOPEN) event generated	Items presented.
6.		WFS_CMD_CDM_DISPENSE completes successfully.		
7.	User takes bills.			
8.			WFS_SRVE_CDM_ITEMSTAKEN event generated. WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTCLOSED) event generated	

Sub-Dispensing Is Required - Command Successful
This table illustrates a successful WFS_CMD_CDM_DISPENSE command where sub-dispensing is required:

Step	End-User	Application	XFS SP	CDM Hardware
1.	User wants to dispense 130 USD in 1 USD denominations.			
2.		WFS_CMD_CDM_DISPENSE command issued.		
3.		Communa issued.	Three "hardware level" dispense commands are required. CDM hardware is limited to dispensing 50 bills in any single "hardware level" dispense.	
4.			WFS_EXEE_CDM_PARTIAL- DISPENSE event generated.	
5.			"Hardware level" dispense command issued for 50 USD.	
6.			WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTOPEN) event generated	Items presented.
7.			WFS_SRVE_CDM_SUBDISPENSEOK event generated.	
8. 9.	User takes bills.		WFS_SRVE_CDM_ITEMSTAKEN event generated. WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTCLOSED) event generated	
10.			"Hardware level" dispense command issued for 50 USD.	
11.			WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTOPEN) event generated	Items presented.
12.			WFS_SRVE_CDM_SUBDISPENSE_O K event generated.	
13.	User takes bills.			
14.			WFS_SRVE_CDM_ITEMSTAKEN event generated. WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTCLOSED) event generated	
15.			"Hardware level" dispense command issued for 30 USD.	
16.			WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTOPEN) event generated	Items presented.
17.			WFS_SRVE_CDM_SUBDISPENSEOK event generated.	
18.		WFS_CMD_CDM_DISPENSE completes successfully.	Č	
19.	User takes bills.			
20.			WFS_SRVE_CDM_ITEMSTAKEN event generated. WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTCLOSED) event generated	

Sub-Dispensing Is Required - Command UnsuccessfulThis table illustrates an unsuccessful WFS_CMD_CDM_DISPENSE command where sub-dispensing is required and the end-user does not take the bills during the second "hardware level" dispense, resulting in a timeout condition.

Step	End-User	Application	XFS SP	CDM Hardware
1.	User wants to dispense 130 USD in 1 USD denominations.			
2.		WFS_CMD_CDM_DISPENSE command issued.		
3.			Three "hardware level" dispense commands are required. CDM hardware is limited to dispensing 50 bills in any single "hardware level" dispense command.	
4.			WFS_EXEE_CDM_PARTIAL- DISPENSE event generated.	
5.			"Hardware level" dispense command issued for 50 USD.	
6.			WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTOPEN) event generated	Items presented
7.			WFS_SRVE_CDM_SUBDISPENSEOK event generated.	
8.	User takes bills.			
9.			WFS_SRVE_CDM_ITEMSTAKEN event generated. WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTCLOSED) event generated	
10.			"Hardware level" dispense command issued for 50 USD.	
11.			WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTOPEN) event generated	Items presented.
12.			WFS_SRVE_CDM_SUBDISPENSEOK event generated.	
13.	User does not take bills.			
14.			Timeout occurs waiting on end-user to take bills.	
15.		WFS_CMD_CDM_DISPENSE completes with WFS_ERR_CDM_ITEMSNOT-TAKEN.		

9. Rules for Cash Unit Exchange

The XFS Start and End Exchange commands should be used by applications to supply the latest information with regards to cash unit replenishment state and content. This guarantees a certain amount of control to an application as to which denominations are stored in which position as well as the general physical state of the logical/physical cash units.

If a cash unit is removed from the CDM outside of the Start/End Exchange operations and subsequently reinserted the status of the physical cash unit should be set to WFS_CDM_STATCUMANIP to indicate to the application that the physical cash unit has been removed, reinserted and possibly tampered with. While the cash unit has this status the Service Provider should not attempt to use it as part of a Dispense operation. The

WFS_CDM_STATCUMANIP status should not change until the next Start/End Exchange operation is performed, even if the cash unit is replaced in its original position.

If all the physical cash units belonging to a logical cash unit are manipulated the parent logical cash unit that the physical cash units belong to should also have its status set to WFS_CDM_STATCUMANIP.

When a cash unit is removed and/or replaced outside of the Start/End Exchange operations the original logical cash unit information such as the values, currency and counts should be preserved in the Cash Unit Info structure reported to the application for accounting purposes until the next Start/End Exchange operations, even if the cash unit physically contains a different denomination.

10. Events Associated with Cash Unit Status Changes

The following instances illustrate which events will be posted when the cash unit statuses change. In all cases bHardwareSensor == TRUE, ulMaximum == 0 and ulMinimum == 0.

10.1 One Physical Cash Unit Goes LOW

The following table describes a dispense transaction case where the status of a physical cash unit only changes from WFS_CDM_STATCULOW.

• Logical CU 1 consists of Physical CU 1 and Physical CU 2

	Action	Status/Event	
1.		Logical CU 1: WFS_CDM_STATCUOK	
		- Physical CU 1: WFS_CDM_STATCUOK	
		- Physical CU 2: WFS_CDM_STATCUOK	
2.	A user withdraws items.		
3.	The device dispenses and presents the items from		
	Physical CU 1, whose status changes to low.		
4.	The status of Logical CU 1 does not change.	Logical CU 1: WFS_CDM_STATCUOK	
		- Physical CU 1: WFS_CDM_STATCULOW	
		- Physical CU 2: WFS_CDM_STATCUOK	
		WFS_SRVE_CDM_CASHUNITINFOCHANGED	

10.2 Last Physical Cash Unit Goes LOW

The following table describes a dispense transaction case where the status of a logical cash unit changes from WFS_CDM_STATCUOK to WFS_CDM_STATCULOW.

• Logical CU 1 consists of Physical CU 1 and Physical CU 2

	Action	Status/Event
1.		Logical CU 1: WFS_CDM_STATCUOK
		- Physical CU 1: WFS_CDM_STATCULOW
		- Physical CU 2: WFS_CDM_STATCUOK
2.	A user withdraws items.	
3.	The device dispenses and presents the items from	
	Physical CU 2, whose status changes to low.	
4.	As a result, the status of Logical CU 1 changes to	Logical CU 1: WFS_CDM_STATCULOW
	low.	- Physical CU 1: WFS CDM STATCULOW
		- Physical CU 2: WFS_CDM_STATCULOW
		WFS_SRVE_CDM_CASHUNITINFOCHANGED
		WFS USRE CDM CASHUNITTHRESHOLD

10.3 One Physical Cash Unit Goes INOP

The following table describes a dispense transaction case where the status of a logical cash unit changes from WFS_CDM_STATCUOK to WFS_CDM_STATCULOW as the result of a physical cash unit failure.

- Logical CU 1 consists of Physical CU 1 and Physical CU 2
- The device has ability to continue transaction when a problem occurs in a physical cash unit.

	Action	Status/Event	
1.		Logical CU 1: WFS_CDM_STATCUOK	
		- Physical CU 1: WFS_CDM_STATCUOK	
		- Physical CU 2: WFS_CDM_STATCULOW	
2.	A user withdraws items.		
3.	The device tries to dispense the items from		
	Physical CU 1; however, a problem occurs in the		
	cash unit, whose status changes to inoperative.		
4.	The device complements the items by dispensing		
	from Physical CU 2.		
5.	As a result, the status of Logical CU 1 changes to	Logical CU 1: WFS_CDM_STATCULOW	
	low.	- Physical CU 1: WFS_CDM_STATCUINOP	
		- Physical CU 2: WFS_CDM_STATCULOW	
		WFS_EXEE_CDM_CASHUNITERROR	
		WFS_SRVE_CDM_CASHUNITINFOCHANGED	
		WFS_USRE_CDM_CASHUNITTHRESHOLD	

10.4 Last Physical Cash Unit Goes EMPTY

The following table describes a dispense transaction case where the status of a logical cash unit changes from WFS_CDM_STATCULOW to WFS_CDM_STATCUEMPTY.

• Logical CU 1 consists of Physical CU 1 and Physical CU 2

	Action	Status/Event
1.		Logical CU 1: WFS_CDM_STATCULOW
		- Physical CU 1: WFS_CDM_STATCUEMPTY
		- Physical CU 2: WFS_CDM_STATCULOW
2.	A user withdraws items.	
3.	The device dispenses and presents the items from	
	Physical CU 2, whose status changes to empty.	
4.	As a result, the status of Logical CU 1 changes to	Logical CU 1: WFS_CDM_STATCUEMPTY
	empty.	- Physical CU 1: WFS CDM STATCUEMPTY
		- Physical CU 2: WFS_CDM_STATCUEMPTY
		WFS_SRVE_CDM_CASHUNITINFOCHANGED

11. Multiple Dispense Command Flow

The Multiple Dispense feature occurs when a WFS_CMD_CDM_DISPENSE execute command is issued multiple times to place items on the stacker. Adding to the stacked items with a second or third dispense may be required where the initially picked Cash Unit fails to fulfill the full dispense request. The application can choose to add to the stacker from another Cash Unit to fulfill the request. Additionally this feature covers the requirement to dispense multiple currencies with a mix number other than WFS_CDM_INDIVIDUAL. Multiple currencies can be picked separately with the bunch of items assembled on the stacker before presentation to the customer.

Applications can refer to WFSCDMCAPS. fwMoveItems to determine if the Service Provider supports the feature. If a Service Provider supports this feature but an application does not wish to use it, the application should check WFSCDMSTATUS. fwIntermediateStacker to determine whether items on the stacker need to be purged prior to a dispense.

Multiple Dispense Example 'Out of Notes'

In the following example WFSCDMCAPS. fwMoveItems reports WFS_CDM_TOSTACKER. The CDM has 2 logical Cash Units. Cash Unit 1 has 20USD, Cash Unit 2 has 10USD. Cash Unit 1 has only 2 notes left. This table illustrates multiple WFS_CMD_CDM_DISPENSE commands to fulfill a dispense request.

Step	End-User	Application	XFS SP	CDM Hardware
1.	User wants to dispense 60 USD.	WFS_CMD_CDM_DISPENSE usMixNumber = WFS_CDM_INDIVIDUAL bPresent = FALSE Request USD20x3 from Cash Unit 1.		2 of 3 items picked and stacked.
2.			WFS_EXEE_CDM_INCOMPLETEDISP ENSE event.	
			lpDenomination output records that 2x20USD were stacked.	
3.			WFS_CMD_CDM_DISPENSE completes WFS_ERR_CDM_NOTDISPENSABLE	
4.		The application decides that the dispense can be fulfilled and calculates the 20USD shortfall can be made up from the 10USD Cash Unit. WFS_CMD_CDM_DISPENSE usMixNumber = WFS_CDM_INDIVIDUAL bPresent = FALSE Request USD10x2 from Cash Unit 2.		2 of 2 notes picked and stacked together with the items already stacked.
5.			WFS_CMD_CDM_DISPENSE completes WFS_SUCCESS lpDenomination output records that 2x10USD were stacked.	
6.		Call WFS_CMD_CDM_PRESENT	WFS_SRVE_CDM_SHUTTERSTATUS- CHANGED(WFS_CDM_SHTOPEN) event generated	Items presented.
7.			WFS_CMD_CDM_PRESENT completes WFS_SUCCESS	
8.	User takes bills.		WFS_SRVE_CDM_ITEMSTAKEN event generated. WFS_SRVE_CDM_SHUTTERSTATUS-CHANGED(WFS_CDM_SHTCLOSED) event generated	

Multiple Dispense Example 'Multiple Currency with Vendor Mix'

In the following example WFSCDMCAPS *fwMoveItems* reports WFS_CDM_TOSTACKER. The CDM has 2 logical Cash Units with good supply of notes in each. Cash Unit 1 has 20CHF, Cash Unit 2 has 20EUR.

This table illustrates multiple WFS_CMD_CDM_DISPENSE commands to fulfill a dispense request of EUR and CHF notes with vendor defined mix number. WFSCDMMIXTYPE.usMixNumber = 1.

Step	End-User	Application	XFS SP	CDM Hardware
1.	User wants to dispense 100 EUR and 100 CHF.	Application will split the dispense stacking all money before a single present. WFS_CMD_CDM_DISPENSE usMixNumber = 1 bPresent = FALSE Request 100 EUR.		100 EUR picked and stacked.
2.			WFS_CMD_CDM_DISPENSE completes WFS_SUCCESS <i>lpDenomination</i> output records that 5x20EUR were stacked.	
3.		WFS_CMD_CDM_DISPENSE usMixNumber = WFS_CDM_INDIVIDUAL bPresent = FALSE Request 100 CHF.		100 CHF picked and stacked.
4.			WFS_CMD_CDM_DISPENSE completes WFS_SUCCESS <i>lpDenomination</i> output records that 5x20CHF were stacked.	
5.		Call WFS_CMD_CDM_PRESENT	WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTOPEN) event generated	Items presented.
6.			WFS_CMD_CDM_PRESENT completes WFS_SUCCESS	
7.	User takes bills.		WFS_SRVE_CDM_ITEMSTAKEN event generated. WFS_SRVE_CDM_SHUTTERSTATUS CHANGED(WFS_CDM_SHTCLOSED) event generated	

12. C - Header file

```
/******************************
 * xfscdm.h XFS - Cash Dispenser (CDM) definitions
                                Version 3.40 (December 6 2019
 ************************
 #ifndef __INC_XFSCDM__H
 #define INC XFSCDM H
 #ifdef __cplu
extern "C" {
                  cplusplus
 #endif
 #include <xfsapi.h>
 /* be aware of alignment */
 #pragma pack (push, 1)
 /* values of WFSCDMCAPS.wClass */
                  WFS_SERVICE_CLASS_CDM
WFS_SERVICE_CLASS_VERSION_CDM
 #define
                                                                                                                (3)
                                                                                                                (0x2803) /* Version 3.40 */
 #define
 #define
                      WFS SERVICE CLASS NAME CDM
                                                                                                               "CDM"
 #define
                      CDM SERVICE OFFSET
                                                                                                              (WFS SERVICE CLASS CDM * 100)
 /* CDM Info Commands */
#define WFS_INF_CDM_STATUS (CDM_SERVICE_OFFSET + 1)
#define WFS_INF_CDM_CAPABILITIES (CDM_SERVICE_OFFSET + 2)
#define WFS_INF_CDM_CASH_UNIT_INFO (CDM_SERVICE_OFFSET + 3)
#define WFS_INF_CDM_TELLER_INFO (CDM_SERVICE_OFFSET + 4)
#define WFS_INF_CDM_CURRENCY_EXP (CDM_SERVICE_OFFSET + 6)
#define WFS_INF_CDM_MIX_TYPES (CDM_SERVICE_OFFSET + 7)
#define WFS_INF_CDM_MIX_TABLE (CDM_SERVICE_OFFSET + 8)
#define WFS_INF_CDM_PRESENT_STATUS (CDM_SERVICE_OFFSET + 9)
#define WFS_INF_CDM_GET_ITEM_INFO (CDM_SERVICE_OFFSET + 10)
#define WFS_INF_CDM_GET_BLACKLIST (CDM_SERVICE_OFFSET + 11)
#define WFS_INF_CDM_GET_ALL_ITEMS_INFO (CDM_SERVICE_OFFSET + 12)
#define WFS_INF_CDM_GET_CLASSIFICATION_LIST (CDM_SERVICE_OFFSET + 12)
 /* CDM Execute Commands */
#define WFS_CMD_CDM_DENOMINATE
#define WFS_CMD_CDM_DISPENSE
#define WFS_CMD_CDM_PRESENT
#define WFS_CMD_CDM_REJECT
#define WFS_CMD_CDM_RETRACT
#define WFS_CMD_CDM_OPEN_SHUTTER
#define WFS_CMD_CDM_CLOSE_SHUTTER
#define WFS_CMD_CDM_SET_TELLER_INFO
#define WFS_CMD_CDM_SET_CASH_UNIT_INFO
#define WFS_CMD_CDM_START_EXCHANGE
#define WFS_CMD_CDM_END_EXCHANGE
#define WFS_CMD_CDM_OPEN_SAFE_DOOR
#define WFS_CMD_CDM_OPEN_SAFE_DOOR
#define WFS_CMD_CDM_CALIBRATE_CASH_UNIT
#define WFS_CMD_CDM_RESET
#define WFS_CMD_CDM_RESET
#define WFS_CMD_CDM_TEST_CASH_UNITS
#define WFS_CMD_CDM_TEST_CASH_UNITS
#define WFS_CMD_CDM_CDUNT
#define WFS_CMD_CDM_COUNT
#define WFS_CMD_CDM_SET_GUIDANCE_LIGHT
                                                                                                             (CDM SERVICE OFFSET + 1)
                                                                                                             (CDM SERVICE OFFSET + 2)
                                                                                                               (CDM_SERVICE_OFFSET + 3)
(CDM_SERVICE_OFFSET + 4)
                                                                                                               (CDM SERVICE OFFSET + 5)
                                                                                                             (CDM SERVICE OFFSET + 7)
                                                                                                             (CDM SERVICE OFFSET + 8)
                                                                                                            (CDM_SERVICE_OFFSET + 9)
(CDM_SERVICE_OFFSET + 10)
(CDM_SERVICE_OFFSET + 11)
                                                                                                             (CDM SERVICE OFFSET + 12)
                                                                                                            (CDM SERVICE OFFSET + 13)
                                                                                                         (CDM_SERVICE_OFFSET + 15)
                                                                                                              (CDM_SERVICE_OFFSET + 20)
(CDM_SERVICE_OFFSET + 21)
                                                                                                             (CDM SERVICE OFFSET + 22)
                                                                                                            (CDM SERVICE OFFSET + 23)
 #define WFS_CMD_CDM_SET_GUIDANCE_LIGHT #define WFS_CMD_CDM_POWER_SAVE_CONTROL
                                                                                                        (CDM_SERVICE_OFFSET + 24)
(CDM_SERVICE_OFFSET + 25)
 #define #define
                       WFS CMD CDM PREPARE DISPENSE
                                                                                                                (CDM SERVICE OFFSET + 26)
```

```
#define WFS_CMD_CDM_SET_BLACKLIST
#define WFS_CMD_CDM_SYNCHRONIZE_COMMAND
#define WFS_CMD_CDM_SET_CLASSIFICATION_LIST
                                                                                                                (CDM SERVICE OFFSET + 27)
                      WFS_CMD_CDM_SET_BLACKLIST (CDM_SERVICE_OFFSET + 27)
WFS_CMD_CDM_SYNCHRONIZE_COMMAND (CDM_SERVICE_OFFSET + 28)
WFS_CMD_CDM_SET_CLASSIFICATION_LIST (CDM_SERVICE_OFFSET + 29)
/* CDM Messages */
#define WFS_SRVE_CDM_SAFEDOOROPEN
#define WFS_SRVE_CDM_SAFEDOORCLOSED
#define WFS_USRE_CDM_CASHUNITTHRESHOLD
#define WFS_SRVE_CDM_CASHUNITINFOCHANGED
#define WFS_SRVE_CDM_TELLERINFOCHANGED
                                                                                                                  (CDM_SERVICE_OFFSET + 1)
                                                                                                                 (CDM_SERVICE_OFFSET + 2)
(CDM_SERVICE_OFFSET + 3)
                                                                                                            (CDM_SERVICE_OFFSET + 4)
(CDM_SERVICE_OFFSET + 4)
(CDM_SERVICE_OFFSET + 5)
#define WFS_EXEE_CDM_DELAYEDDISPENSE (CDM_SERVICE_OFFSET + 6)
#define WFS_EXEE_CDM_STARTDISPENSE (CDM_SERVICE_OFFSET + 7)
#define WFS_EXEE_CDM_CASHUNITERROR (CDM_SERVICE_OFFSET + 7)
#define WFS_SRVE_CDM_ITEMSTAKEN (CDM_SERVICE_OFFSET + 8)
#define WFS_EXEE_CDM_PARTIALDISPENSE (CDM_SERVICE_OFFSET + 9)
#define WFS_EXEE_CDM_SUBDISPENSEOK (CDM_SERVICE_OFFSET + 10)
#define WFS_SRVE_CDM_ITEMSPRESENTED (CDM_SERVICE_OFFSET + 11)
#define WFS_SRVE_CDM_COUNTS_CHANGED (CDM_SERVICE_OFFSET + 13)
#define WFS_EXEE_CDM_INCOMPLETEDISPENSE (CDM_SERVICE_OFFSET + 15)
#define WFS_EXEE_CDM_NOTEERROR (CDM_SERVICE_OFFSET + 16)
#define WFS_SRVE_CDM_MEDIADETECTED (CDM_SERVICE_OFFSET + 17)
#define WFS_SRVE_CDM_DEVICEPOSITION (CDM_SERVICE_OFFSET + 18)
#define WFS_SRVE_CDM_DEVICEPOSITION (CDM_SERVICE_OFFSET + 19)
#define WFS_SRVE_CDM_POWER_SAVE_CHANGE (CDM_SERVICE_OFFSET + 20)
#define WFS_EXEE_CDM_INFO_AVAILABLE (CDM_SERVICE_OFFSET + 21)
#define WFS_EXEE_CDM_INCOMPLETERETRACT (CDM_SERVICE_OFFSET + 22)
#define WFS_SRVE_CDM_SHUTTERSTATUSCHANGED (CDM_SERVICE_OFFSET + 22)
 #define WFS_EXEE_CDM_DELAYEDDISPENSE
                                                                                                               (CDM SERVICE OFFSET + 6)
 /* values of WFSCDMSTATUS.fwDevice */
#define WFS_CDM_DEVONLINE WFS_CDM_DEVOFFLINE
                                                                                                                 WFS STAT DEVONLINE
                                                                                                                  WFS STAT DEVOFFLINE
 #define WFS_CDM_DEVPOWEROFF
                                                                                                                  WFS_STAT_DEVPOWEROFF
#define WFS_CDM_DEVNODEVICE
#define WFS_CDM_DEVHWERROR
#define WFS_CDM_DEVUSERERROR
#define WFS_CDM_DEVBUSY
                                                                                                                 WFS_STAT_DEVNODEVICE
WFS_STAT_DEVHWERROR
                                                                                                               WFS STAT DEVUSERERROR
                                                                                                              WFS STAT DEVBUSY
 #define WFS_CDM_DEVFRAUDATTEMPT
                                                                                                               WFS STAT DEVFRAUDATTEMPT
 #define WFS CDM DEVPOTENTIALFRAUD
                                                                                                               WFS STAT DEVPOTENTIALFRAUD
/* values of WFSCDMSTATUS.fwSafeDoor */
                      WFS CDM DOORNOTSUPPORTED
 #define
                                                                                                                  (1)
 #define WFS_CDM_DOOROPEN
                                                                                                                  (2)
 #define
                        WFS CDM DOORCLOSED
                                                                                                                  (3)
                  WFS_CDM_DOORUNKNOWN
 #define
                                                                                                                  (5)
 /* values of WFSCDMSTATUS.fwDispenser */
#define WFS_CDM_DISPOK
#define WFS_CDM_DISPCUSTATE
#define WFS_CDM_DISPCUSTOP
#define WFS_CDM_DISPCUUNKNOWN
                                                                                                                  (0)
                                                                                                                   (1)
                                                                                                                  (2)
                                                                                                                  (3)
 /* values of WFSCDMSTATUS.fwIntermediateStacker */
                       WFS CDM ISEMPTY
 #define
                                                                                                                  (0)
 #define WFS_CDM_ISNOTEMPTY
                                                                                                                  (1)
 #define WFS CDM ISNOTEMPTYCUST
                                                                                                                  (2)
 #define WFS_CDM_ISNOTEMPTYUNK
                                                                                                                  (3)
 #define WFS_CDM_ISUNKNOWN #define WFS_CDM_ISNOTSUPPORTED
                                                                                                                  (4)
                                                                                                                  (5)
 /* Size and max index of dwGuidLights array */
 #define WFS_CDM_GUIDLIGHTS_SIZE #define WFS_CDM_GUIDLIGHTS_MAX
                                                                                                                  (32)
                                                                                                                  (WFS CDM GUIDLIGHTS SIZE - 1)
```

```
/* Indices of WFSCDMSTATUS.dwGuidLights [...]
                          WFSCDMCAPS.dwGuidLights [...] */
#define WFS_CDM_GUIDANCE_POSOUTNULL
#define WFS_CDM_GUIDANCE_POSOUTLEFT
#define WFS_CDM_GUIDANCE_POSOUTRIGHT
#define WFS_CDM_GUIDANCE_POSOUTCENTER
#define WFS_CDM_GUIDANCE_POSOUTTOP
#define WFS_CDM_GUIDANCE_POSOUTBOTTOM
#define WFS_CDM_GUIDANCE_POSOUTFRONT
#define WFS_CDM_GUIDANCE_POSOUTREAR
                                                                                                              (0)
                                                                                                              (1)
                                                                                                             (2)
                                                                                                             (3)
                                                                                                             (4)
                                                                                                             (5)
                                                                                                             (6)
                                                                                                             (7)
 /* Values of WFSCDMSTATUS.dwGuidLights [...]
                       WFSCDMCAPS.dwGuidLights [...] */
#define WFS_CDM_GUIDANCE_NOT_AVAILABLE
#define WFS_CDM_GUIDANCE_OFF
#define WFS_CDM_GUIDANCE_SLOW_FLASH
#define WFS_CDM_GUIDANCE_MEDIUM_FLASH
#define WFS_CDM_GUIDANCE_QUICK_FLASH
#define WFS_CDM_GUIDANCE_CONTINUOUS
#define WFS_CDM_GUIDANCE_RED
#define WFS_CDM_GUIDANCE_GREEN
#define WFS_CDM_GUIDANCE_YELLOW
#define WFS_CDM_GUIDANCE_YELLOW
#define WFS_CDM_GUIDANCE_BLUE
#define WFS_CDM_GUIDANCE_CYAN
#define WFS_CDM_GUIDANCE_MAGENTA
#define WFS_CDM_GUIDANCE_WHITE
#define WFS_CDM_GUIDANCE_ENTRY
#define WFS_CDM_GUIDANCE_ENTRY
#define WFS_CDM_GUIDANCE_EXIT
                                                                                                           (0x00000000)
                                                                                                         (0 \times 000000001)
                                                                                                    (0x00000008)
(0x000000010)
                                                                                                            (0\times00000080)
                                                                                                          (0 \times 00000100)
                                                                                                            (0x00000200)
                                                                                                            (0x00000400)
                                                                                                             (0x00000800)
                                                                                                             (0x00001000)
                                                                                                            (0 \times 00002000)
                                                                                                          (0x00004000)
                                                                                                            (0x00100000)
                                                                                                             (0x00200000)
 /* values of WFSCDMSTATUS.wDevicePosition
                         WFSCDMDEVICEPOSITION.wPosition */
 #define WFS_CDM_DEVICEINPOSITION
#define WFS_CDM_DEVICENOTINPOSITION
#define WFS_CDM_DEVICEPOSUNKNOWN
#define WFS_CDM_DEVICEPOSNOTSUPP
                                                                                                              (0)
                                                                                                              (1)
                                                                                                              (2)
                                                                                                              (3)
 /* values of WFSCDMOUTPOS.fwShutter */
 #define WFS_CDM_SHTCLOSED #define WFS_CDM_SHTOPEN #define WFS_CDM_SHTJAMMED
                                                                                                              (0)
                                                                                                              (1)
                                                                                                              (2)
 #define
                     WFS CDM SHTUNKNOWN
                                                                                                              (3)
 #define
                     WFS CDM SHTNOTSUPPORTED
                                                                                                              (4)
 /* values of WFSCDMOUTPOS.fwPositionStatus */
 #define WFS_CDM_PSEMPTY
#define WFS_CDM_PSNOTEMPTY
#define WFS_CDM_PSUNKNOWN
#define WFS_CDM_PSNOTSUPPORTED
                                                                                                              (0)
                                                                                                              (1)
                                                                                                              (2)
                                                                                                              (3)
 /* values of WFSCDMOUTPOS.fwTransport */
#define WFS_CDM_TPOK
#define WFS_CDM_TPINOP
#define WFS_CDM_TPUNKNOWN
#define WFS_CDM_TPNOTSUPPORTED
                                                                                                              (0)
                                                                                                              (1)
                                                                                                              (2)
                                                                                                              (3)
 /* values of WFSCDMOUTPOS.fwTransportStatus */
 #define WFS_CDM_TPSTATEMPTY
#define WFS_CDM_TPSTATNOTEMPTY
#define WFS_CDM_TPSTATNOTEMPTYCUST
                                                                                                              (0)
                                                                                                             (1)
                                                                                                             (2)
 #define
                     WFS CDM TPSTATNOTEMPTY UNK
                                                                                                             (3)
 #define
                     WFS CDM TPSTATNOTSUPPORTED
                                                                                                              (4)
 /* values of WFSCDMOUTPOS.fwJammedShutterPosition */
```

```
#define WFS_CDM_SHUTTERPOS_NOTSUPPORTED
#define WFS_CDM_SHUTTERPOS_NOTJAMMED
#define WFS_CDM_SHUTTERPOS_OPEN
#define WFS_CDM_SHUTTERPOS_PARTIALLY_OPEN
#define WFS_CDM_SHUTTERPOS_CLOSED
#define WFS_CDM_SHUTTERPOS_UNKNOWN
                                                                                                               (0)
                                                                                                               (1)
                                                                                                               (2)
                                                                                                              (3)
                                                                                                              (4)
                                                                                                              (5)
/* values of WFSCDMCAPS.fwType */
#define WFS_CDM_TELLERBILL
#define WFS_CDM_SELFSERVICEBILL
#define WFS_CDM_TELLERCOIN
#define WFS_CDM_SELFSERVICECOIN
                                                                                                             (0)
                                                                                                              (1)
                                                                                                               (2)
                                                                                                               (3)
/* values of WFSCDMCAPS.fwRetractAreas,
                       WFSCDMRETRACT.usRetractArea */
#define WFS_CDM_RA_RETRACT
#define WFS_CDM_RA_TRANSPORT
#define WFS_CDM_RA_STACKER
#define WFS_CDM_RA_REJECT
#define WFS_CDM_RA_NOTSUPP
                                                                                                               (0 \times 0.001)
                                                                                                               (0x0002)
                                                                                                               (0x0004)
                                                                                                              (0x0008)
                                                                                                               (0x0010)
#define WFS CDM RA_ITEMCASSETTE
                                                                                                               (0x0020)
/* values of WFSCDMCAPS.fwRetractTransportActions,
                       WFSCDMCAPS.fwRetractStackerActions */
#define WFS_CDM_PRESENT
#define WFS_CDM_RETRACT
#define WFS_CDM_REJECT
#define WFS_CDM_NOTSUPP
#define WFS_CDM_ITEMCASSETTE
                                                                                                               (0 \times 0001)
                                                                                                               (0x0002)
                                                                                                               (0x0004)
                                                                                                               (0 \times 0.008)
                                                                                                               (0x0010)
/* values of WFSCDMCAPS.fwMoveItems */
#define
                      WFS CDM FROMCU
                                                                                                               (0x0001)
#define WFS_CDM_FROMCU
#define WFS_CDM_TOCU
#define WFS_CDM_TOTRANSPORT
#define WFS_CDM_TOSTACKER
                                                                                                               (0 \times 0002)
                                                                                                               (0x0004)
                                                                                                               (0x0008)
/* values of WFSCDMCASHUNIT.usType */
#define WFS_CDM_TYPENA
#define WFS_CDM_TYPEREJECTCASSETTE
                                                                                                               (1)
                                                                                                               (2)
#define WFS_CDM_TYPEREJECTCASSETTE
#define WFS_CDM_TYPEBILLCASSETTE
#define WFS_CDM_TYPECOINCYLINDER
#define WFS_CDM_TYPECOINDISPENSER
#define WFS_CDM_TYPECOUPON
#define WFS_CDM_TYPECOUPON
#define WFS_CDM_TYPEDOCUMENT
#define WFS_CDM_TYPEDOCUMENT
                                                                                                               (3)
                                                                                                               (4)
                                                                                                               (5)
                                                                                                              (6)
                                                                                                              (7)
                                                                                                               (8)
#define WFS_CDM_TYPEREPCONTAINER #define WFS_CDM_TYPERECYCLING
                                                                                                               (11)
                                                                                                               (12)
/* values of WFSCDMCASHUNIT.usStatus */
#define WFS_CDM_STATCUOK
#define WFS_CDM_STATCUFULL
#define WFS_CDM_STATCUHIGH
#define WFS_CDM_STATCULOW
#define WFS_CDM_STATCUEMPTY
#define WFS_CDM_STATCUINOP
#define WFS_CDM_STATCUINOP
                                                                                                               (0)
                                                                                                               (1)
                                                                                                               (2)
                                                                                                               (3)
                                                                                                               (4)
                                                                                                               (5)
#define WFS_CDM_STATCUMISSING
#define WFS_CDM_STATCUNOVAL
#define WFS_CDM_STATCUNOREF
#define WFS_CDM_STATCUMANIP
                                                                                                               (6)
                                                                                                               (7)
                                                                                                               (8)
                                                                                                               (9)
/* values of WFSCDMMIXTYPE.usMixType */
#define
                     WFS CDM MIXALGORITHM
                                                                                                               (1)
```

```
#define
              WFS CDM MIXTABLE
                                                                         (2)
/* values of WFSCDMMIXTYPE.usMixNumber */
              WFS CDM INDIVIDUAL
#define
                                                                         (0)
/* values of WFSCDMMIXTYPE.usSubType (predefined mix algorithms) */
              WFS_CDM_MIX_MINIMUM_NUMBER_OF_BILLS (1)
WFS_CDM_MIX_EQUAL_EMPTYING_OF_CASH_UNITS (2)
#define
#define
#define WFS CDM MIX MAXIMUM NUMBER OF CASH UNITS (3)
/* values of WFSCDMPRESENTSTATUS.wPresentState */
#define
               WFS CDM PRESENTED
                                                                          (1)
            WFS CDM_NOTPRESENTED
#define
                                                                         (2)
              WFS_CDM_UNKNOWN
                                                                         (3)
#define
/* values of WFSCDMDISPENSE.fwPosition,
                 WFSCDMCAPS.fwPositions,
                 WFSCDMOUTPOS.fwPosition,
                 WFSCDMTELLERDETAILS.fwOutputPosition,
                 WFSCDMPHYSICALCU.fwPosition */
#define WFS_CDM_POSNULL
#define WFS_CDM_POSLEFT
#define WFS_CDM_POSRIGHT
#define WFS_CDM_POSCENTER
#define WFS_CDM_POSTOP
#define WFS_CDM_POSBOTTOM
#define WFS_CDM_POSFRONT
#define WFS_CDM_POSREAR
                                                                         (0x0000)
                                                                          (0x0001)
                                                                         (0x0002)
                                                                         (0 \times 0.004)
                                                                         (0x0040)
                                                                         (0 \times 0.080)
                                                                         (0x0800)
                                                                         (0x1000)
/* additional values of WFSCDMPHYSICALCU.fwPosition */
#define WFS CDM POSREJECT
                                                                         (0x0100)
/* values of WFSCDMTELLERDETAILS.ulInputPosition */
#define WFS_CDM_POSINLEFT
#define WFS_CDM_POSINRIGHT
#define WFS_CDM_POSINCENTER
#define WFS_CDM_POSINTOP
#define WFS_CDM_POSINBOTTOM
#define WFS_CDM_POSINFRONT
                                                                         (0x0001)
                                                                         (0 \times 0002)
                                                                         (0 \times 0.004)
                                                                         (0x0008)
                                                                         (0x0010)
                                                                         (0x0020)
#define WFS_CDM_POSINREAR
                                                                         (0 \times 0040)
/* values of fwExchangeType */
               WFS CDM EXBYHAND
#define
                                                                         (0 \times 0.001)
#define
              WFS CDM EXTOCASSETTES
                                                                         (0x0002)
/* values of WFSCDMTELLERUPDATE.usAction */
#define
              WFS CDM CREATE TELLER
                                                                         (1)
#define WFS CDM MODIFY TELLER
                                                                         (2)
#define WFS CDM DELETE TELLER
                                                                         (3)
/* values of WFSCDMCUERROR.wFailure */
#define WFS_CDM_CASHUNITEMPTY
#define WFS_CDM_CASHUNITERROR
#define WFS_CDM_CASHUNITFULL
                                                                         (1)
                                                                         (2)
                                                                         (4)
#define WFS_CDM_CASHUNITLOCKED
#define WFS_CDM_CASHUNITINVALID
#define WFS_CDM_CASHUNITCONFIG
                                                                         (5)
                                                                         (6)
                                                                         (7)
#define
              WFS CDM CASHUNITNOTCONF
                                                                         (8)
/* values of lpusReason in WFS EXEE CDM NOTEERROR */
               WFS CDM DOUBLENOTEDETECTED
#define
                                                                         (1)
```

```
#define WFS_CDM_LONGNOTEDETECTED
#define WFS_CDM_SKEWEDNOTE
#define WFS_CDM_INCORRECTCOUNT
#define WFS_CDM_NOTESTOOCLOSE
#define WFS_CDM_OTHERNOTEERROR
                                                                    (2)
                                                                    (3)
                                                                    (4)
                                                                    (5)
                                                                    (6)
#define WFS_CDM_SHORTNOTEDETECTED
                                                                    (7)
/* values of WESCDMPREPAREDISPENSE.wAction */
#define
             WFS CDM START
                                                                    (1)
            WFS CDM_STOP
#define
                                                                    (2)
/* values of WFSCDMSTATUS.wAntiFraudModule */
#define
             WFS CDM AFMNOTSUPP
                                                                    (0)
#define WFS_CDM_AFMNOTSU
#define WFS_CDM_AFMOK
#define WFS_CDM_AFMINOP
                                                                    (1)
                                                                    (2)
#define WFS CDM AFMDEVICEDETECTED
                                                                    (3)
#define WFS CDM AFMUNKNOWN
                                                                    (4)
/* values of WFSCDMGETITEMINFO.usLevel,
                WFSCDMITEMINFOSUMMARY.usLevel,
                WFSCDMGETALLITEMSINFO.usLevel,
                WFSCDMITEMINFOALL.usLevel */
#define
             WFS CDM LEVEL 1
                                                            (1)
#define WFS_CDM_LEVEL_1
#define WFS_CDM_LEVEL_2
#define WFS_CDM_LEVEL_3
                                                            (2)
                                                            (3)
#define
            WFS_CDM_LEVEL_4
                                                            (4)
/* values of WFSCDMITEMINFOALL.usLevel */
             WFS CDM LEVEL ALL
                                                            (0)
/* values for WFSCDMGETITEMINFO.dwItemInfoType */
          WFS_CDM_ITEM_SERIALNUMBER
WFS_CDM_ITEM_SIGNATURE
#define
                                                            (0x00000001)
                                                            (0x00000002)
#define
#define
             WFS CDM ITEM IMAGEFILE
                                                            (0x00000004)
/* values of lpusReason in WFS EXEE CDM INCOMPLETERETRACT */
#define
             WFS CDM IRRETRACTFAILURE
                                                                    (1)
#define WFS_CDM_IRRETRACTAREAFULL
#define WFS_CDM_IRFOREIGNITEMSDETECTED
                                                                    (2)
                                                                    (3)
#define WFS_CDM_IRINVALIDBUNCH
                                                                    (4)
/* values for WFSCDMITEMINFOALL.wOnBlacklist */
            WFS_CDM_ONBLACKLIST
#define WFS_CDM_BLACKLIST
#define WFS_CDM_BLACKLISTUNKNOWN
                                                          (0x0001)
                                                          (0x0002)
                                                          (0x0003)
/* values for WFSCDMITEMINFOALL.wItemLocation */
#define
                                                          (0x0001)
             WFS CDM LOCATION DEVICE
#define WFS_CDM_LOCATION_CASHUNIT (0x0002)
#define WFS_CDM_LOCATION_CUSTOMER (0x0003)
#define WFS_CDM_LOCATION_UNKNOWN (0x0004)
#define WFS_CDM_LOCATION_CUSTOMEK
#define WFS_CDM_LOCATION_UNKNOWN
/* values for WFSCDMITEMINFOALL.wOnClassificationList */
            WFS_CDM_CLASSIFICATIONLIST_ON (0x0001)
WFS_CDM_CLASSIFICATIONLIST_NOTON (0x0002)
WFS_CDM_CLASSIFICATIONLIST_UNKNOWN (0x0003)
#define
#define
#define
/* values for WFSCDMITEMINFOALL.wItemDeviceLocation */
#define
               WFS CDM DEVLOC STACKER
                                                            (0x0001)
            WFS CDM DEVLOC OUTPUT
#define
                                                            (0 \times 0002)
```

```
WFS_CDM_DEVLOC_TRANSPORT (0x0003)
WFS_CDM_DEVLOC_UNKNOWN (0x0004)
#define
#define
/* XFS CDM Errors */
#define WFS ERR CDM INVALIDCURRENCY
                                                          (-(CDM SERVICE OFFSET + 0))
#define WFS ERR CDM INVALIDTELLERID
                                                         (-(CDM SERVICE OFFSET + 1))
#define WFS ERR CDM CASHUNITERROR
                                                         (-(CDM_SERVICE_OFFSET + 2))
#define WFS_ERR_CDM_INVALIDDENOMINATION #define WFS_ERR_CDM_INVALIDMIXNUMBER
                                                         (-(CDM_SERVICE_OFFSET + 3))
(-(CDM_SERVICE_OFFSET + 4))
#define WFS ERR CDM NOCURRENCYMIX
                                                         (-(CDM SERVICE OFFSET + 5))
#define WFS ERR CDM NOTDISPENSABLE
                                                         (-(CDM SERVICE OFFSET + 6))
#define WFS_ERR_CDM_TOOMANYITEMS
                                                         (-(CDM SERVICE OFFSET + 7))
#define WFS_ERR_CDM_UNSUPPOSITION
                                                         (-(CDM_SERVICE_OFFSET + 8))
#define WFS ERR CDM SAFEDOOROPEN
                                                         (-(CDM SERVICE OFFSET + 10))
                                                         (-(CDM SERVICE OFFSET + 12))
#define WFS ERR CDM SHUTTERNOTOPEN
#define WFS ERR CDM SHUTTEROPEN
                                                         (-(CDM SERVICE OFFSET + 13))
#define WFS ERR CDM SHUTTERCLOSED
                                                         (-(CDM SERVICE OFFSET + 14))
                                                         (-(CDM_SERVICE_OFFSET + 15))
#define WFS ERR CDM INVALIDCASHUNIT
#define WFS_ERR_CDM_NOITEMS
#define WFS_ERR_CDM_EXCHANGEACTIVE
                                                         (-(CDM_SERVICE_OFFSET + 16))
(-(CDM_SERVICE_OFFSET + 17))
                                                        (-(CDM SERVICE OFFSET + 18))
#define WFS ERR CDM NOEXCHANGEACTIVE
#define WFS ERR CDM SHUTTERNOTCLOSED
                                                        (-(CDM SERVICE OFFSET + 19))
#define WFS_ERR_CDM_PRERRORNOITEMS
                                                         (-(CDM_SERVICE_OFFSET + 20))
                                                         (-(CDM_SERVICE_OFFSET + 21))
(-(CDM_SERVICE_OFFSET + 22))
#define WFS_ERR_CDM_PRERRORITEMS
#define WFS ERR CDM PRERRORUNKNOWN
#define WFS ERR CDM ITEMSTAKEN
                                                         (-(CDM SERVICE OFFSET + 23))
#define WFS ERR CDM INVALIDMIXTABLE
                                                        (-(CDM SERVICE OFFSET + 27))
#define WFS_ERR_CDM_OUTPUTPOS_NOT_EMPTY
                                                        (-(CDM_SERVICE_OFFSET + 28))
#define WFS_ERR_CDM_INVALIDRETRACTPOSITION
                                                        (-(CDM_SERVICE_OFFSET + 29))
#define WFS_ERR_CDM_NOTRETRACTAREA
#define WFS_ERR_CDM_NOCASHBOXPRESENT
                                                         (-(CDM_SERVICE_OFFSET + 30))
(-(CDM_SERVICE_OFFSET + 33))
                                                         (-(CDM SERVICE OFFSET + 34))
#define WFS ERR CDM AMOUNTNOTINMIXTABLE
#define WFS ERR CDM ITEMSNOTTAKEN
                                                         (-(CDM SERVICE OFFSET + 35))
#define WFS_ERR_CDM_ITEMSLEFT
                                                         (-(CDM_SERVICE_OFFSET + 36))
#define WFS_ERR_CDM_INVALID_PORT
#define WFS_ERR_CDM_POWERSAVETOOSHORT
                                                         (-(CDM_SERVICE_OFFSET + 37))
(-(CDM_SERVICE_OFFSET + 38))
#define WFS ERR CDM POWERSAVEMEDIAPRESENT
                                                        (-(CDM SERVICE OFFSET + 39))
#define WFS ERR CDM POSITION NOT EMPTY
                                                        (-(CDM SERVICE OFFSET + 40))
#define WFS ERR CDM INCOMPLETERETRACT
                                                         (-(CDM SERVICE OFFSET + 41))
#define WFS_ERR_CDM_COMMANDUNSUPP
                                                         (-(CDM_SERVICE_OFFSET + 42))
#define WFS ERR CDM SYNCHRONIZEUNSUPP
                                                          (-(CDM SERVICE OFFSET + 43))
/*----*/
/* CDM Info Command Structures */
/*========*/
typedef struct _wfs_cdm_position
    WORD
                           fwPosition;
    WORD
                           fwShutter;
                           fwPositionStatus;
    WORD
    WORD
                           fwTransport;
    WORD
                           fwTransportStatus;
                           fwJammedShutterPosition;
} WFSCDMOUTPOS, *LPWFSCDMOUTPOS;
typedef struct wfs cdm status
    WORD
                           fwDevice:
    WORD
                          fwSafeDoor;
    WORD
                          fwDispenser;
                          fwIntermediateStacker;
    WORD
    LPWFSCDMOUTPOS
                           *lppPositions;
                           lpszExtra;
    LPSTR
    DWORD
                           dwGuidLights[WFS CDM GUIDLIGHTS SIZE];
    WORD
                           wDevicePosition;
    USHORT
                           usPowerSaveRecoveryTime;
                           wAntiFraudModule;
} WFSCDMSTATUS, *LPWFSCDMSTATUS;
```

```
typedef struct _wfs_cdm_caps
    WORD
                          wClass;
    WORD
                          fwType;
    WORD
                          wMaxDispenseItems;
    BOOL
                          bCompound;
    BOOL
                          bShutter;
    BOOL
                          bShutterControl;
    WORD
                          fwRetractAreas;
    WORD
                          fwRetractTransportActions;
    WORD
                          fwRetractStackerActions;
    BOOL
                          bSafeDoor;
    BOOL
                          bCashBox;
    BOOL
                          bIntermediateStacker;
    BOOT.
                          bItemsTakenSensor:
    WORD
                          fwPositions;
    WORD
                          fwMoveItems;
                          fwExchangeType;
    WORD
    LPSTR
                          lpszExtra;
                          dwGuidLights[WFS CDM GUIDLIGHTS SIZE];
    DWORD
    BOOL
                          bPowerSaveControl;
    BOOL
                          bPrepareDispense;
                          bAntiFraudModule;
    BOOL
    DWORD
                          dwItemInfoTypes;
    BOOL
                          bBlacklist;
    T.PDWORD
                          lpdwSynchronizableCommands;
                          bClassificationList;
} WFSCDMCAPS, *LPWFSCDMCAPS;
typedef struct wfs cdm physicalcu
                          lpPhysicalPositionName;
    LPSTR
    CHAR
                          cUnitID[5];
    ULONG
                          ulInitialCount;
    ULONG
                          ulCount;
    ULONG
                          ulRejectCount;
    III.ONG
                          ulMaximum:
    USHORT
                          usPStatus;
    BOOL
                          bHardwareSensor;
    ULONG
                          ulDispensedCount;
    ULONG
                          ulPresentedCount;
    ULONG
                          ulRetractedCount;
} WFSCDMPHCU, *LPWFSCDMPHCU;
typedef struct _wfs_cdm_cashunit
    USHORT
                          usNumber;
    USHORT
                          usType;
    LPSTR
                          lpszCashUnitName;
    CHAR
                          cUnitID[5];
                          cCurrencyID[3];
    CHAR
    ULONG
                          ulValues;
    ULONG
                          ulInitialCount;
    ULONG
                         ulCount;
    ULONG
                         ulRejectCount;
    ULONG
                         ulMinimum;
    ULONG
                          ulMaximum;
    BOOL
                          bAppLock;
    USHORT
                          usStatus;
    USHORT
                          usNumPhysicalCUs;
    LPWFSCDMPHCU
                          *lppPhysical;
    ULONG
                          ulDispensedCount;
    ULONG
                          ulPresentedCount;
    ULONG
                          ulRetractedCount;
} WFSCDMCASHUNIT, *LPWFSCDMCASHUNIT;
typedef struct _wfs_cdm_cu_info
```

usTellerID;

USHORT

```
USHORT usCount;
LPWFSCDMCASHUNIT *lppList;
} WFSCDMCUINFO, *LPWFSCDMCUINFO;
typedef struct _wfs_cdm_teller_info
   USHORT
                         usTellerID;
   CHAR
                         cCurrencyID[3];
} WFSCDMTELLERINFO, *LPWFSCDMTELLERINFO;
typedef struct wfs cdm teller totals
   CHAR
                        cCurrencyID[3];
   ULONG
                         ulItemsReceived;
   ULONG
                         ulItemsDispensed;
   ULONG
                         ulCoinsReceived;
   ULONG
                         ulCoinsDispensed;
   ULONG
                        ulCashBoxReceived;
   ULONG
                         ulCashBoxDispensed;
} WFSCDMTELLERTOTALS, *LPWFSCDMTELLERTOTALS;
typedef struct _wfs_cdm_teller_details
   USHORT
                        usTellerID;
   ULONG
                         ulInputPosition;
   WORD
                         fwOutputPosition;
   LPWFSCDMTELLERTOTALS *lppTellerTotals;
} WFSCDMTELLERDETAILS, *LPWFSCDMTELLERDETAILS;
typedef struct _wfs_cdm_currency_exp
   CHAR
                          cCurrencyID[3];
   SHORT
                         sExponent;
} WFSCDMCURRENCYEXP, *LPWFSCDMCURRENCYEXP;
typedef struct _wfs_cdm_mix_type
   USHORT
                         usMixNumber:
   USHORT
                        usMixType;
   USHORT
                        usSubType;
   LPSTR
                         lpszName;
} WFSCDMMIXTYPE, *LPWFSCDMMIXTYPE;
typedef struct _wfs_cdm_mix_row
   ULONG
                         ulAmount;
   LPUSHORT
                          lpusMixture;
} WFSCDMMIXROW, *LPWFSCDMMIXROW;
typedef struct _wfs_cdm_mix_table
                         usMixNumber;
   USHORT
   LPSTR
                         lpszName;
                        usRows;
   USHORT
   USHORT
                        usCols;
                        lpulMixHeader;
   LPULONG
   LPWFSCDMMIXROW *lppMixRows;
} WFSCDMMIXTABLE, *LPWFSCDMMIXTABLE;
typedef struct _wfs_cdm_denomination
   CHAR
                         cCurrencyID[3];
   ULONG
                         ulAmount;
   USHORT
                         usCount;
   LPULONG
                         lpulValues;
                         ulCashBox:
} WFSCDMDENOMINATION, *LPWFSCDMDENOMINATION;
typedef struct _wfs_cdm_present_status
```

```
LPWFSCDMDENOMINATION lpDenomination;
   WORD
                         wPresentState;
                          lpszExtra;
} WFSCDMPRESENTSTATUS, *LPWFSCDMPRESENTSTATUS;
typedef struct wfs cdm signature
   ULONG
                          ulLength;
   LPVOID
                          lpData;
} WFSCDMSIGNATURE, *LPWFSCDMSIGNATURE;
typedef struct wfs cdm get item info
   USHORT
                          usLevel:
   USHORT
                          usIndex;
   DWORD
                          dwItemInfoType;
} WFSCDMGETITEMINFO, *LPWFSCDMGETITEMINFO;
typedef struct _wfs_cdm_item_info
   CHAR
                          cCurrencyID[3];
   ULONG
                         ulValue;
   USHORT
                         usRelease;
   T.PWSTR
                         lpszSerialNumber;
                       lpSignature;
   LPWFSCDMSIGNATURE
   LPSTR
                          lpszImageFileName;
} WFSCDMITEMINFO, *LPWFSCDMITEMINFO;
typedef struct _wfs_cdm_get_all_items_info
                          usLevel;
} WFSCDMGETALLITEMSINFO, *LPWFSCDMGETALLITEMSINFO;
typedef struct wfs cdm item info all
   USHORT
                          usLevel;
   CHAR
                          cCurrencyID[3];
   ULONG
                         ulValue:
   USHORT
                         usRelease;
   LPWSTR
                         lpszSerialNumber;
                          lpszImageFileName;
   LPSTR
   WORD
                          wOnBlacklist;
   WORD
                          wItemLocation;
   USHORT
                         usNumber;
   WORD
                         wOnClassificationList;
   WORD
                         wItemDeviceLocation;
} WFSCDMITEMINFOALL, *LPWFSCDMITEMINFOALL;
typedef struct _wfs_cdm_all_items_info
   USHORT usCount;
LPWFSCDMITEMINFOALL *lppItemsList;
} WFSCDMALLITEMSINFO, *LPWFSCDMALLITEMSINFO;
typedef struct wfs cdm classification element
   LPWSTR
                          lpszSerialNumber;
   CHAR
                          cCurrencyID[3];
   ULONG
                          ulValue;
   USHORT
                          usLevel:
                          bUnfit;
} WFSCDMCLASSIFICATIONELEMENT, *LPWFSCDMCLASSIFICATIONELEMENT;
typedef struct _wfs_cdm_classification_list
   LPWSTR
                          lpszVersion;
   USHORT
                         usCount;
   LPWFSCDMCLASSIFICATIONELEMENT *lppClassificationElements;
} WFSCDMCLASSIFICATIONLIST, *LPWFSCDMCLASSIFICATIONLIST;
```

```
/*=============*/
/* CDM Execute Command Structures */
typedef struct _wfs_cdm_denominate
   USHORT
                       usTellerID;
   USHORT usMixNumber;
LPWFSCDMDENOMINATION lpDenomination;
} WFSCDMDENOMINATE, *LPWFSCDMDENOMINATE;
typedef struct wfs cdm dispense
   USHORT
                       usTellerID:
   USHORT
                        usMixNumber;
   WORD
                        fwPosition;
   BOOL
                       bPresent;
   LPWFSCDMDENOMINATION lpDenomination;
} WFSCDMDISPENSE, *LPWFSCDMDISPENSE;
typedef struct wfs cdm physical cu
   BOOL
                        bEmptyAll;
   WORD
                        fwPosition;
   LPSTR
                        lpPhysicalPositionName;
} WFSCDMPHYSICALCU, *LPWFSCDMPHYSICALCU;
typedef struct wfs cdm counted phys cu
   LPSTR
                       lpPhysicalPositionName;
   CHAR
                        cUnitId[5];
   ULONG
                        ulDispensed;
   ULONG
                       ulCounted:
                       usPStatus;
} WFSCDMCOUNTEDPHYSCU, *LPWFSCDMCOUNTEDPHYSCU;
typedef struct _wfs_cdm_count
   USHORT
                       usNumPhysicalCUs;
   LPWFSCDMCOUNTEDPHYSCU *lppCountedPhysCUs;
} WFSCDMCOUNT, *LPWFSCDMCOUNT;
typedef struct _wfs_cdm_retract
   WORD
                       fwOutputPosition;
   USHORT
                        usRetractArea;
   USHORT
                        usIndex;
} WFSCDMRETRACT, *LPWFSCDMRETRACT;
typedef struct _wfs_cdm_item_number
   CHAR
                        cCurrencyID[3];
   ULONG
                        ulValues;
   USHORT
                       usRelease:
   ULONG
                       ulCount;
   USHORT
                       usNumber;
} WFSCDMITEMNUMBER, *LPWFSCDMITEMNUMBER;
typedef struct _wfs_cdm_item_number_list
                      usNumOfItemNumbers;
*lppItemNumber;
   USHORT
   LPWFSCDMITEMNUMBER
} WFSCDMITEMNUMBERLIST, *LPWFSCDMITEMNUMBERLIST;
typedef struct _wfs_cdm_teller_update
   USHORT
                       usAction;
   LPWFSCDMTELLERDETAILS lpTellerDetails;
} WFSCDMTELLERUPDATE, *LPWFSCDMTELLERUPDATE;
```

```
typedef struct _wfs_cdm_start_ex
                       fwExchangeType;
   USHORT
                       usTellerID;
   USHORT
                       usCount;
   LPUSHORT
                        lpusCUNumList;
} WFSCDMSTARTEX, *LPWFSCDMSTARTEX;
typedef struct wfs cdm itemposition
   USHORT
                       usNumber;
   LPWFSCDMRETRACT
                      lpRetractArea;
   WORD
                       fwOutputPosition;
} WFSCDMITEMPOSITION, *LPWFSCDMITEMPOSITION;
typedef struct _wfs_cdm_calibrate
   USHORT
                       usNumber:
   USHORT
                       usNumOfBills;
   LPWFSCDMITEMPOSITION *lpPosition;
} WFSCDMCALIBRATE, *LPWFSCDMCALIBRATE;
typedef struct _wfs_cdm_set_guidlight
   WORD
                        wGuidLight;
   DWORD
                        dwCommand:
} WFSCDMSETGUIDLIGHT, *LPWFSCDMSETGUIDLIGHT;
typedef struct _wfs_cdm_power_save_control
   USHORT
                        usMaxPowerSaveRecoveryTime;
} WFSCDMPOWERSAVECONTROL, *LPWFSCDMPOWERSAVECONTROL;
typedef struct _wfs_cdm_prepare_dispense
   WORD
                        wAction;
} WFSCDMPREPAREDISPENSE, *LPWFSCDMPREPAREDISPENSE;
typedef struct _wfs_cdm_blacklist element
   LPWSTR
                        lpszSerialNumber;
   CHAR
                        cCurrencyID[3];
   ULONG
                       ulValue;
} WFSCDMBLACKLISTELEMENT, *LPWFSCDMBLACKLISTELEMENT;
typedef struct _wfs_cdm_blacklist
   LPWSTR
                       lpszVersion;
                       usCount;
   LPWFSCDMBLACKLISTELEMENT *lppBlacklistElements;
} WFSCDMBLACKLIST, *LPWFSCDMBLACKLIST;
typedef struct _wfs_cdm_synchronize_command
   DWORD
                        dwCommand;
   LPVOID
                       lpCmdData;
} WFSCDMSYNCHRONIZECOMMAND, *LPWFSCDMSYNCHRONIZECOMMAND;
/*----*/
/* CDM Message Structures */
/*=======*/
typedef struct _wfs_cdm_cu_error
                       wFailure;
   LPWFSCDMCASHUNIT lpCashUnit;
} WFSCDMCUERROR, *LPWFSCDMCUERROR;
typedef struct wfs cdm counts changed
```

```
{
    USHORT
                         usCount;
    LPUSHORT
                           lpusCUNumList;
} WFSCDMCOUNTSCHANGED, *LPWFSCDMCOUNTSCHANGED;
typedef struct _wfs_cdm_device_position
    WORD
                          wPosition;
} WFSCDMDEVICEPOSITION, *LPWFSCDMDEVICEPOSITION;
typedef struct _wfs_cdm_power_save_change
USHORT usPowerSaveRecoveryTime; } WFSCDMPOWERSAVECHANGE, *LPWFSCDMPOWERSAVECHANGE;
typedef struct _wfs_cdm_item_info_summary
    USHORT
                          usLevel;
    USHORT
                          usNumOfItems;
} WFSCDMITEMINFOSUMMARY, *LPWFSCDMITEMINFOSUMMARY;
typedef struct _wfs_cdm_incomplete_retract
    WFSCDMITEMNUMBERLIST lpItemNumberList;
                           usReason;
} WFSCDMINCOMPLETERETRACT, *LPWFSCDMINCOMPLETERETRACT;
typedef struct wfs cdm shutter status changed
    WORD
                           fwPosition;
    WORD
                           fwShutter;
} WFSCDMSHUTTERSTATUSCHANGED, *LPWFSCDMSHUTTERSTATUSCHANGED;
/* restore alignment */
#pragma pack (pop)
#ifdef __cplusplus
}    /*extern "C"*/
#endif
#endif /* INC XFSCDM H */
```